



Safety Data Sheet

Material Name: PERFORMANCE PLUS DEXOS SAE 0W-20, 5W-20, 5W-30
MOTOR OIL

SDS ID: 820172

*** Section 1 - Identification ***

Product Identifier

PERFORMANCE PLUS DEXOS SAE 0W-20, 5W-20, 5W-30 MOTOR OIL

Product Code

Prefix 21

Synonyms

Petroleum oil; Lube oil; Petroleum hydrocarbon; Lubricant.

Recommended Use

For lubricating passenger car motors. If these products are used in combination with other products, refer to the Material Safety Data Sheet for those products.

Restrictions on Use

None known.

FOR PRODUCT MANUFACTURED IN THE U.S.A.:**MANUFACTURER**

Safety-Kleen Systems, Inc.
42 Longwater Drive
Norwell, MA 02061-9149
U.S.A.

SUPPLIER (in Canada)

Safety-Kleen Canada, Inc.
25 Regan Road
Brampton, Ontario, L7A 1B2
Canada

FOR PRODUCT MANUFACTURED IN CANADA:**MANUFACTURER**

Safety-Kleen Canada Inc.
25 Regan Road
Brampton, Ontario, L7A 1B2
Canada

SUPPLIER (in the U.S.A.)

Safety-Kleen Systems, Inc.
42 Longwater Drive
Norwell, MA 02061-9149
U.S.A.

www.safety-kleen.com

Phone: 1-800-669-5740

Emergency Phone #: 1-800-468-1760

Issue Date

September 15, 2021

Supersedes Issue Date

March 20, 2017

Original Issue Date

February 25, 2014

*** Section 2 - Hazard(s) Identification ***

Classification in accordance with Schedule 1 of Canada's Hazardous Products Regulations (HPR) (SOR/2015-17) and paragraph (d) of 29 CFR 1910.1200 in the United States

Not hazardous according to classification criteria.

GHS LABEL ELEMENTS**Symbol(s)**

None needed according to classification criteria.

Signal Word

None needed according to classification criteria.

Hazard Statement(s)

None needed according to classification criteria.

Precautionary Statement(s)**Prevention**

None needed according to classification criteria.

Response

None needed according to classification criteria.

Storage

None needed according to classification criteria.

Safety Data Sheet

Material Name: PERFORMANCE PLUS DEXOS SAE 0W-20, 5W-20, 5W-30
MOTOR OIL

SDS ID: 820172

Disposal

Dispose in accordance with all applicable regulations.

Hazard(s) Not Otherwise Classified

Repeated exposure may cause skin dryness or cracking. When aerosolizing, misting, or heating these products, high concentrations of generated vapor or mist may irritate the respiratory tract (nose, throat, and lungs).

*** Section 3 - Composition / Information on Ingredients ***

CAS	Component	Percent
64741-88-4	Petroleum distillates, solvent-refined heavy paraffinic	0-35
64742-01-4	Residual oils (petroleum), solvent refined	0-35
64742-57-0	Residual oils (petroleum), hydrotreated	0-35
64742-62-7	Residual oils (petroleum), solvent dewaxed	0-35
72623-83-7	Lubricating oils (petroleum), C>25, hydrotreated bright stock	0-35
64742-58-1	Lubricating oils, petroleum, hydrotreated spent	5-45
178603-65-1	Gas oils, petroleum, vacuum, hydrocracked, hydroisomerized, hydrogenated, C20-40, branched and cyclic, high viscosity index	0-45
Not available	Mineral Oil	5-15
68649-42-3	Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts	0.5-1

*** Section 4 - First Aid Measures ***

Description of Necessary Measures

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if needed.

Skin

IF ON SKIN: Wash skin with plenty of soap and water. Get medical attention, if needed.

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. Get medical attention if needed.

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.

Most Important Symptoms/Effects

Acute

No information on significant adverse effects.

Delayed

Repeated exposure may cause skin dryness or cracking.

Indication of Immediate Medical Attention and Special Treatment Needed, If Needed

Treat symptomatically and supportively.

*** Section 5 - Fire-Fighting Measures ***

Suitable Extinguishing Media

Carbon dioxide, regular foam, dry chemical, water spray, or water fog. Water or foam may cause frothing.

Unsuitable Extinguishing Media

None known.

Specific Hazards Arising from the Chemical

Negligible fire hazard. "Empty" containers may retain residue and can be dangerous. Product is not sensitive to mechanical impact or static discharge.

Hazardous Combustion Products

Decomposition and combustion materials may be toxic. Burning may produce aldehydes, hydrogen sulfide, alkyl mercaptans, sulfides, carbon monoxide, and oxides of sulfur, calcium and zinc and other unidentified organic compounds.

Safety Data Sheet

Material Name: PERFORMANCE PLUS DEXOS SAE 0W-20, 5W-20, 5W-30
MOTOR OIL

SDS ID: 820172

Special Protective Equipment and Precautions for Firefighters

A positive-pressure, self-contained breathing apparatus (SCBA) and full-body protective equipment are required for fire emergencies.

Fire Fighting Measures

Move container from fire area if it can be done without risk. Cool containers with water spray until well after the fire is out. Stay away from the ends of tanks. Keep unnecessary people away, isolate hazard area and deny entry.

* * * Section 6 - Accidental Release Measures * * *

Personal Precautions, Protective Equipment and Emergency Procedures

Wear personal protective clothing and equipment, see Section 8. Avoid release to the environment.

Methods and Materials for Containment and Clean Up

Remove all ignition sources. Do not touch or walk through spilled product. Stop leak if you can do it without risk. Wear protective equipment and provide engineering controls as specified in Section 9: Exposure Controls/Personnel Protection. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Ventilate area and avoid breathing vapor or mist. Contain spill away from surface water and sewers. Contain spill as a liquid for possible recovery, or sorb with compatible sorbent material and shovel with a clean, sparkproof tool into a sealable container for disposal. Additionally, for large spills: Dike far ahead of liquid spill for collection and later disposal.

There may be specific federal regulatory reporting requirements associated with spills, leaks, or releases of this product. Also see Section 15: Regulatory Information.

* * * Section 7 - Handling and Storage * * *

Precautions for Safe Handling

Keep away from sparks or flame. Where flammable mixtures may be present, equipment safe for such locations should be used. Use clean tools. When transferring large volumes of product, metal containers, including trucks and tank cars, should be grounded and bonded. These products have a low vapor pressure and are not expected to present an inhalation hazard under normal temperatures and pressures. However, when aerosolizing, misting, or heating these products, do not breathe vapor or mist. Use in a well ventilated area. Avoid contact with eyes, skin, clothing, and shoes.

Conditions for Safe Storage, Including Any Incompatibilities

Keep container tightly closed when not in use and during transport. Store containers in a cool, dry place. Store locked up. Do not pressurize, cut, weld, braze, solder, drill, or grind containers. Keep containers away from flame, sparks, static electricity, or other sources of ignition. Empty product containers may retain product residue and can be dangerous.

Incompatibilities

Oxidizing materials, acids, reactive halogens.

* * * Section 8 - Exposure Controls / Personal Protection * * *

Component Exposure Limits

Canada, ACGIH, OSHA, and NIOSH have not developed exposure limits for any of this product's components.

Appropriate Engineering Controls

Provide general ventilation needed to maintain concentration of vapor or mist below applicable exposure limits. Where adequate general ventilation is unavailable, use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below applicable exposure limits.

Individual Protective Measures, such as Personal Protective Equipment

Protective equipment should be selected based upon the conditions under which this material is used. A hazard assessment of the work area for PPE requirements should be conducted by a qualified professional pursuant to regulatory requirements.

The following PPE should be considered the minimum required: safety glasses, gloves, lab coat, or apron.

Eyes/Face Protection

Wear safety glasses. Additional protection like goggles, face shields, or respirators may be needed dependent upon anticipated use and concentrations of mists or vapors. Eye wash fountain and emergency showers are recommended.

Contact lens use is not recommended

Skin Protection/Glove Recommendations

Where skin contact is likely, wear chemical impervious protective gloves; use of natural rubber or equivalent gloves is not recommended.

Safety Data Sheet

Material Name: PERFORMANCE PLUS DEXOS SAE 0W-20, 5W-20, 5W-30
MOTOR OIL

SDS ID: 820172

Respiratory Protection

No respirator is required under normal conditions of use. A respiratory protection program which meets USA's OSHA General Industry Standard 29 CFR 1910.134 or Canada's CSA Standard Z94.4-M1982 requirements must be followed whenever workplace conditions warrant a respirator's use. Consult a qualified Industrial Hygienist or Safety Professional for respirator selection guidance.

* * * Section 9 - Physical & Chemical Properties * * *

Appearance	Amber liquid.	Physical State	liquid
Odor	Petroleum odor.	Color	amber
Odor Threshold	Not available	pH	Not available
Melting Point	Not available	Boiling Point	246 °C (475 °F)
Boiling Point Range	Not available	Freezing point	Not available
Evaporation Rate	Not available	Flammability (solid, gas)	Not available
Autoignition Temperature	Not available	Flash Point	Not available
Lower Explosive Limit	Not available	Decomposition temperature	Not available
Upper Explosive Limit	Not available	Vapor Pressure	<0.1 mmHg @ 68 °F (20° C)
Vapor Density (air=1)	Not available	Specific Gravity (water=1)	0.87 (Approximate Water = 1)
Water Solubility	Insoluble	Partition coefficient: n-octanol/water	Not available
Viscosity	>20.5 mm ² /s 40 °C (104 °F)	Kinematic viscosity	Not available
Solubility (Other)	Not available	Density	7.3 lb/gal (US Approximate)
Physical Form	liquid	Molecular Weight	Not available
OSHA Flammability Class	Not flammable		

Other Property Information

No information is available.

* * * Section 10 - Stability & Reactivity * * *

Reactivity

No reactivity hazard is expected.

Chemical Stability

Stable under normal temperatures and pressures.

Possibility of Hazardous Reactions

Will not polymerize.

Conditions To Avoid

Avoid sparks or flame when not in use.

Incompatible Materials

Avoid oxidizing agents, acids and reactive halogens.

Hazardous Decomposition Products

None under normal temperatures and pressures.

Safety Data Sheet

Material Name: PERFORMANCE PLUS DEXOS SAE 0W-20, 5W-20, 5W-30
MOTOR OIL

SDS ID: 820172

*** Section 11 - Toxicological Information ***

Toxicity Data and Information

Component Analysis - LD50/LC50

Petroleum distillates, solvent-refined heavy paraffinic (64741-88-4)

Dermal LD50 Rabbit >2000 mg/kg; Inhalation LC50 Rat 2.18 mg/L 4 h; Oral LD50 Rat >5000 mg/kg

Residual oils (petroleum), solvent refined (64742-01-4)

Dermal LD50 Rabbit >2000 mg/kg; Inhalation LC50 Rat 2.18 mg/L 4 h; Oral LD50 Rat >5000 mg/kg

Residual oils (petroleum), solvent dewaxed (64742-62-7)

Dermal LD50 Rabbit >2000 mg/kg; Inhalation LC50 Rat 2.18 mg/L 4 h; Oral LD50 Rat >5000 mg/kg

Lubricating oils (petroleum), C>25, hydrotreated bright stock (72623-83-7)

Oral LD50 Rat >5000 mg/kg

Lubricating oils, petroleum, hydrotreated spent (64742-58-1)

Dermal LD50 Rabbit >4480 mg/kg; Oral LD50 Rat >2000 mg/kg

Lubricating oils, petroleum, C20-50, hydrotreated neutral oil-based (72623-87-1)

Dermal LD50 Rabbit >2000 mg/kg; Inhalation LC50 Rat 2.18 mg/L 4 h; Oral LD50 Rat >5000 mg/kg

Information on Likely Routes of Exposure

Inhalation

When aerosolizing, misting, or heating these products, high concentrations of generated vapor or mist may irritate the respiratory tract (nose, throat, and lungs).

Ingestion

May be harmful if swallowed.

Skin Contact

No information on significant adverse effects.

Eye Contact

No information on significant adverse effects.

Immediate Effects

No information on significant adverse effects.

Delayed Effects

No information on significant adverse effects.

Irritation/Corrosivity

May cause slight skin and respiratory irritation.

Respiratory Sensitization

No information available for the products.

Skin Sensitization

No information available for the product.

Carcinogenicity

Component Carcinogenicity

None of this product's components are listed by ACGIH, IARC, OSHA, NIOSH, or NTP.

Germ Cell Mutagenicity

No information available for the product.

Teratogenicity

No information available for the product.

Reproductive Effects

No information available for the product.

Specific Target Organ Effects - Single Exposure

No information on significant adverse effects.

Specific Target Organ Effects - Repeated Exposure

No information on significant adverse effects.

Aspiration Hazard

No data available.

Safety Data Sheet

Material Name: PERFORMANCE PLUS DEXOS SAE 0W-20, 5W-20, 5W-30
MOTOR OIL

SDS ID: 820172

Medical Conditions Aggravated by Exposure

Individuals with pre-existing respiratory tract (nose, throat, and lungs), eye, and/or skin disorders may have increased susceptibility to the effects of exposure.

***** Section 12 - Ecological Information *****

Ecotoxicity

Harmful to aquatic life.

Component Analysis - Ecotoxicity - Aquatic Toxicity

Lubricating oils, petroleum, hydrotreated spent	64742-58-1
Fish:	LC50 96 h Brachydanio rerio 79.6 mg/L [semi-static]; LC50 96 h Pimephales promelas 3.2 mg/L [semi-static]
Petroleum distillates, solvent-refined heavy paraffinic	64741-88-4
Fish:	LC50 96 h Oncorhynchus mykiss >5000 mg/L
Invertebrate:	EC50 48 h Daphnia magna >1000 mg/L IUCLID
Residual oils, petroleum, solvent-refined	64742-01-4
Fish:	LC50 96 h Oncorhynchus mykiss >5000 mg/L
Invertebrate:	EC50 48 h Daphnia magna >1000 mg/L IUCLID
Residual oils (petroleum), solvent dewaxed	64742-62-7
Fish:	LC50 96 h Oncorhynchus mykiss >5000 mg/L
Invertebrate:	EC50 48 h Daphnia magna >1000 mg/L IUCLID
Lubricating oils, petroleum, C>25, hydrotreated bright stock-based	72623-83-7
Fish:	LC50 96 h Lepomis macrochirus >10000 mg/L

Persistence and Degradability

No information available for the product.

Bioaccumulation Potential

No information available for the product.

Mobility in Soil

No information available for the product.

Other Adverse Effects

***** Section 13 - Disposal Considerations *****

Disposal Methods

Dispose in accordance with federal, state, provincial, and local regulations. Regulations may also apply to empty containers. The responsibility for proper waste disposal lies with the owner of the waste. Contact Safety-Kleen regarding proper recycling or disposal.

These products, if discarded, are not expected to be a characteristic or listed hazardous waste. If recycled as used oil in the USA, they can be managed in accordance with the used oil exemption under 40 CFR Part 279. Processing, use, or contamination by the user may change the waste code(s) applicable to the disposal of these products.

Safety Data Sheet

Material Name: PERFORMANCE PLUS DEXOS SAE 0W-20, 5W-20, 5W-30
MOTOR OIL

SDS ID: 820172

*** Section 14 - Transport Information ***

Emergency Response Guide Number

Not applicable.

DOT: Not regulated for transport.

IATA Information: Not regulated for transport.

IMDG Information: Not regulated for transport.

TDG Information: Not regulated for transport.

International Bulk Chemical Code

This material does not contain any chemicals required by the IBC Code to be identified as dangerous chemicals in bulk.

*** Section 15 - Regulatory Information ***

Volatile Organic Compounds (As Regulated)

Negligible as per U.S EPA 40 CFR 51.100(s)

Canada Regulations

CEPA - Priority Substances List

None of this product's components are on the list.

Ozone Depleting Substances

None of this product's components are on the list.

Council of Ministers of the Environment - Soil Quality Guidelines

None of this product's components are on the list.

Council of Ministers of the Environment - Water Quality Guidelines

None of this product's components are on the list.

U.S. Federal Regulations

None of this products components are listed under SARA Sections 302/304 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), CERCLA (40 CFR 302.4), TSCA 12(b), or require an OSHA process safety plan.

SARA Section 311/312 (40 CFR 370 Subparts B and C) 2016 reporting categories

Acute Health: Yes **Chronic Health:** Yes **Fire:** No **Pressure:** No **Reactivity:** No

Component Analysis - Inventory

Residual oils, petroleum, solvent-refined (64742-01-4); Lubricating oils, petroleum, C>25, hydrotreated bright stock-based (72623-83-7)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR KECI - Annex 1	KR KECI - Annex 2	KR - REACH CCA	CN	NZ	MX	TW
Yes	DSL	EIN	Yes	Yes	No	No	Yes	No	No	Yes	Yes	No	Yes

Gas oils, petroleum, v Gas oils, petroleum, vacuum, hydrocracked, hydroisomerized, hydrogenated, C20-40, branched and cyclic, high viscosity index (178603-65-1)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR KECI - Annex 1	KR KECI - Annex 2	KR - REACH CCA	CN	NZ	MX	TW
Yes	DSL	No	No	No	No	No	No	No	No	Yes	No	No	Yes

Lubricating oils, petroleum, hydrotreated spent (64742-58-1); Petroleum distillates, solvent-refined heavy paraffinic (64741-88-4); Residual oils (petroleum), hydrotreated (64742-57-0); Residual oils (petroleum), solvent dewaxed (64742-62-7);

Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts (68649-42-3)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR KECI - Annex 1	KR KECI - Annex 2	KR - REACH CCA	CN	NZ	MX	TW
Yes	DSL	EIN	Yes	Yes	No	No	Yes	No	No	Yes	Yes	Yes	Yes

Safety Data Sheet

Material Name: PERFORMANCE PLUS DEXOS SAE 0W-20, 5W-20, 5W-30
MOTOR OIL

SDS ID: 820172

*** Section 16 - Other Information ***

NFPA Ratings: Health: 1 Fire: 1 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

Revision Information

Regulatory review and update.

Key/Legend

ACGIH - American Conference of Governmental Industrial Hygienists; BOD - Biochemical Oxygen Demand; C - Celsius; CA - Canada; CA/MA/MN/NJ/PA - California/Massachusetts/Minnesota/New Jersey/Pennsylvania*; CAS - Chemical Abstracts Service; CFR - Code of Federal Regulations (US); CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CLP - Classification, Labelling, and Packaging; CPR - Controlled Products Regulations; DOT - Department of Transportation; DSL - Domestic Substances List; EPA - Environmental Protection Agency; F - Fahrenheit; IDL - Ingredient Disclosure List; IDLH - Immediately Dangerous to Life and Health; IMDG - International Maritime Dangerous Goods; LEL - Lower Explosive Limit; LLV - Level Limit Value; LOLI - List Of Lists™ - ChemADVISOR's Regulatory Database; MAK - Maximum Concentration Value in the Workplace; MEL - Maximum Exposure Limits; NDSL - Non-Domestic Substance List (Canada); NFPA - National Fire Protection Agency; NIOSH - National Institute for Occupational Safety and Health; NJTSR - New Jersey Trade Secret Registry; NTP - National Toxicology Program; OSHA - Occupational Safety and Health Administration; PEL - Permissible Exposure Limit; RCRA - Resource Conservation and Recovery Act; SARA - Superfund Amendments and Reauthorization Act; STEL - Short-term Exposure Limit; TDG - Transportation of Dangerous Goods; TLV - Threshold Limit Value; TSCA - Toxic Substances Control Act; TWA - Time Weighted Average; UEL - Upper Explosive Limit; UN/NA - United Nations /North American; US - United States; WHMIS - Workplace Hazardous Materials Information System (Canada).

Disclaimer

User assumes all risks incident to the use of this (these) product(s). To the best of our knowledge, the information contained herein is accurate. However, Safety-Kleen assumes no liability whatsoever for the accuracy or completeness of the information contained herein. No representations or warranties, either express or implied, of merchantability, fitness for a particular purpose or of any other nature are made hereunder with respect to information or the product to which information refers. The data contained on this sheet apply to the product(s) as supplied to the user.