



HEAVY DUTY DIESEL 15W-40 PLD-3

AMERICA'S CHOICE[®] Heavy Duty Diesel 15W-40 PLD-3 Motor Oil provides unmatched engine protection while preventing sludge and carbon deposits. Meets manufacturer requirements for EGR engines and is recommended for naturally aspirated, turbocharged, or supercharged diesel, gasoline or propane engines. Approved for use where Cummins CES 20078 or Mack EO-N Premium Plus '03 is specified. Also meets or exceeds requirements of Caterpillar ECF-1, and Volvo VDS-3. Suitable for power shift transmissions specifying Allison C-3 / C-4, CAT TO-2, and mobile equipment hydraulic systems specifying engine oils.

Since America's Choice[®] is made from recycled and re-refined used motor oil, it satisfies recent Federal directives for government agencies to use recycled/recovered materials, including:

- Executive Order 13423, signed in 2007 by President Bush, mandates "in Federal agency acquisitions of goods and services use of sustainable environmental practices, including acquisition of bio-based, environmentally preferable, energy-efficient, water-efficient, and recycled-content products"
- Section 6002 of RCRA that requires federal agencies to "procure such items composed of the highest percentage of recovered materials practicable"
- Federal Regulation 23.4 that requires Federal Agencies to "use recovered materials to the maximum extent practicable"

TYPICAL PROPERTIES

| PERFORMANCE PLUS [®] | SAE | 15W-40 |
|--------------------------------|-----|----------------|
| API Service | | CI-4 Plus / SL |
| Kinematic Viscosity | | |
| cSt @ 40°C | | 118.7 |
| cSt @ 100°C | | 15.8 |
| Viscosity Index | | 139 |
| CCS Viscosity | | |
| cP @ -20°C | | 6200 |
| Flash Point, °C | | 230 |
| Pour Point, °C | | -33 |
| Specific Gravity 15.6°C (60°F) | | 0.872 |
| Color (ASTM) | | L 3.5 |
| TBN | | 10.5 |
| Sulfated Ash, wt% | | 1.06 |

Note: Values shown above are representative of current production and may vary within modest ranges

Rev. BZ12L