



NGP-2 DIESEL 15W-40 MOTOR OIL

AMERICA'S CHOICE[®] NGP-2 Diesel 15W-40 Motor Oil is specially formulated to satisfy the requirements of natural gas fueled heavy duty engines. It is formally approved for use in natural gas engines with OEM specifications Cummins CES 20074 and Detroit Diesel PGOS 93K216.

Since America's Choice[®] is made from recycled and re-refined used motor oil, it satisfies recent Federal directives for government agencies to use recycled/recovered materials, including:

- Executive Order 13423, signed in 2007 by President Bush, mandates "in Federal agency acquisitions of goods and services use of sustainable environmental practices, including acquisition of bio-based, environmentally preferable, energy-efficient, water-efficient, and recycled-content products"
- Section 6002 of RCRA that requires federal agencies to "procure such items composed of the highest percentage of recovered materials practicable"
- Federal Regulation 23.4 that requires Federal Agencies to "use recovered materials to the maximum extent practicable"

TYPICAL PROPERTIES

| PERFORMANCE PLUS [®] | SAE | 15W-40 |
|-----------------------------------|-----|--------|
| Kinematic Viscosity cSt @ 40°C | | 104.9 |
| cSt @ 100°C | | 14.9 |
| Viscosity Index | | 148 |
| CCS Viscosity cP @ -20°C | | 5100 |
| Flash Point, °C | | 240 |
| Pour Point, °C | | -39 |
| Color (ASTM) | | L 3.0 |
| Specific Gravity 15.6°C (60°F) | | 0.867 |
| TBN | | 5 |
| TAN | | 1.8 |
| Sulfated Ash wt% | | 0.57 |

Note: Values shown above are representative of current production and may vary within modest ranges.

Rev. BZ12N