



SPINDLE OILS

AMERICA'S CHOICE[®] Spindle Oils are formulated for use in high speed, light to moderate load spindle applications where heat dissipation as well as rust and oxidation inhibiting properties are important.

Since America's Choice[®] is made from recycled and re-refined used motor oil, it satisfies recent Federal directives for government agencies to use recycled/recovered materials, including:

- Executive Order 13423, signed in 2007 by President Bush, mandates "in Federal agency acquisitions of goods and services use of sustainable environmental practices, including acquisition of bio-based, environmentally preferable, energy-efficient, water-efficient, and recycled-content products"
- Section 6002 of RCRA that requires federal agencies to "procure such items composed of the highest percentage of recovered materials practicable"
- Federal Regulation 23.4 that requires Federal Agencies to "use recovered materials to the maximum extent practicable"

TYPICAL PROPERTIES

PERFORMANCE PLUS [®]	ISO GRADE	22	32
Color		L 1.0	L 1.0
Specific Gravity 15.6°C (60°F)		0.855	0.861
Kinematic Viscosity			
cSt @ 40°C		22.0	32.1
cSt @ 100°C		4.4	5.6
Viscosity Index		110	111
Flash Point, °C		208	220
Pour Point, °C		-36	-33
Demulsibility D1401		Pass	Pass
Rust Characteristics D665		Pass	Pass
Copper Corrosion		1B	1B

Note: Values shown above are representative of current production and may vary within modest ranges

Rev. BYU74