



HEAVY DUTY DIESEL 15W-40 XHD-7

PERFORMANCE PLUS[®] Heavy Duty Diesel 15W-40 XHD-7 Motor Oil is specifically engineered to meet the latest requirements for EGR / EPF engines. Meets or exceeds API Service CJ-4 / SM as well as older API categories CI-4 Plus, and CI-4. 15W-40 XHD-7 meets or exceeds OEM specifications and is formally approved for Mack EO-O Premium Plus, Cummins CES 20081, Detroit Diesel PGOS 93K218 and Volvo VDS-4. Meets or exceeds Caterpillar ECF-1A, 2 and 3, MB 228.3, ACEA E7, and MTU Type II standards for performance and protection. Recommended for naturally aspirated, turbocharged or supercharged diesel, gasoline, or propane engines.

The foundation of Performance Plus Oils are Safety-Kleen's hydro-treated, high VI, Group II base oils.

For more than 30 years, Safety-Kleen oil products have performed without fail in the most severe operating conditions.

TYPICAL PROPERTIES		
PERFORMANCE PLUS [®]	SAE	15W-40
API Service		CJ-4 / SM
Kinematic Viscosity		
cSt @ 40°C		118.5
cSt @ 100°C		15.7
Viscosity Index		141
CCS Viscosity		
cP @ -20°C		6300
Flash Point, °C		236
Pour Point, °C		-33
Specific Gravity 15.6°C (60°F)		0.871
Color (ASTM)		L 4.0
TBN		9.6
Sulfated Ash, wt%		0.98

Note: Values shown above are representative of current production and may vary within modest ranges

Rev. BZ12L