



HEAVY DUTY DIESEL HD-2

PERFORMANCE PLUS® HD-2 Heavy Duty Diesel Motor Oils are engineered to reduce wear and tear on valve trains and rings while preventing sludge and carbon deposits. Recommended for naturally aspirated, turbocharged, or supercharged diesel, gasoline, and propane engines that require API CF-2, CF Service Categories (now obsolete), and power shift transmissions specifying Allison C-3 / C-4, and CAT TO-2.

The foundation of Performance Plus Oils are Safety-Kleen’s hydro-treated, high VI, Group II base oils. **For more than 30 years, Safety-Kleen oil products have performed without fail in the most severe operating conditions.**

TYPICAL PROPERTIES

PERFORMANCE PLUS®	SAE	30	40	50
API Service Also recommended for use in engines specifying:		CF-2, CF Detroit Diesel Two-Cycle (6V71 & 6V93)	CF-2, CF Detroit Diesel Two-Cycle (6V71 & 6V93)	CF-2, CF
Kinematic Viscosity cSt @ 40°C		94.6	123.5	185.1
cSt @ 100°C		12.1	14.4	18.4
Viscosity Index		121	117	112
Flash Point, °C		238	242	250
Pour Point, °C		-36	-27	-21
Specific Gravity 15.6°C (60°F)		0.874	0.880	0.888
Color (ASTM)		L 3.0	L 3.5	L 5.0
TBN		7.5	7.5	7.5
Sulfated Ash, wt%		0.86	0.86	0.86

Note: Values shown above are representative of current production and may vary within modest ranges

Rev. BZ12L