



# PASSENGER CAR MOTOR OIL

**PERFORMANCE PLUS<sup>®</sup> Synthetic Blend Passenger Car Motor Oils** are specially formulated with a combination of Group II and Group III base oils plus state-of-the-art performance additives and are engineered to exceed the demands of turbocharged and high-power, high-efficiency gasoline, propane, and natural gas engines in the latest model passenger cars and light duty trucks. SAE 5W-20 and 5W-30 grades are Resource Conserving motor oils that exceed API service SN and ILSAC Starburst GF-5, as well as older service categories SM, SL, and previous ILSAC categories.

The foundation of Performance Plus Oils are Safety-Kleen's hydro-treated, high VI, Group II base oils. **For more than 30 years, Safety-Kleen oil products have performed without fail in the most severe operating conditions.**

TYPICAL PROPERTIES			
PERFORMANCE PLUS <sup>®</sup>	SAE	5W-20	5W-30
API Service		SN	SN
ILSAC		GF-5	GF-5
Kinematic Viscosity			
cSt @ 40°C		50.0	62.1
cSt @ 100°C		8.6	10.4
Viscosity Index		150	157
CCS Viscosity			
cP @ -30°C		6000	6300
Evaporative Loss, NOACK, wt%		<15	<15
Specific Gravity 15.6°C (60°F)		0.862	0.861
Flash Point, °C		218	220
Pour Point, °C		-39	-39
Color (ASTM)		3.0	3.0
Sulfated Ash, wt%		0.92	0.92

*Note: Values shown above are representative of current production and may vary within modest ranges*

*Rev. BYU74*