

Section 1 - PRODUCT AND COMPANY IDENTIFICATION**Material Name**

SAFETY-KLEEN VIRGIN 105 SOLVENT

Product Code

6617

Synonyms

Parts Washer Solvent; Petroleum Distillates; Petroleum Naphtha, Solvent; Mineral Spirits

Product Use

Cleaning and degreasing metal parts. If this product is used in combination with other products, refer to the Safety Data Sheet for those products. SDS for use in Canada and the U.S.

Restrictions on Use

None known.

MANUFACTURERSafety-Kleen Systems, Inc.
2600 North Central Expressway
Suite 200
Richardson, TX 75080**SUPPLIER**Safety-Kleen Canada, Inc.
25 Regan Road
Brampton, Ontario, Canada L1A 1B2www.safety-kleen.com

Phone: 1-800-669-5740

Emergency Phone #: 1-800-468-1760

Issue Date

July 30, 2018

Supersedes Issue Date

November 8, 2016

Original Issue Date

February 13, 1991

Section 2 - HAZARDS IDENTIFICATION**Classification in accordance with Schedule 1 of Hazardous Products Regulations (HPR) (SOR/2015-17) and 29 CFR 1910.1200**

Flammable Liquids - Category 3

Specific Target Organ Toxicity – Single Exposure, Category 3 (central nervous system)

Aspiration Hazard - Category 1

GHS Label Elements**Symbol(s)****Signal Word**

Danger

Safety Data Sheet

Material Name: SAFETY-KLEEN VIRGIN 105 SOLVENT

SDS ID: 82341

Hazard Statement(s)

Flammable liquid and vapor.
May cause drowsiness and dizziness.
May be fatal if swallowed and enters airways.

Precautionary Statement(s)

Prevention

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wear protective gloves/protective clothing/eye protection/face protection. Keep container tightly closed. Ground/Bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves/protective clothing/eye protection/face protection. Avoid breathing vapor or mist. Use only outdoors or in a well-ventilated area.

Response

In case of fire: Use Class B/C or Class A/B/C fire extinguisher, carbon dioxide, regular form, or dry chemical for extinction. IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.

Storage

Store in a well-ventilated place. Keep cool. Store locked up.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards

None known.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

CAS	Component Name	Percent
64742-47-8	Distillates (petroleum), hydrotreated light	<100

Additional information

This product may be regulated, have exposure limits or other information identified as the following:
Stoddard solvent.

Section 4 - FIRST AID MEASURES

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

Skin

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical attention if irritation develops or persists.

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops or persists.

Ingestion

IF SWALLOWED: Aspiration hazard. Do NOT induce vomiting. If vomiting occurs, keep head lower than hips to help prevent aspiration. Call a poison control center or doctor immediately for treatment advice.

Safety Data Sheet

Material Name: SAFETY-KLEEN VIRGIN 105 SOLVENT

SDS ID: 82341

Most Important Symptoms/Effects

Acute

May be fatal if swallowed and enters airways. Central nervous system depression.

Delayed

Central nervous system damage.

Indication of any immediate medical attention and special treatment needed

IF exposed: Call a POISON CENTER or doctor/physician. Treat symptomatically and supportively.

Treatment may vary with condition of victim and specifics of incident. Call 1-800-468-1760 for additional information.

Section 5 - FIRE FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media

Class B/C or Class A/B/C fire extinguisher, carbon dioxide, regular foam, regular dry chemical, water spray, water fog

Unsuitable Extinguishing Media

Do not use high-pressure water streams.

Special Hazards Arising from the Chemical

Flammable liquid and vapor. The vapor is heavier than air. Vapors or gases may ignite at distant ignition sources and flash back. Run-off to sewer may create a fire hazard. Heated containers may rupture or be thrown into the air. Empty containers may retain product residue including flammable/explosive vapors. Product may be sensitive to static discharge, which could result in fire or explosion.

Hazardous Combustion Products

Decomposition and combustion materials may be toxic. Burning may produce carbon monoxide and unidentified organic compounds.

Fire Fighting Measures

Keep away from sources of ignition - No Smoking. Keep unnecessary people away, isolate hazard area and deny entry. Move container from fire area if it can be done without risk. Cool containers with water spray until well after the fire is out. Fight fire from maximum distance or use unmanned hose holders or monitor nozzles. For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible withdraw from area and let fire burn. Withdraw immediately in case of rising sound from venting safety device or any discoloration of tanks due to fire. Stay away from the ends of tanks. For tank, rail car or tank truck, evacuation radius: 800 meters (1/2 mile). Stay upwind and keep out of low areas. Dike for later disposal.

Special Protective Equipment and Precautions for Firefighters

A positive-pressure, self-contained breathing apparatus (SCBA) and full-body protective equipment are required for fire emergencies.

Section 6 - ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Wear personal protective clothing and equipment. SEE SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION. Avoid release to the environment.

Methods and Materials for Containment and Cleaning Up

Remove all ignition sources. Do not touch or walk through spilled product. Stop leak if you can do it without risk. Wear protective equipment and provide engineering controls as specified in SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Ventilate area and avoid breathing vapor or mist. A vapor suppressing foam may be used to reduce vapors. Contain spill away from surface water and sewers. Contain spill as a liquid for possible recovery, or sorb with compatible sorbent material and shovel with a clean, sparkproof tool into a sealable container for disposal. Additionally, for large spills: Water spray may reduce vapor, but may not prevent

Safety Data Sheet

Material Name: SAFETY-KLEEN VIRGIN 105 SOLVENT

SDS ID: 82341

ignition in closed spaces. Dike far ahead of liquid spill for collection and later disposal. There may be specific regulatory reporting requirements associated with spills, leaks, or releases of this product. Also see SECTION 15: REGULATORY INFORMATION.

Section 7 - HANDLING AND STORAGE

Precautions for Safe Handling

Keep away from heat, sparks, or flame. Where flammable mixtures may be present, equipment safe for such locations should be used. When transferring large quantities of product, trucks and tank cars, should be grounded and bonded. Do not breathe vapor or mist. Use in a well ventilated area. Avoid contact with eyes, skin, clothing, shoes. Do not smoke while using these products.

Conditions for Safe Storage, Including any Incompatibilities

Keep containers away from heat, flame, sparks, static electricity, or other sources of ignition. Do not pressurize, cut, weld, braze, solder, drill, or grind containers. Empty product containers may retain product residue and can be dangerous. Store in a well-ventilated area. Keep container tightly closed. Keep cool. See SECTION 14: TRANSPORTATION INFORMATION for Packing Group information.

Incompatible Materials

Strong oxidizing materials.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Component Exposure Limits

Distillates (petroleum), hydrotreated light	64742-47-8
Alberta	100 ppm TWA ; 572 mg/m3 TWA (related to Stoddard solvent)
British Columbia	200 mg/m3 TWA (application restricted to conditions in which there are negligible aerosol exposures) as total Hydrocarbon vapor; Skin notation; 580 mg/m3 STEL (related to Stoddard solvent)
Manitoba	100 ppm TWA (related to Stoddard solvent)
New Brunswick	100 ppm TWA ; 525 mg/m3 TWA (related to Stoddard solvent)
Northwest Territories	100 ppm TWA (related to Stoddard solvent); 125 ppm STEL (related to Stoddard solvent)
Nova Scotia	100 ppm TWA (related to Stoddard solvent)
Nunavut	100 ppm TWA (related to Stoddard solvent); 125 ppm STEL (related to Stoddard solvent)
Ontario	525 mg/m3 TWA (related to Stoddard solvent)
Prince Edward Island	100 ppm TWA (related to Stoddard solvent)
Quebec	100 ppm TWAEV ; 525 mg/m3 TWAEV (related to Stoddard solvent)
Saskatchewan	100 ppm TWA (related to Stoddard solvent); 125 ppm STEL (related to Stoddard solvent)

Safety Data Sheet

Material Name: SAFETY-KLEEN VIRGIN 105 SOLVENT

SDS ID: 82341

Yukon	100 ppm TWA ; 575 mg/m3 TWA (related to Stoddard solvent); 150 ppm STEL ; 720 mg/m3 STEL (related to Stoddard solvent)
ACGIH	100 ppm TWA (related to Stoddard solvent)
OSHA	500 ppm TWA; 2900 mg/m3 TWA (related to Stoddard solvent)
NIOSH	350 mg/m3 TWA (related to Stoddard solvent) 1800 mg/m3 Ceiling (15 min, related to Stoddard solvent)

ACGIH - Threshold Limit Values - Biological Exposure Indices (BEI)

There are no biological limit values for any of this product's components.

Engineering Controls

Provide general ventilation needed to maintain concentration of vapor or mist below applicable exposure limits. Where adequate general ventilation is unavailable, use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below applicable exposure limits. Where explosive mixtures may be present, equipment safe for such locations should be used.

Individual Protection Measures, such as Personal Protective Equipment

Eye/face protection

Wear safety glasses. Additional protection like goggles, face shields, or respirators may be needed dependent upon anticipated use and concentrations of mists or vapors. Eye wash fountain and emergency showers are recommended. Contact lens use is not recommended.

Skin Protection

To avoid prolonged or repeated contact with products where spills and splashes are likely, wear appropriate chemical-resistant faceshield, boots, apron, coveralls, long sleeve shirts, or other protective clothing.

Respiratory Protection

Respiratory Protection

Use NIOSH-certified P- or R- series particulate filter and organic vapor cartridges when concentration of vapor or mist exceeds applicable exposure limits. Protection by air purifying respirators is limited.

Selection and use of respiratory protective equipment should be in accordance in the USA with OSHA General Industry Standard 29 CFR 1910.134; or in Canada with CSA Standard Z94.4.

Glove Recommendations

Where skin contact is likely, wear neoprene, nitrile, or equivalent protective gloves; use of natural rubber or equivalent gloves is not recommended.

Protective Materials

Personal protective equipment should be selected based upon the conditions under which this material is used. A hazard assessment of the work area for PPE requirements should be conducted by a qualified professional pursuant to regulatory requirements. The following PPE should be considered the minimum required: Safety glasses, gloves, lab coat or apron.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Clear.	Physical State	Liquid
Odor	aromatic	Color	Colorless to pale yellow.
Odor Threshold	30 ppm (Stoddard solvent)	pH	Not available
Melting Point	-43 °C (-45 °F Maximum)	Boiling Point	177 °C (350 °F Initial)
Boiling Point Range	Not available	Freezing point	Not available
Evaporation Rate	<0.1 (Butyl acetate = 1)	Flammability (solid, gas)	Not available

Safety Data Sheet

Material Name: SAFETY-KLEEN VIRGIN 105 SOLVENT

SDS ID: 82341

Autoignition Temperature	249 °C (480 °F Minimum)	Flash Point	40 °C (105 °F.)
Lower Explosive Limit	0.7 vol% (Minimum)	Decomposition temperature	Not available
Upper Explosive Limit	5 vol% (Maximum)	Vapor Pressure	0.2 mmHg @ 68 °F (20° C)
Vapor Density (air=1)	5 (Approximate Air = 1)	Specific Gravity (water=1)	0.77 - 0.82 at 15.6 °C
Water Solubility	(Insoluble)	Partition coefficient: n-octanol/water	Not available
Viscosity	Not available	Solubility (Other)	Not available
Density	6.4 - 6.7 lb/gal at 60 °F (Water = 1.)	Physical Form	Liquid.
Volatile Organic Compounds (As Regulated)	100 WT%; 6.4 to 6.7 LB/US gal; 770 to 800 g/l As per 40 CFR Part 51.100(s). VOC Vapor Pressure: <1.0 mmHg @20°C Product may or may not be considered photochemically reactive (100% by weight). Consult your state or local air district regulations for location specific information.		

Section 10 - STABILITY AND REACTIVITY

Reactivity

No reactivity hazard is expected.

Chemical Stability

Stable under normal temperatures and pressures.

Possibility of Hazardous Reactions

Will not polymerize under normal temperature and pressure conditions.

Conditions to Avoid

Avoid heat, flames, sparks and other sources of ignition Avoid contact with incompatible materials.

Incompatible Materials

Acids, alkalis, oxidizing agents, reducing agents, or reactive halogens.

Hazardous decomposition products

None under normal temperatures and pressures. See also SECTION 5: HAZARDOUS COMBUSTION PRODUCTS.

Section 11 - TOXICOLOGICAL INFORMATION

Information on Likely Routes of Exposure

Inhalation

May cause irritation, nausea, loss of appetite, headache, drowsiness, dizziness, disorientation, tremors, lung damage (from aspiration), convulsions, coma.

Skin Contact

May cause irritation of the skin.

Eye Contact

May cause eye irritation.

Safety Data Sheet

Material Name: SAFETY-KLEEN VIRGIN 105 SOLVENT

SDS ID: 82341

Ingestion

May cause, headache, drowsiness, dizziness, loss of coordination, aspiration hazard.

Acute and Chronic Toxicity

Component Analysis - LD50/LC50

The components of this material have been reviewed in various sources and the following selected endpoints are published:

Distillates (petroleum), hydrotreated light (64742-47-8)

Oral LD50 Rat >5000 mg/kg; Dermal LD50 Rabbit >2000 mg/kg; Inhalation LC50 Rat >5.2 mg/L 4 h

Product Toxicity Data

Acute Toxicity Estimate

Dermal	> 2000 mg/kg
Oral	> 2000 mg/kg

Immediate Effects

Central nervous system depression, lung damage (from aspiration).

Delayed Effects

No information on significant adverse effects.

Irritation/Corrosivity Data

May cause respiratory tract irritation, skin irritation, eye irritation.

Respiratory Sensitization

No information available for the product.

Dermal Sensitization

No information available for the product.

Component Carcinogenicity

None of this product's components are listed by ACGIH, IARC, OSHA, or NTP.

Germ Cell Mutagenicity

Based on best current information, there is no known mutagenicity associated with this product.

Tumorigenic Data

No data available

Reproductive Toxicity

No epidemiological data is available for this product.

Specific Target Organ Toxicity - Single Exposure

Central nervous system.

Specific Target Organ Toxicity - Repeated Exposure

Central nervous system.

Aspiration hazard

Lung aspiration hazard if swallowed.

Medical Conditions Aggravated by Exposure

Individuals with pre-existing respiratory tract (nose, throat, and lungs), central nervous system, kidneys, and eye and/or skin disorders may have increased susceptibility to the effects of exposure.

Section 12 - ECOLOGICAL INFORMATION

Ecotoxicity

Toxic to aquatic life with long lasting effects.

Component Analysis - Aquatic Toxicity

Distillates (petroleum), hydrotreated light	64742-47-8
--	------------

Safety Data Sheet

Material Name: SAFETY-KLEEN VIRGIN 105 SOLVENT

SDS ID: 82341

Fish:	LC50 96 h Pimephales promelas 45 mg/L [flow-through]; LC50 96 h Lepomis macrochirus 2.2 mg/L [static]; LC50 96 h Oncorhynchus mykiss 2.4 mg/L [static]
-------	---

Persistence and Degradability

This material is believed not to biodegrade.

Bioaccumulative Potential

This material is believed not to bioaccumulate.

Mobility

Expected to have high mobility in soil.

Other Toxicity

No additional information is available.

Section 13 - DISPOSAL CONSIDERATIONS

Disposal Methods

Based on available data, this information applies to the product as supplied to the user. Processing, use, or contamination by the user may change the waste code applicable to the disposal of this product. Dispose in accordance with federal, state, provincial, and local regulations. Regulations may also apply to empty containers. The responsibility for proper waste disposal lies with the owner of the waste. Contact Safety-Kleen regarding proper recycling or disposal. D018. D001.

Section 14 - TRANSPORT INFORMATION

DOT NON-BULK PACKAGES (≤119 Gallons)(Shipments via vessel and aircraft must use bulk shipping description.):

Shipping Name: Cleaning compounds (petroleum naphtha)(Not US DOT Regulated)

BULK PACKAGES (≥120 Gallons):

Shipping Name: Combustible liquid, n.o.s. (petroleum naphtha)

UN/NA: NA1993 Hazard Class: Combustible liquid Packing Group: III Required Placards: Class 3, NA1993

TDG SMALL MEANS OF CONTAINMENT (Shipments via aircraft must use large means of containment shipping description):

Shipping Name: CLEANING COMPOUNDS (petroleum naphtha)(Not TDG regulated)

LARGE MEANS OF CONTAINMENT

Shipping Name: PETROLEUM DISTILLATES, N.O.S. (petroleum naphtha)

UN/NA #: UN1268 Hazard Class: 3 Packing Group: III

Required Placards: Class 3, UN1268

Emergency Response Guide Number 128: Reference . North American Emergency Response Guide Book

Section 15 - REGULATORY INFORMATION

U.S. Federal Regulations

None of this product's components are listed under SARA Sections 302/304 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), CERCLA (40 CFR 302.4), TSCA 12(b), or require an OSHA process safety plan.

SARA Section 311/312 (40 CFR 370 Subparts B and C) reporting categories

Flammable; Specific Target Organ Toxicity; Aspiration Hazard

U.S. State Regulations

Safety Data Sheet

Material Name: SAFETY-KLEEN VIRGIN 105 SOLVENT

SDS ID: 82341

The following components appear on one or more of the following state hazardous substances lists:

Component	CAS	CA	MA	MN	NJ	PA
Distillates (petroleum), hydrotreated light	64742-47-8	Yes	Yes	Yes	Yes	Yes

California Safe Drinking Water and Toxic Enforcement Act (Proposition 65)

WARNING! This product can expose you to chemicals including benzene, ethylbenzene, and naphthalene which are known to the State of California to cause cancer and benzene and toluene which are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Canada Regulations

CEPA - Priority Substances List

None of this product's components are on the list.

Ozone Depleting Substances

None of this product's components are on the list

Council of Ministers of the Environment - Soil Quality Guidelines

None of this product's components are on the list

Council of Ministers of the Environment - Water Quality Guidelines

None of this product's components are on the list

Component Analysis - Inventory

This product has been classified in accordance with the criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by the CPR.

All of the components of this product are listed on or are exempt from the TSCA inventory listing.

Distillates (petroleum), hydrotreated light (64742-47-8)

US	CA
Yes	DSL

Section 16 - OTHER INFORMATION

NFPA Ratings

Health: 1 Fire: 2 Reactivity: 0

Hazard Scale: 0 = Minimal; 1 = Slight; 2 = Moderate; 3 = Serious; 4 = Severe

Summary of Changes

2018-07-30: Regulatory review and update.

Key / Legend

ACGIH - American Conference of Governmental Industrial Hygienists; BOD - Biochemical Oxygen Demand; C - Celsius; CA - Canada; CA/MA/MN/NJ/PA - California/Massachusetts/Minnesota/New Jersey/Pennsylvania*; CAS - Chemical Abstracts Service; CFR - Code of Federal Regulations (US); CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CLP - Classification, Labelling, and Packaging; CPR - Controlled Products Regulations; DOT - Department of Transportation; DSL - Domestic Substances List; EPA - Environmental Protection Agency; F - Fahrenheit; IDL - Ingredient Disclosure List; IDLH - Immediately Dangerous to Life and Health; IMDG - International Maritime Dangerous Goods; LEL - Lower Explosive Limit; LLV - Level Limit Value; LOLI - List Of LIsts™ - ChemADVISOR's Regulatory Database; MAK - Maximum Concentration Value in the Workplace; MEL - Maximum Exposure Limits; NDSL - Non-Domestic Substance List (Canada); NFPA - National Fire Protection Agency; NIOSH - National Institute for Occupational Safety and Health; NJTSR - New Jersey Trade Secret Registry; NTP - National Toxicology Program; OSHA - Occupational Safety and Health Administration; PEL - Permissible Exposure Limit; RCRA - Resource Conservation and Recovery Act; SARA - Superfund Amendments and Reauthorization Act; STEL - Short-term Exposure Limit; TDG - Transportation of Dangerous Goods; TLV - Threshold Limit Value; TSCA - Toxic Substances Control Act; TWA - Time Weighted

Safety Data Sheet

Material Name: SAFETY-KLEEN VIRGIN 105 SOLVENT

SDS ID: 82341

Average; UEL - Upper Explosive Limit; UN/NA - United Nations /North American; US - United States; WHMIS - Workplace Hazardous Materials Information System (Canada).

Other Information

Disclaimer:

User assumes all risks incident to the use of this product. To the best of our knowledge, the information contained herein is accurate. However, Safety-Kleen assumes no liability whatsoever for the accuracy or completeness of the information contained herein. No representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose or of any other nature are made hereunder with respect to the information or the product to which the information refers. The data contained on this sheet apply to the product as supplied to the user.