MODEL 16/30

TIME TESTED. Our legacy sink-on-drum part washers have been around for more than fifty years, featuring a sink for washing parts on top of a 16- or 30-gallon drum of solvent. Machines feature a lid with fusible link, plastic spigot for solvent delivery, brush for cleaning parts and a lamp. Soiled parts are manually washed in the sink with solvent draining into the reservoir below.

| | Model 16* | Model 30* |
|---|--|--|
| Approved Solvents | Premium Solvent QSOL 220/300 PD 680 Type II PRF 680 Type II Odorless Solvent | Premium Solvent QSOL 220/300 PD 680 Type II PRF 680 Type II Odorless Solvent |
| Operation Type | Manual | Manual |
| Floor Space Height Width | 53" (134.7 cm) 16" (40.7 cm) | 60" (152.4 cm) 19.5" (49.6 cm) |
| Sink Size Height Width Depth (front to back) | 7.5" (19.1 cm) 27.5" (69.9 cm) 16.25" (41.3 cm) | 8" (20.4 cm) 33.25" (84.5 cm) 22.25" (56.6 cm) |
| Electric Power | 115 VAC, 60 Hz, 1.4 A | 115 VAC, 60 Hz, 1.4 A |
| Standard Fill | 8 gal. (30.2 L) | 15 gal. (56.8 L) |
| Operating Temp | Ambient | Ambient |
| Material | Steel | Steel |
| Machine Color | Red | Red |
| Max Workload | 25 lbs. (11.3 kg) | 25 lbs. (11.3 kg) |
| Shipping Wt | 57 lbs. (25.9 kg) | 57 lbs. (25.9 kg) |
| Max Filled Wt | 111 lbs. (50.3 kg) | 162 lbs. (73.5 kg) |
| Listing | cETLus | cETLus |



^{*}Certified reconditioned equipment. Local regulations may cause variations in requirements. Drum and chemistry sold separately.

CALL YOUR SAFETY-KLEEN REPRESENTATIVE TODAY FOR A FREE ASSESSMENT. SAFETY-KLEEN.COM | 800-323-5040

