



# Performance Plus Oils and Lubricants

PERFORMANCE UNDER THE MOST EXTREME CONDITIONS.

## AUTOMATIC TRANSMISSION FLUID

**PERFORMANCE PLUS™ Automatic Transmission Fluid** is formulated to reduce wear, protect against corrosion, and last longer in vehicles with automatic and power-shift transmissions.

The foundation of Performance Plus Oils are hydro-treated, high VI, Group II+ base oils.

**Performance Plus® Automatic Transmission Fluid** meets or exceeds following requirements: DEXRON® III, DEXRON® IIE, DEXRON®, MERCON®, Ford ESP-M2C138-CJ, Ford ESP-M2C166-H or Type A Suffix A, Allison C-3/C-4, or Caterpillar TO-2 fluids.

### PERFORMANCE PLUS PROPERTIES

Kinematic Viscosity cSt @ 40°C	32.9
cSt @ 100°C	7.0
Viscosity Index	180
Brookfield Viscosity cP @ -40°C	15,000
API Gravity	32.6
Specific Gravity 15.6°C (60°F)	0.862
Flash Point, °C (°F)	204 (399)
Pour Point, °C (°F)	-51 (-60)
Color	Red

**For additional questions, please contact your Performance Plus® Products Sales Representative.**

Note: Values shown above are representative of current production and may vary within modest ranges. Rev. 10/18