



Performance Plus Oils and Lubricants

PERFORMANCE UNDER THE MOST EXTREME CONDITIONS.

CONVENTIONAL GEAR OIL (GL-5)

PERFORMANCE PLUS™ Conventional Gear Oils (GL-5) are premium quality multi-purpose gear oils formulated to minimize gear friction, reduce corrosion, and prevent the formation of sludge. Conventional Gear Oils (GL-5) are recommended for all vehicles and heavy-duty equipment differentials, final drives, manual transmissions and gearboxes and is suitable for drain-and-fill or top-off limited-slip service. Also suitable for industrial gearboxes specifying US Steel 224.

Performance Plus® Conventional Gear Oils (GL-5) meets, exceeds, or carries the approvals to match the performance requirements of the following: API GL-5, MT-1; Mack GO-J approved (80W-90) GO-H, GO-G; meets SAE J2360, Arvin Meritor 076-D (80W-90), 076-A (85W-140), Ford WSP-M2C197-A (80W-90)

PERFORMANCE PLUS PROPERTIES

PERFORMANCE PLUS PROPERTIES		
ISO Viscosity Grade	80W-90	85W-140
API Service Category	GL-5 / MT-1	GL-5 / MT-1
Kinematic Viscosity		
cSt @ 40°C	145.4	341.3
cSt @ 100°C	15.2	25.6
Viscosity Index	106	97
Brookfield Viscosity		
cP @ -26°C	105,000	-
cP @ -12°C	-	60,000
Specific Gravity 15.6°C (60°F)	0.885	0.896
Flash Point, °C (°F)	214 (417)	218 (424)
Pour Point, °C (°F)	-30 (-22)	-12 (10)
Color (ASTM)	L 3.5	L 4.5

For additional questions, please contact your Performance Plus® Products Sales Representative.

Note: Values shown above are representative of current production and may vary within modest ranges. Rev. 10/18