



Performance Plus Oils and Lubricants

PERFORMANCE UNDER THE MOST EXTREME CONDITIONS.

FULL SYNTHETIC GEAR OILS

PERFORMANCE PLUS™ Full Synthetic Gear Oils are extremely versatile gear oils meeting the widest operating temperature ranges for automotive; light, medium and heavy-duty trucks; farm, logging and construction equipment. This product meets or exceeds Ford OEM specifications for use in rear axle units per Ford Spec WSLM2C192A.

Performance Plus® Full Synthetic Gear Oils also meets or exceeds the following requirements: API Performance Level: GL-5, MT-1; Extreme Pressure Hypoid Gears; Dana Corporation: SHAE-256 Rev. C (75W-90), Arvin Meritor: O-76E (75W-90); Military Specifications: MIL-PRF-2105D, PRF 2105E; Mack Truck: GO-G, GO-H, GO-J, GO-J Plus; and SAE J2360.

PERFORMANCE PLUS PROPERTIES

PERFORMANCE PLUS PROPERTIES		
SAE Viscosity Grade	75W-90	75W-140
API Performance Level	GL-5, MT-1	GL-5, MT-1
Kinematic Viscosity cSt @ 40°C	94.4	172.1
cSt @ 100°C	16.7	27.1
Viscosity Index	192	199
Brookfield Viscosity cP @ -40°C	85,200	122,000
Specific Gravity 15.6°C (60°F)	0.854	0.852
Flash Point, °C (°F)	242 (468)	248 (478)
Pour Point, °C (°F)	-38 (-36)	-44 (-47)

For additional questions, please contact your Performance Plus® Products Sales Representative.

Note: Values shown above are representative of current production and may vary within modest ranges. Rev. 10/18