



Performance Plus Greases

PERFORMANCE UNDER THE MOST EXTREME CONDITIONS.

ALL-PURPOSE LITHIUM GREASE (NLGI 2)

PERFORMANCE PLUS All-Purpose Lithium Grease is a premium lithium grease suitable for many industrial and light duty applications.

Performance Plus All-Purpose Lithium Grease is ideal for use in applications calling for a Lithium NLGI #2 grease with good corrosion protection, water resistance, oxidative stability and wear protection. Performance Plus All-Purpose Lithium Grease starts with premium, low viscosity base oils for pumpability cold environments. Our polymer package reduces oil separation and resists water washout keeping the grease in applications longer. A state-of-the-art extreme pressure additive package helps moving components withstand light to moderate shock loading and prevents early wear.

PERFORMANCE PLUS PROPERTIES

| | Test Method | Typical Properties |
|---------------------------------------|-------------|--------------------|
| NLGI Grade | ASTM D-217 | 2 |
| NLGI Specification | ASTM D-4950 | LB |
| Thickener Type | Report | Lithium Complex |
| Color | Visual | Green |
| Texture | Visual | Smooth |
| Worked Penetration | ASTM D-217 | 270 |
| Base Oil Viscosity cSt @ 40°C | ASTM D-445 | 138 |
| cSt @ 100°C | ASTM D-445 | 12 |
| Viscosity Index | ASTM D-445 | 68 |
| Dropping Point, °F | ASTM D-2265 | 370 |
| 4-Ball weld, kgf | ASTM D-2596 | 250 |
| 4-Ball wear , scar mm | ASTM D 2266 | 0.66 |
| 4-Ball LWI | ASTM D-2596 | 30 |
| Rust Prevention | ASTM D-1743 | Pass |
| Oxidation Stability psi loss/100 Hrs. | ASTM D-942 | 3 |
| Timken, OK load, lbs. | ASTM D-2509 | 40 |
| Water Washout (% loss @ 175°F) | ASTM D-1264 | 5 |

For additional questions, please contact your Performance Plus® Products Sales Representative.

Note: Values shown above are representative of current production and may vary within modest ranges. Rev. 10/18