



# Performance Plus Oils and Lubricants

PERFORMANCE UNDER THE MOST EXTREME CONDITIONS.

## NGP 15W-40 NATURAL GAS ENGINE OIL

**PERFORMANCE PLUS™ NGP 15W-40 Natural Gas Engine Oil** is specially formulated to satisfy the requirements of natural gas fueled heavy duty engines.

The foundation of Performance Plus Oils are hydro-treated, high VI, Group II+ base oils.

**Performance Plus® NGP 15W-40 Natural Gas Engine Oil** is formally approved for use in natural gas engines with OEM specification Cummins CES 20074.

### PERFORMANCE PLUS PROPERTIES

SAE Viscosity Grade	15W-40
API Service Category	-
Kinematic Viscosity cSt @ 40°C cSt @ 100°C	104.5 14.5
Viscosity Index	143
CCS Viscosity cP @ -35°C cP @ -30°C cP @ -25°C cP @ -20°C	- - - 4,900
MRV Viscosity cP @ -25°C	14,900
TBN	5.9
Evaporative Loss, NOACK, wt%	< 13
Specific Gravity 15.6°C (60°F)	0.867
Flash Point, °C (°F)	240 (464)
Pour Point, °C (°F)	-39 (-38)
Color (ASTM)	L 3.0
Sulfated Ash, wt%	0.59

**For additional questions, please contact your Performance Plus® Products Sales Representative.**

Note: Values shown above are representative of current production and may vary within modest ranges. Rev. 10/18