



Performance Plus Oils and Lubricants

PERFORMANCE UNDER THE MOST EXTREME CONDITIONS.

FULL SYNTHETIC HEAVY-DUTY TRANSMISSION FLUID

PERFORMANCE PLUS™ Full Synthetic Heavy-Duty Transmission Fluid is a fully synthetic fluid formulated to meet the demanding requirements of the latest heavy duty automatic transmissions and is recommended for use in applications where comparable Allison TES-295 & TES-389 performance capability is specified. Providing outstanding power transfer and gear shifting performance, it is made to: protect against thermal breakdown at high and sub-zero temperatures, offer excellent shear stability, and provide outstanding performance in severe operating conditions. Performance Plus Full Synthetic Heavy Duty Transmission Fluid is designed to protect transmissions against corrosion, oxidation and deposits delivering smooth shifting and prevent wear.

Performance Plus® Full Synthetic Heavy-Duty Transmission Fluid meets or exceeds following requirements: Allison TES-295 and TES-389, C-4; MAN 339 Type V1, Z2; ZF TE-ML 03D, 04D, 14A, 14B, 16L, 17C, 20B; Voith 55.6335 (G607); MB 236.9; Chrysler ATF +4; GM Dexron III H; Ford Mercon V; JASO Class 1-A

PERFORMANCE PLUS PROPERTIES

Kinematic Viscosity cSt @ 40°C cSt @ 100°C	31.6 7.2
Viscosity Index	203
API Gravity	34.7
Specific Gravity 15.6°C (60°F)	0.851
Flash Point, °C (°F)	150 (302)
Pour Point, °C (°F)	-48 (-54)
Allison TES-295	Meets
Allison TES-389	Meets

TES-295® and TES-389® are registered trademarks of Allison Transmission Corporation.

For additional questions, please contact your Performance Plus® Products Sales Representative.

Note: Values shown above are representative of current production and may vary within modest ranges. Rev. 10/18