



Performance Plus Oils and Lubricants

PERFORMANCE UNDER THE MOST EXTREME CONDITIONS.

UNIVERSAL TRACTOR FLUID

PERFORMANCE PLUS™ Universal Tractor Fluid is a premium transmission / differential / hydraulic fluid with superior anti-wear properties recommended for use in: power shift transmissions, hydrostatic manual transmissions, differentials, final drives, wet brakes, clutches, power steering, and PTO drives commonly used in farm and construction equipment, off-highway vehicles, and industrial tractors.

The foundation of Performance Plus Oils are hydro-treated, high VI, Group II+ base oils.

Performance Plus® NGP 15W-40 Universal Tractor Fluid is approved for use power shift transmissions specifying Allison C-3/C-4 or CAT TO-2 fluids; John Deere J20A, J20C; Ford New Holland M2C -41B, -48B, -48C, -86C, -134D; Kubota B6 (UDT); and Vickers 35VQ25.

PERFORMANCE PLUS PROPERTIES

Kinematic Viscosity cSt @ 40°C cSt @ 100°C	58.7 9.4
Viscosity Index	143
Brookfield Viscosity cP @ -35°C	23,000
Specific Gravity 15.6°C (60°F)	0.869
Flash Point, °C (°F)	226 (439)
Pour Point, °C (°F)	-42 (-44)
Color (ASTM)	L 3.0

For additional questions, please contact your Performance Plus® Products Sales Representative.

Note: Values shown above are representative of current production and may vary within modest ranges. Rev. 10/18