



Performance Plus Oils and Lubricants

PERFORMANCE UNDER THE MOST EXTREME CONDITIONS.

FULL SYNTHETIC PASSENGER CAR MOTOR OIL (SN)

PERFORMANCE PLUS™ Full Synthetic Passenger Car Motor Oils are specially formulated with high-quality Group III base oil plus state-of-the art performance additives. They are engineered to meet or exceed the demands of turbocharged, high powered, high-efficiency, gasoline and propane engines in the latest model passenger cars and light duty trucks.

Performance Plus®™ Full Synthetic Passenger Car Motor Oils meets, exceeds, or carries the approvals to match the performance requirements of the following: Ford WSS-M2C-945A (5W-20), Ford WSS-M2C-946-A (5W-30), Ford WSS-M2C-947-A (0W-20) and GM 6094M.

PERFORMANCE PLUS PROPERTIES			
SAE Viscosity Grade	0W-20	5W-20	5W-30
API Service Category	SN	SN	SN
ILSAC Specification	GF-5	GF-5	GF-5
Kinematic Viscosity			
cSt @ 40°C	46.3	48.7	62.7
cSt @ 100°C	8.7	8.6	10.8
Viscosity Index	169	157	164
CCS Viscosity			
cP @ -35°C	5800	-	-
cP @ -30°C	-	5000	5000
MRV Viscosity			
cP @ -40°C	20000		
cP @ -35°C		15000	20000
TBN	7.0	7.9	7.9
Evaporative Loss, NOACK, wt%	< 15	< 15	< 15
Specific Gravity 15.6°C (60°F)	0.846	0.850	0.850
Flash Point, °C (°F)	210	208	204
Pour Point, °C (°F)	-51	-48	-48
Color (ASTM)	3.0	3.0	3.0
Sulfated Ash, wt%	0.92	0.92	0.92

For additional questions, please contact your Performance Plus® Products Sales Representative.

Note: Values shown above are representative of current production and may vary within modest ranges. Rev. 10/18