



Performance Plus Oils and Lubricants

PERFORMANCE UNDER THE MOST EXTREME CONDITIONS.

HIGH MILEAGE SYNTHETIC BLEND PASSENGER CAR MOTOR OIL

PERFORMANCE PLUS™ High Mileage Synthetic Blend Passenger Car Motor Oils are specially formulated to provide protection for vehicles with over 75,000 miles. Blended with high-quality Group II+ base oils plus state-of-the-art performance additives to help stop leaks and reduce oil consumption by conditioning seals and gaskets while reducing sludge and damaging deposits. They are engineered to meet the latest demands of turbocharged gasoline, propane, and natural gas engines in passenger cars and light duty trucks. They meet ILSAC GF-5 specifications and the 5W-30, 5W-20 and 10W-30 grades are Resource Conserving and with an API Service Category of API SN PLUS, they are backwards compatible (SN and SM) and designed to keep engines clean by fighting sludge; provide oxidation control; and protect engines against low speed pre-ignition (LSPI) in turbo-charged gasoline direct injection engines (TGDI).

Performance Plus® Product Name meets, exceeds, or carries the approvals to match the performance requirements of the following: Ford WSS-M2C-946-A (5W-30) and GM 6094M.

PERFORMANCE PLUS PROPERTIES

SAE Viscosity Grade	5W-30	10W-30
API Service Category	SN Plus	SN Plus
ILSAC Specification	GF-5	GF-5
Kinematic Viscosity cSt @ 40°C cSt @ 100°C	64.5 10.7	65.0 10.2
Viscosity Index	157	144
CCS Viscosity cP @ -30°C cP @ -25°C	5,400 -	- 5,100
MRV Viscosity cP @ -30°C cP @ -35°C	- 21,000	15,000 -
TBN	7.3	7.3
Evaporative Loss, NOACK, wt%	< 15	< 15
Specific Gravity 15.6°C (60°F)	0.858	0.862
Flash Point, °C (°F)	204 (399)	206 (403)
Pour Point, °C (°F)	-39 (-38)	-42 (-44)
Color (ASTM)	3.0	3.0
Sulfated Ash, wt%	0.92	0.92

For additional questions, please contact your Performance Plus® Products Sales Representative.

Note: Values shown above are representative of current production and may vary within modest ranges. Rev. 10/18