



# Performance Plus Oils and Lubricants

PERFORMANCE UNDER THE MOST EXTREME CONDITIONS.

## dexos1™ Gen 1 FULL SYNTHETIC PASSENGER CAR MOTOR OIL (SN)

PERFORMANCE PLUS™ dexos1™ Gen 1 Full Synthetic Passenger Car Motor Oil are approved and licensed to meet GM's stringent requirements for dexos1™ passenger car engine oils. They are specially formulated with a combination of Group III base oils plus state-of-the art performance additives. And they are engineered to meet or exceed the demands of all engines that specify GM dexos™ approved 0W-20, 5W-20, and 5W-30 engine oils. They also meet or exceed the requirements of Resource Conserving engine oils for API service SN and ILSAC Starburst GF-5, as well as older service categories SM, SL and previous ILSAC categories.

Performance Plus® dexos1™ Gen1 Full Synthetic Passenger Car Motor Oils meets, exceeds, or carries the approvals to match the performance requirements of the following: Ford WSS-M2C-947-A (0W-20), Ford WSS-M2C-946-A (5W-30), Ford WSS-M2C-945-A (5W-20), Chrysler MS-6395, and GM 6094M.

PERFORMANCE PLUS PROPERTIES			
SAE Viscosity Grade	0W-20	5W-20	5W-30
GM Approved	dexos1™	dexos1™	dexos1™
API Service Category	SN	SN	SN
ILSAC Specification	GF-5	GF-5	GF-5
Kinematic Viscosity			
cSt @ 40°C	8.4	8.5	11.0
cSt @ 100°C	44.8	48.3	63.9
Viscosity Index	167	154	165
CCS Viscosity			
cP @ -30°C	5600	-	-
cP @ -25°C	-	4800	4900
MRV Viscosity			
cP @ -40°C	< 40000	-	-
cP @ -35°C	-	< 40000	< 40000
Evaporative Loss, NOACK, wt%	< 13	< 13	< 13
Specific Gravity 15.6°C (60°F)	0.846	0.850	0.849
Flash Point, °C (°F)	230 (446)	230 (446)	232 (450)
Pour Point, °C (°F)	-42 (-44)	-39 (-38)	-36 (-33)
Color (ASTM)	3.0	3.0	3.0
Sulfated Ash, wt%	< 1.0	< 1.0	< 1.0

For additional questions, please contact your Performance Plus® Products Sales Representative.

Note: Values shown above are representative of current production and may vary within modest ranges. Rev. 10/18