



Performance Plus Oils and Lubricants

PERFORMANCE UNDER THE MOST EXTREME CONDITIONS.

dexos1™ Gen 2 FULL SYNTHETIC PASSENGER CAR MOTOR OIL

PERFORMANCE PLUS® dexos1™ Gen 2 Full Synthetic Passenger Car Motor Oils are specially engineered with premium state-of-the-art performance additives to provide superior wear protection, improve fuel economy, perform under extreme conditions (low and high temperatures), and extend engine life. They are approved and licensed to meet General Motors' stringent requirements for dexos1™ licensed passenger car engine oils; designed to meet and exceed the latest API Service Category of API SN PLUS making them backwards compatible (SN and SM); and formulated to keep engines clean by fighting sludge; provide oxidation control; and protect engines against low speed pre-ignition (LSPI) in turbo-charged gasoline direct injection engines (TGDI). They are Resource Conserving passenger car motor oils and meet the latest ILSAC specification of GF-5.

Performance Plus® dexos1™ Gen 2 Full Synthetic Passenger Car Motor Oils meets, exceeds, or carries the approvals to match the performance requirements of the following: Ford WSS-M2C-947-A (0W-20), Ford WSS-M2C-946-A (5W-30), Chrysler MS-6395, and GM 6094M.

PERFORMANCE PLUS PROPERTIES

	0W-20	5W-30
SAE Viscosity Grade	0W-20	5W-30
GM Approved	dexos1™ Gen 2	dexos1™ Gen 2
API Service Category	SN Plus	SN Plus
ILSAC Specification	GF-5	GF-5
Kinematic Viscosity cSt @ 40°C cSt @ 100°C	44.2 8.3	61.1 10.9
Viscosity Index	166	172
CCS Viscosity cP @ -30°C cP @ -25°C	5,600 -	- 4,000
MRV Viscosity cP @ -40°C cP @ -35°C	< 40,000 -	- < 40,000
Evaporative Loss, NOACK, wt%	< 13	< 13
Specific Gravity 15.6°C (60°F)	0.846	0.847
Flash Point, °C (°F)	226 (439)	228 (442)
Pour Point, °C (°F)	-42 (-44)	-39 (-38)
Color (ASTM)	3.0	3.0
Sulfated Ash, wt%	< 1.0	0.92

For additional questions, please contact your Performance Plus® Products Sales Representative.

Note: Values shown above are representative of current production and may vary within modest ranges. Rev. 10/18