

Material Name: QSOL™ 300 CLEANING SOLVENT SDS ID: 82836

Section 1 - PRODUCT AND COMPANY IDENTIFICATION

Material Name

QSOL™ 300 CLEANING SOLVENT

Product Code

6660

Synonyms

Cyclic, branched, or linear, completely methylated siloxanes (VMS)

Product Use

Cleaning and degreasing metal parts. This solvent is qualified under U.S. Military Detail Specification MIL-PRF-32295 as a non-aqueous, low-VOC, HAP-free cleaner and is included on the U.S. Military Qualified Products List (QPL). Also see Section 9: Volatile Organic Compounds. If this product is used in combination with other products, refer to the Safety Data Sheet for those products. SDS for use in Canada and the U.S.

Restrictions on Use

None known.

MANUFACTURER/SUPPLIER

Safety-Kleen Systems, Inc. 2600 North Central Expressway Suite 200 Richardson, TX 75080 www.safety-kleen.com IMPORTER/DISTRIBUTOR, Canada

Safety-Kleen Canada, Inc. 25 Regan Road Brampton, Ontario, Canada L1A 1B2

Phone: 1-800-669-5740 Emergency Phone #: 1-800-468-1760

Issue Date

November 8, 2016

Supersedes Issue Date

September 4, 2014

Original Issue Date

December 1, 1989

Section 2 - HAZARDS IDENTIFICATION

Classification in accordance with Schedule 1 of Hazardous Products Regulations (HPR) (SOR/2015-17) and 29 CFR 1910.1200

Flammable Liquids - Category 4

Specific Target Organ Toxicity – Repeated Exposure, Category 2 (lungs)

GHS Label Elements

Symbol(s)



Signal Word

Warning

Material Name: QSOL™ 300 CLEANING SOLVENT

Hazard Statement(s)

Combustible liquid.

May cause damage to lungs through prolonged or repeated exposure.

Precautionary Statement(s)

Prevention

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not breathe vapor or mist. Wear protective gloves/protective clothing/eye protection/face protection.

SDS ID: 82836

Response

In case of fire: Use carbon dioxide, regular foam, dry chemical, water spray, or water fog.

Storage

Store in a well-ventilated place. Keep cool.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards

None known.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

CAS	Component Name	Percent
541-02-6	Decamethylcyclopentasiloxane	97.5-100
69430-24-6	Cyclosiloxanes, dimethyl-	0-3

Section 4 - FIRST AID MEASURES

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention.

Skin

IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Remove contaminated clothing and wash before use.

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists, get medical advice/attention.

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

Most Important Symptoms/Effects

Acute

No information on significant adverse effects.

Delayed

Lung damage.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically and supportively. Treatment may vary with condition of victim and specifics of incident. Call 1-800-468-1760 for additional information.

Section 5 - FIRE FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media

Carbon dioxide, regular foam, dry chemical, water spray, or water fog.

Page 2 of 8 Rev. 11/16

Material Name: QSOL™ 300 CLEANING SOLVENT SDS ID: 82836

Unsuitable Extinguishing Media

Do not use high-pressure water streams.

Special Hazards Arising from the Chemical

Combustible liquid and vapor. Avoid friction, static electricity and sparks. The vapor is heavier than air. Vapors or gases may ignite at distant ignition sources and flash back. Empty containers may contain product residue. Runoff to sewer may cause a fire or explosion hazard.

Hazardous Combustion Products

Decomposition and combustion materials may be toxic. Burning may produce formaldehyde, silicon dioxide, carbon monoxide and unidentified organic compounds.

Fire Fighting Measures

Move container from fire area if it can be done without risk, Cool containers with water spray until well after the fire is out. Fight fire from maximum distance or use unmanned hose holders or monitor nozzles. Withdraw immediately in case of rising sound from venting safety device or any discoloration of tanks due to fire. Avoid inhalation of material or combustion by-products. Stay upwind and keep out of low areas. Apply water from a protected location or from a safe distance. Dike for later disposal.

Special Protective Equipment and Precautions for Firefighters

A positive-pressure, self-contained breathing apparatus (SCBA) and full-body protective equipment are required for fire emergencies.

Section 6 - ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Wear personal protective clothing and equipment, see Section 8. Avoid release to the environment.

Methods and Materials for Containment and Cleaning Up

Remove all ignition sources. Do not touch or walk through spilled product. Stop leak if you can do it without risk. Wear protective equipment and provide engineering controls as specified in SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Ventilate area and avoid breathing vapor or mist. A vapor suppressing foam may be used to reduce vapors. Contain spill away from surface water and sewers. Contain spill as a liquid for possible recovery, or sorb with compatible sorbent material and shovel with a clean, sparkproof tool into a sealable container for disposal. Additionally, for large spills: Water spray may reduce vapor, but may not prevent ignition in closed spaces. Dike far ahead of liquid spill for collection and later disposal.

Section 7 - HANDLING AND STORAGE

Precautions for Safe Handling

Keep away from heat, sparks, or flame. Where flammable mixtures may be present, equipment safe for such locations should be used. Use clean, sparkproof tools and explosion-proof equipment. When transferring product, metal containers, including trucks and tank cars, should be grounded and bonded. Do not breathe vapor or mist. Use in a well ventilated area. Avoid contact with eyes, skin, clothing, shoes. Do not smoke while using this product.

Conditions for Safe Storage, Including any Incompatibilities

Keep container tightly closed when not in use and during transport. Store containers below 85°F (30°C). Store containers in a cool, dry place. Do not pressurize, cut, weld, braze, solder, drill, or grind containers. Keep containers away from heat, flame, sparks, static electricity, or other sources of ignition. Empty product containers may retain product residue and can be dangerous. See SECTION 14: TRANSPORTATION INFORMATION for Packing Group information.

Incompatible Materials

Avoid strong oxidizing materials.

Ρ Rev. 11/16

Material Name: QSOL™ 300 CLEANING SOLVENT SDS ID: 82836

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Component Exposure Limits

Canada, ACGIH, OSHA, and NIOSH have not developed exposure limits for any of this product's components.

ACGIH - Threshold Limit Values - Biological Exposure Indices (BEI)

There are no biological limit values for any of this product's components.

Engineering Controls

Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits. Where adequate general ventilation is unavailable, use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below applicable exposure limits.

Individual Protection Measures, such as Personal Protective Equipment Eye/face protection

Wear safety glasses. Additional protection like goggles, face shields, or respirators may be needed dependent upon anticipated use and concentrations of vapors or mists. Eye wash fountain and emergency showers are recommended. Contact lens use is not recommended.

Respiratory Protection

Use NIOSH-certified P- or R- series particulate filter and organic vapor cartridges when concentration of vapor or mist exceeds applicable exposure limits. Protection provided by air purifying respirators is limited. Do not use N-rated respirators. Selection and use of respiratory protective equipment should be in accordance in the USA with OSHA General Industry Standard 29 CFR 1910.134; or in Canada with CSA Standard Z94.4.

Glove Recommendations

Where skin contact is likely, wear chemical impervious protective gloves; use of natural rubber (latex) or equivalent gloves is not recommended. To avoid prolonged or repeated contact with product where spills and splashes are likely, wear appropriate chemical-resistant faceshield, boots, apron, whole body suits or other protective clothing.

Protective Materials

Personal protective equipment should be selected based upon the conditions under which this material is used. A hazard assessment of the work area for PPE requirements should be conducted by a qualified professional pursuant to regulatory requirements. The following PPE should be considered the minimum required: Safety glasses, gloves, and lab coat or apron.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Clear, colorless liquid	Physical State	Liquid
Odor	Odorless	Color	Clear, colorless
Odor Threshold	Not available	рН	Not available
Melting Point	-38 °C (-36 °F Approximate)	Boiling Point	210 °C (410 °F)
Boiling Point Range	Not available	Freezing point	Not available
Evaporation Rate	<1 (Butyl acetate = 1)	Flammability (solid, gas)	Not available
Autoignition Temperature	Not available	Flash Point	77 °C (170 °F Approximate)
Lower Explosive Limit	Not available	Decomposition temperature	Not available

Page 4 of 8 Rev. 11/16

Material Name: QSOL™ 300 CLEANING SOLVENT SDS ID: 82836

Upper Explosive Limit Not available Vapor Pressure 1.3 mmHg @ 68 °F (20 °C

Approximate)

Vapor Density (air=1) Not available **Specific Gravity (water=1)** 0.95 (Water = 1)

Water Solubility (Insoluble) Partition coefficient: n-Not available

octanol/water

Viscosity Not available Solubility (Other) Not available

Density 7.9 lb/ US gal (950 g/l) **Molecular Weight** Not available

100 WT %; 7.9 LB/US gal; 950 g/L As per 40 CFR Part 51.100(s)

VOC Vapor Pressure @ $20^{\circ}C = 1.3$ mm Hg; Non-photochemically reactive This product has been certified as a Clean Air Solvent, having passed a chemical analysis performed by California's South Coast Air Quality Management District (SCAQMD) Laboratory. It complies with the Volatile Organics (VOC) requirement

Volatile Organic
Compounds (As
Regulated)

solvent requirements of the Bay Area Air Quality Management District (BAAQMD) Regulation 8, Rule 16, because the cleaning solution is composed of branched, cyclic,

or linear complement methylated siloxane (VMS).

Other Information

No additional information is available.

Section 10 - STABILITY AND REACTIVITY

Reactivity

No reactivity hazard is expected.

Chemical Stability

Stable under normal temperatures and pressures.

Possibility of Hazardous Reactions

Will not polymerize under normal temperature and pressure conditions.

Conditions to Avoid

Heat, sparks, or flame and incompatible materials.

Incompatible Materials

Avoid strong oxidizing materials.

Hazardous decomposition products

None under normal temperatures and pressures. See also SECTION 5: HAZARDOUS COMBUSTION PRODUCTS.

Section 11 - TOXICOLOGICAL INFORMATION

Information on Likely Routes of Exposure

Inhalation

This product contains a siloxane compound which may generate formaldehyde vapors when exposed to temperatures exceeding 302°F in the presence of air. Formaldehyde is a known cancer hazard, causes irritation and sensitization to the respiratory system, causes throat irritation, and is extremely toxic.

Skin Contact

No information on significant adverse effects.

Eye Contact

No information on significant adverse effects.

Page 5 of 8 Rev. 11/16

Material Name: QSOL™ 300 CLEANING SOLVENT

Ingestion

No information on significant adverse effects.

Acute and Chronic Toxicity

Component Analysis - LD50/LC50

The components of this material have been reviewed in various sources and the following selected endpoints are published:

SDS ID: 82836

Decamethylcyclopentasiloxane (541-02-6)

Oral LD50 Rat >24134 mg/kg

Cyclosiloxanes, dimethyl- (69430-24-6)

Oral LD50 Rat >16 mL/kg

Product Toxicity Data

Acute Toxicity Estimate

Oral	> 2000 mg/kg
------	--------------

Immediate Effects

No information on significant adverse effects.

Delayed Effects

No information on significant adverse effects. May cause lung damage.

Irritation/Corrosivity Data

May cause irritation of the skin and eyes. May cause respiratory tract irritation.

Respiratory Sensitization

No information available for the product.

Dermal Sensitization

No information available for the product.

Component Carcinogenicity

None of this product's components are listed by ACGIH, IARC, NTP, NIOSH, or OSHA

This product contains a siloxane compound which may generate formaldehyde vapors when exposed to temperatures exceeding 302°F in the presence of air. Formaldehyde is a known carcinogen.

Germ Cell Mutagenicity

Based on best current information, there is no known mutagenicity associated with this product.

Tumorigenic Data

Based on best current information, there is no known teratogenicity associated with this product.

Reproductive Toxicity

Based on best current information, there is no known reproductive toxicity associated with this product.

Specific Target Organ Toxicity - Single Exposure

No information on significant adverse effects.

Specific Target Organ Toxicity - Repeated Exposure

Lung damage.

Aspiration hazard

No information available for the product.

Medical Conditions Aggravated by Exposure

Medical conditions may include respiratory disorders.

Additional Data

Respiratory disorders.

Section 12 - ECOLOGICAL INFORMATION

Ecotoxicity

According to the California Code of Regulations, a toxicity to aquatic life is determined using an acute 96 hour bioassay. A material is non-hazardous if the LC50 is >500 mg/L. This product passed the bioassay and is considered non-hazardous.

Page 6 of 8 Rev. 11/16

Material Name: QSOL™ 300 CLEANING SOLVENT SDS ID: 82836

Component Analysis - Aquatic Toxicity

Not available.

Persistence and Degradability

This product is not expected to persist in the environment.

Bioaccumulative Potential

This material is believed not to bioaccumulate.

Mobility

Expected to have high mobility in soil.

Other Toxicity

No additional information is available.

Section 13 - DISPOSAL CONSIDERATIONS

Disposal Methods

Dispose of in accordance with all applicable federal, state and local regulations. Regulations may also apply to empty containers. The responsibility for proper waste disposal lies with the owner of the waste.

Processing, use, or contamination by the user may change the waste code(s) applicable to the disposal of this product. Contact Safety-Kleen regarding proper recycling or disposal.

Section 14 - TRANSPORT INFORMATION

Transportation Regulations

Non-Bulk Packages (less than or equal to 119 gallons) (Shipments via vessel and aircraft must use bulk shipping description.): Shipping Name: Cleaning compounds

(decamethylcyclopentasiloxane)(Not US DOT Regulated)

Bulk Packages

Shipping Name: Combustible liquid, n.o.s. (decamethylcyclopentasiloxane)

UN/NA: NA1993 Hazard Class: Combustible liquid Packing Group: III Required Placards: Class 3,

NA1993

TDG Shipping Name: Not regulated.

Section 15 - REGULATORY INFORMATION

Canada Regulations

CEPA - Priority Substances List

None of this product's components are on the list.

Ozone Depleting Substances

None of this product's components are on the list

Council of Ministers of the Environment - Soil Quality Guidelines

None of this product's components are on the list

Council of Ministers of the Environment - Water Quality Guidelines

None of this product's components are on the list

U.S. Federal Regulations

None of this products components are listed under SARA Sections 302/304 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), CERCLA (40 CFR 302.4), TSCA 12(b), or require an OSHA process safety plan.

SARA Section 311/312 (40 CFR 370 Subparts B and C)

Acute Health: Yes Chronic Health: Yes Fire: Yes Pressure: No Reactivity: No

U.S. State Regulations

None of this product's components are listed on the state lists from CA, MA, MN, NJ, or PA.

Page 7 of 8 Rev. 11/16

SDS ID: 82836

Material Name: QSOL™ 300 CLEANING SOLVENT

Component Analysis - Inventory

Decamethylcyclopentasiloxane (541-02-6), Cilosiloxanes, dimethyl – (69430-24-6)



Section 16 - OTHER INFORMATION

NFPA Ratings: Health: 1 Fire: 2 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

Summary of Changes

Revision to comply with WHMIS 2015.

ACGIH - American Conference of Governmental Industrial Hygienists; BOD - Biochemical Oxygen Demand; C - Celsius; CA - Canada; CA/MA/MN/NJ/PA - California/Massachusetts/Minnesota/New Jersey/Pennsylvania*; CAS - Chemical Abstracts Service; CFR - Code of Federal Regulations (US); CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CLP -Classification, Labelling, and Packaging; CPR - Controlled Products Regulations; DOT - Department of Transportation; DSL - Domestic Substances List; EPA - Environmental Protection Agency; F - Fahrenheit; IDL - Ingredient Disclosure List; IDLH - Immediately Dangerous to Life and Health; IMDG - International Maritime Dangerous Goods; LEL - Lower Explosive Limit; LLV - Level Limit Value; LOLI - List Of LIstsTM - ChemADVISOR's Regulatory Database; MAK - Maximum Concentration Value in the Workplace; MEL - Maximum Exposure Limits; NDSL - Non-Domestic Substance List (Canada); NFPA -National Fire Protection Agency; NIOSH - National Institute for Occupational Safety and Health; NJTSR -New Jersey Trade Secret Registry; NTP - National Toxicology Program; OSHA - Occupational Safety and Health Administration; PEL- Permissible Exposure Limit; RCRA - Resource Conservation and Recovery Act; SARA - Superfund Amendments and Reauthorization Act; STEL - Short-term Exposure Limit; TDG -Transportation of Dangerous Goods; TLV - Threshold Limit Value; TSCA - Toxic Substances Control Act; TWA - Time Weighted Average; UEL - Upper Explosive Limit; UN/NA - United Nations /North American; US - United States; WHMIS - Workplace Hazardous Materials Information System (Canada).

Other Information

Disclaimer:

User assumes all risks incident to the use of this product. To the best of our knowledge, the information contained herein is accurate. However, Safety-Kleen assumes no liability whatsoever for the accuracy or completeness of the information contained herein. No representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose or of any other nature are made hereunder with respect to the information or the product to which the information refers. The data contained on this sheet apply to the product as supplied to the user.

Rev. 11/16 Page 8 of 8

Dogo O of O	