



# Performance Plus Metalworking Soluble S

Safety Data Sheet

SDS ID: 820393

## Section 1 - PRODUCT AND COMPANY IDENTIFICATION

### Material Name

Performance Plus Metalworking Soluble S

### Product Code

33MSSXX

### Synonyms

None.

### Product Use

Metal working fluids. If this product is used in combination with other products, refer to the Safety Data Sheet for those products.

### Restrictions on Use

None known.

### FOR PRODUCT MANUFACTURED IN THE U.S.A.:

#### MANUFACTURER

Kleen Performance Products  
2600 North Central Expressway  
Suite 200  
Richardson, TX 75080

#### SUPPLIER (In Canada)

Safety-Kleen Canada, Inc.  
25 Regan Road  
Brampton, Ontario, Canada L1A 1B2

### FOR PRODUCT MANUFACTURED IN CANADA:

#### MANUFACTURER

Kleen Performance Products  
25 Regan Road  
Brampton, Ontario, Canada L1A 1B2

#### SUPPLIER (In the U.S.A)

Safety-Kleen Systems, Inc.  
2600 North Central Expressway  
Suite 200  
Richardson, TX 75080

[www.safety-kleen.com](http://www.safety-kleen.com)

Phone: 1-800-669-5740

Emergency Phone #: 1-800-468-1760

### Issue Date

April 11, 2019

### Supersedes Issue Date

New Issue SDS

### Original Issue Date

April 11, 2019

## Section 2 - HAZARDS IDENTIFICATION

### Classification in accordance with paragraph (d) of 29 CFR 1910.1200.

Flammable Liquids - Category 4

Skin Corrosion/Irritation - Category 2

Serious Eye Damage/Eye Irritation - Category 2A

### GHS Label Elements

#### Symbol(s)



# Safety Data Sheet

Material Name: Performance Plus Metalworking Soluble-S

SDS ID: 820393

## Signal Word

Warning

## Hazard Statement(s)

Combustible liquid.

Causes skin irritation and serious eye irritation.

## Precautionary Statement(s)

### Prevention

Keep away from heat/sparks/open flame/hot surfaces - No smoking. Wear protective gloves/protective clothing/eye protection/face protection. Wash thoroughly after handling.

### Response

In case of fire: Use carbon dioxide, regular foam, dry chemical, water spray, water fog. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

### Storage

Store in a well-ventilated place. Keep cool.

### Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

### Other Hazards

Repeated exposure may cause skin dryness or cracking.

## Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

CAS	Component Name	Percent
64742-58-1	Lubricating oils, petroleum, hydrotreated spent	80
Mixture	Mineral oil	1.8-3.6

## Section 4 - FIRST AID MEASURES

### Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention, if needed.

### Skin

IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse.

### Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists, get medical advice/attention.

### Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

### Most Important Symptoms/Effects

#### Acute

Causes skin irritation and serious eye irritation.

#### Delayed

Repeated exposure may cause skin dryness or cracking.

### Indication of any immediate medical attention and special treatment needed

Treat symptomatically and supportively.

# Safety Data Sheet

Material Name: Performance Plus Metalworking Soluble-S

SDS ID: 820393

## Section 5 - FIRE FIGHTING MEASURES

### Extinguishing Media

#### Suitable Extinguishing Media

Carbon dioxide, regular foam, dry chemical, water spray, water fog. Water or foam may cause frothing.

#### Unsuitable Extinguishing Media

Do not use high-pressure water streams.

### Special Hazards Arising from the Chemical

Combustible liquid. Vapors are heavier than air and may flashback. Avoid friction, static electricity and sparks. Vapors or gases may ignite at distant ignition sources and flash back.

### Hazardous Combustion Products

Decomposition and combustion materials may be toxic. Burning may produce carbon monoxide and unidentified organic compounds.

### Fire Fighting Measures

Move container from fire area if it can be done without risk. Cool containers with water spray until well after the fire is out. Stay away from the ends of tanks. Cool containers with water from unmanned hose holder or monitor nozzles until well after fire is out. Keep unnecessary people away, isolate hazard area and deny entry. Cool containers with water spray until well after the fire is out.

### Special Protective Equipment and Precautions for Firefighters

Wear full protective fire fighting gear including self contained breathing apparatus (SCBA) for protection against possible exposure.

## Section 6 - ACCIDENTAL RELEASE MEASURES

### Personal Precautions, Protective Equipment and Emergency Procedures

Wear personal protective clothing and equipment, see Section 8. Avoid release to the environment.

### Methods and Materials for Containment and Cleaning Up

Remove all ignition sources. Do not touch or walk through spilled product. Stop leak if you can do it without risk. Wear protective equipment and provide engineering controls as specified in SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Ventilate area and avoid breathing vapor or mist. Contain spill away from surface water and sewers. Contain spill as a liquid for possible recovery, or sorb with compatible sorbent material and shovel with a clean, spark proof tool into a sealable container for disposal. Additionally, for large spills: Dike far ahead of liquid spill for collection and later disposal.

## Section 7 - HANDLING AND STORAGE

### Precautions for Safe Handling

Keep away from heat, sparks and naked flames. Where flammable mixtures may be present, equipment safe for such locations should be used. Use clean tools and explosion-proof equipment. When transferring large volumes of product, metal containers, including trucks and tank cars, should be grounded and bonded. This product has a low vapor pressure and is not expected to present an inhalation hazard under normal temperatures and pressures. However, when aerosolizing, misting, or heating this product, do not breathe vapor or mist. Use in a well ventilated area. Avoid contact with eyes Skin clothing shoes.

### Conditions for Safe Storage, Including any Incompatibilities

Store in a well-ventilated place. Keep cool.

Further information: Storage. Keep container tightly closed when not in use and during transport. Store containers in a cool, dry place. Do not pressurize, cut, weld, braze, solder, drill, or grind containers. Keep containers away from flame, sparks, static electricity, or other sources of ignition. Empty product containers may retain product residue and can be dangerous.

# Safety Data Sheet

Material Name: Performance Plus Metalworking Soluble-S

SDS ID: 820393

## Incompatible Materials

Strong oxidizing materials, strong acids.

## Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

### Component Exposure Limits

Canada, ACGIH, OSHA, and NIOSH have not developed exposure limits for any of this product's components.

### ACGIH - Threshold Limit Values - Biological Exposure Indices (BEI)

There are no biological limit values for any of this product's components.

### Engineering Controls

Provide general ventilation. Where adequate general ventilation is unavailable, use process enclosures, local exhaust ventilation, or other engineering controls.

### Individual Protection Measures, such as Personal Protective Equipment

#### Eye/face protection

Wear safety glasses. Additional protection like goggles, face shields, or respirators may be needed dependent upon anticipated use and concentrations of mists or vapors. Eye wash fountain and emergency showers are recommended. Contact lens use is not recommended.

#### Respiratory Protection

A respiratory protection program which meets USA's OSHA General Industry Standard 29 CFR 1910.134 or Canada's CSA Standard Z94.4-M1982 requirements must be followed whenever workplace conditions warrant a respirator's use. Consult a qualified Industrial Hygienist or Safety Professional for respirator selection guidance.

#### Glove Recommendations

Where skin contact is likely, wear gloves impervious to product; use of natural rubber (latex) or equivalent gloves is not recommended. To avoid prolonged or repeated contact where spills and splashes are likely, wear appropriate chemical-resistant face shield, boots, apron, whole body suits or other protective clothing. When product is heated and skin contact is likely, wear heat-resistant gloves, boots, and other protective clothing.

#### Protective Materials

Personal protective equipment should be selected based upon the conditions under which this material is used. A hazard assessment of the work area for PPE requirements should be conducted by a qualified professional pursuant to regulatory requirements. The following PPE should be considered the minimum required: Safety glasses, Gloves, and Lab coat or apron.

## Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance</b>	Amber liquid	<b>Physical State</b>	Liquid
<b>Odor</b>	Petroleum	<b>Color</b>	Amber.
<b>Odor Threshold</b>	Not available	<b>pH</b>	Not available
<b>Melting Point</b>	Not available	<b>Boiling Point</b>	Not available
<b>Boiling Point Range</b>	Not available	<b>Freezing point</b>	Not available
<b>Evaporation Rate</b>	Not available	<b>Flammability (solid, gas)</b>	Not available
<b>Autoignition Temperature</b>	Not available	<b>Flash Point</b>	65.55 °C
<b>Lower Explosive Limit</b>	Not available	<b>Decomposition temperature</b>	Not available
<b>Upper Explosive Limit</b>	Not available	<b>Vapor Pressure</b>	<0.1 mmHg

# Safety Data Sheet

Material Name: Performance Plus Metalworking Soluble-S

SDS ID: 820393

Vapor Density (air=1)	Not available	Specific Gravity (water=1)	0.87
Water Solubility	Not available	Partition coefficient: n-octanol/water	Not available
Viscosity	>20.5 mm <sup>2</sup> /s 40 °C (104 °F)	Kinematic viscosity	Not available
Solubility (Other)	Not available	Density	Not available
Physical Form	Liquid.	Molecular Weight	Not available

## Section 10 - STABILITY AND REACTIVITY

### Reactivity

No reactivity hazard is expected.

### Chemical Stability

Stable under normal temperatures and pressures.

### Possibility of Hazardous Reactions

Will not polymerize.

### Conditions to Avoid

Avoid heat, flames, sparks and other sources of ignition

### Incompatible Materials

Strong oxidizing agents, strong acids.

### Hazardous decomposition products

Carbon monoxide and carbon dioxide.

## Section 11 - TOXICOLOGICAL INFORMATION

### Information on Likely Routes of Exposure

#### Inhalation

No information on significant adverse effects.

#### Skin Contact

Repeated exposure may cause skin dryness or cracking. Causes skin irritation.

#### Eye Contact

Causes serious eye irritation.

#### Ingestion

No information on significant adverse effects.

### Acute and Chronic Toxicity

#### Component Analysis - LD50/LC50

The components of this material have been reviewed in various sources and the following selected endpoints are published:

#### Lubricating oils, petroleum, hydrotreated spent (64742-58-1)

Oral LD50 Rat >2000 mg/kg; Dermal LD50 Rabbit >4480 mg/kg

### Product Toxicity Data

#### Acute Toxicity Estimate

Dermal	> 2000 mg/kg
Oral	> 2000 mg/kg

### Immediate Effects

Causes skin irritation. Causes serious eye irritation.

# Safety Data Sheet

Material Name: Performance Plus Metalworking Soluble-S

SDS ID: 820393

## Delayed Effects

Repeated exposure may cause skin dryness or cracking.

## Irritation/Corrosivity Data

Causes skin irritation. Causes serious eye irritation.

## Respiratory Sensitization

No information available for the product.

## Dermal Sensitization

No information available for the product.

## Component Carcinogenicity

None of this product's components are listed by ACGIH, IARC, NTP, DFG or OSHA.

## Germ Cell Mutagenicity

No information available for the product.

## Tumorigenic Data

No data available

## Reproductive Toxicity

No information available for the product.

## Specific Target Organ Toxicity - Single Exposure

No information on significant adverse effects.

## Specific Target Organ Toxicity - Repeated Exposure

No information on significant adverse effects.

## Aspiration hazard

No information available for the product.

## Medical Conditions Aggravated by Exposure

Individuals with pre-existing respiratory tract (nose, throat, and lungs), eye, and/or skin disorders may have increased susceptibility to the effects of exposure.

## Section 12 - ECOLOGICAL INFORMATION

### Component Analysis - Aquatic Toxicity

No LOLI ecotoxicity data are available for this product's components.

### Persistence and Degradability

No information available for the product.

### Bioaccumulative Potential

No information available for the product.

### Mobility

No information available for the product.

### Other Toxicity

No additional information is available.

## Section 13 - DISPOSAL CONSIDERATIONS

### Disposal Methods

Dispose in accordance with federal, state, provincial, and local regulations. Regulations may also apply to empty containers. The responsibility for proper waste disposal lies with the owner of the waste. Contact Kleen Performance Products regarding proper recycling or disposal.

### Component Waste Numbers

The U.S. EPA has not published waste numbers for this product's components.

# Safety Data Sheet

**Material Name: Performance Plus Metalworking Soluble-S**

**SDS ID: 820393**

## Section 14 - TRANSPORT INFORMATION

**US DOT Information:** Not regulated for transport.

**IATA Information:** Not regulated for transport.

**IMDG Information:** Not regulated for transport.

**TDG Information:** Not regulated for transport.

**International Bulk Chemical Code**

This material does not contain any chemicals required by the IBC Code to be identified as dangerous chemicals in bulk.

## Section 15 - REGULATORY INFORMATION

**U.S. Federal Regulations**

None of this product's components are listed under SARA Sections 302/304 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), CERCLA (40 CFR 302.4), TSCA 12(b), or require an OSHA process safety plan.

**SARA Section 311/312 (40 CFR 370 Subparts B and C) reporting categories**

Flammable; Skin Corrosion/Irritation; Serious Eye Damage/Eye Irritation

**U.S. State Regulations**

None of this product's components are listed on the state lists from CA, MA, MN, NJ or PA.

**California Safe Drinking Water and Toxic Enforcement Act (Proposition 65)**

Not listed under California Proposition 65.

**Canada Regulations**

**CEPA - Priority Substances List**

None of this product's components are on the list.

**Ozone Depleting Substances**

None of this product's components are on the list.

**Council of Ministers of the Environment - Soil Quality Guidelines**

None of this product's components are on the list.

**Council of Ministers of the Environment - Water Quality Guidelines**

None of this product's components are on the list.

**Component Analysis - Inventory**

**Lubricating oils, petroleum, hydrotreated spent (64742-58-1)**

US	CA	AU	CN	EU	JP - ENCS	JP - ISHL	KR KECI - Annex 1	KR KECI - Annex 2
Yes	DSL	Yes	Yes	EIN	No	No	Yes	No
KR - REACH CCA			MX	NZ	PH	TH-TECI	TW	VN (Draft)
No			Yes	Yes	Yes	No	Yes	Yes

# Safety Data Sheet

**Material Name: Performance Plus Metalworking Soluble-S**

**SDS ID: 820393**

**Mineral oil (Mixture)**

US	CA	AU	CN	EU	JP - ENCS	JP - ISHL	KR KECI - Annex 1	KR KECI - Annex 2
No	No	No	No	No	No	No	No	No
KR - REACH CCA			MX	NZ	PH	TH-TECI	TW	VN (Draft)
No			No	No	No	No	No	No

## Section 16 - OTHER INFORMATION

**NFPA Ratings**

Health: 2 Fire: 2 Instability: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

**Preparation Date**

New: 4/11/2019

**Key / Legend**

ACGIH - American Conference of Governmental Industrial Hygienists; ADR - European Road Transport; AU - Australia; BOD - Biochemical Oxygen Demand; C - Celsius; CA - Canada; CA/MA/MN/NJ/PA - California/Massachusetts/Minnesota/New Jersey/Pennsylvania\*; CAS - Chemical Abstracts Service; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CFR - Code of Federal Regulations (US); CLP - Classification, Labelling, and Packaging; CN - China; CPR - Controlled Products Regulations; DFG - Deutsche Forschungsgemeinschaft; DOT - Department of Transportation; DSD - Dangerous Substance Directive; DSL - Domestic Substances List; EC - European Commission; EEC - European Economic Community; EIN - European Inventory of (Existing Commercial Chemical Substances); EINECS - European Inventory of Existing Commercial Chemical Substances; ENCS - Japan Existing and New Chemical Substance Inventory; EPA - Environmental Protection Agency; EU - European Union; F - Fahrenheit; F - Background (for Venezuela Biological Exposure Indices); IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; ICAO - International Civil Aviation Organization; IDL - Ingredient Disclosure List; IDLH - Immediately Dangerous to Life and Health; IMDG - International Maritime Dangerous Goods; ISHL - Japan Industrial Safety and Health Law; IUCLID - International Uniform Chemical Information Database; JP - Japan; Kow - Octanol/water partition coefficient; KR KECI Annex 1 - Korea Existing Chemicals Inventory (KECI) / Korea Existing Chemicals List (KECL); KR KECI Annex 2 - Korea Existing Chemicals Inventory (KECI) / Korea Existing Chemicals List (KECL) , KR - Korea; LD50/LC50 - Lethal Dose/ Lethal Concentration; LEL - Lower Explosive Limit; LLV - Level Limit Value; LOLI - List Of Lists™ - ChemADVISOR's Regulatory Database; MAK - Maximum Concentration Value in the Workplace; MEL - Maximum Exposure Limits; MX - Mexico; Ne - Non-specific; NFPA - National Fire Protection Agency; NIOSH - National Institute for Occupational Safety and Health; NJTSR - New Jersey Trade Secret Registry; Nq - Non-quantitative; NSL - Non-Domestic Substance List (Canada); NTP - National Toxicology Program; NZ - New Zealand; OSHA - Occupational Safety and Health Administration; PEL - Permissible Exposure Limit; PH - Philippines; RCRA - Resource Conservation and Recovery Act; REACH - Registration, Evaluation, Authorisation, and restriction of Chemicals; RID - European Rail Transport; SARA - Superfund Amendments and Reauthorization Act; Sc - Semi-quantitative; STEL - Short-term Exposure Limit; TCCA - Korea Toxic Chemicals Control Act; TDG - Transportation of Dangerous Goods; TLV - Threshold Limit Value; TSCA - Toxic Substances Control Act; TW - Taiwan; TWA - Time Weighted Average; UEL - Upper Explosive Limit; UN/NA - United Nations /North American; US - United States; VLE - Exposure Limit Value (Mexico); VN (Draft) - Vietnam (Draft); WHMIS - Workplace Hazardous Materials Information System (Canada).



## Safety Data Sheet

**Material Name: Performance Plus Metalworking Soluble-S**

**SDS ID: 820393**

### **Other Information**

#### **Disclaimer:**

User assumes all risks incident to the use of this product. To the best of our knowledge, the information contained herein is accurate. However, Kleen Performance Products assumes no liability whatsoever for the accuracy or completeness of the information contained herein. No representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose or of any other nature are made hereunder with respect to the information or the product to which the information refers. The data contained on this sheet apply to the product as supplied to the user.