



Safety Data Sheet

Material Name: SAFETY-KLEEN HEAVY DUTY LACQUER THINNER

SDS ID: 82343

Section 1 - PRODUCT AND COMPANY IDENTIFICATION

Material Name

SAFETY-KLEEN HEAVY DUTY LACQUER THINNER

Product Code

5850, 5825, 6782

Synonyms

None

Product Use

For cleaning coating equipment (e.g., paint spray guns). If this product is used in combination with other products, refer to the Safety Data Sheet for those products.

Restrictions on Use

THIS PRODUCT IS NOT FOR SALE OR USE IN THE STATE OF CALIFORNIA.

MANUFACTURER

Safety-Kleen Systems, Inc.
2600 North Central Expressway
Suite 200
Richardson, TX 75080
www.safety-kleen.com

SUPPLIER

Safety-Kleen Canada, Inc.
25 Regan Road
Brampton, Ontario, Canada L1A 1B2

Phone: 1-800-669-5740

Emergency Phone #: 1-800-468-1760

Issue Date

June 12, 2019

Supersedes Issue Date

February 8, 2017

Original Issue Date

July 20, 1989

Section 2 - HAZARDS IDENTIFICATION

Classification in accordance with Schedule 1 of Hazardous Products Regulations (HPR)(SOR/2015-17) and paragraph (d) of 29 CFR 1910.1200.

Flammable Liquids - Category 2

Aspiration Hazard - Category 1

Acute Toxicity - Oral - Category 4

Acute Toxicity - Dermal - Category 4

Acute Toxicity - Inhalation - Vapor - Category 2

Skin Corrosion/Irritation - Category 2

Serious Eye Damage/Eye Irritation - Category 1

Germ Cell Mutagenicity - Category 1B

Carcinogenicity - Category 1B

Reproductive Toxicity - Category 2

Specific Target Organ Toxicity - Single Exposure - Category 3

Specific Target Organ Toxicity - Repeated Exposure - Category 2

Safety Data Sheet

Material Name: SAFETY-KLEEN HEAVY DUTY LACQUER THINNER 6782

SDS ID: 82343

GHS Label Elements

Symbol(s)



Signal Word

Danger

Hazard Statement(s)

Highly flammable liquid and vapor.
May be fatal if swallowed and enters airways.
Fatal if inhaled.
Harmful if swallowed or in contact with skin.
Causes skin irritation and serious eye damage.
May cause genetic defects and cancer.
Suspected of damaging fertility or the unborn child.
May cause respiratory irritation and drowsiness or dizziness.
May cause damage to organs through prolonged or repeated exposure.

Precautionary Statement(s)

Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep container tightly closed. Keep away from heat/sparks/open flame/hot surfaces - No smoking. Ground/Bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Take precautionary measures against static discharge. Use only non-sparking tools. Use only outdoors or in a well-ventilated area. Do not breathe fume/gas/mist/vapors/spray. Wear protective gloves/ clothing, eye, face, and respiratory protection. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.

Response

In case of fire: Use carbon dioxide, regular foam, regular dry chemical and water spray.
IF exposed or concerned: Get medical advice/attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER or doctor/physician. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician. IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse. IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting. If vomiting occurs, keep head lower than hips to help prevent aspiration. Rinse mouth.

Storage

Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Statement(s) of Unknown Acute Toxicity

0% of the mixture consists of ingredient(s) of unknown acute toxicity.

Other Hazards

None known.

Safety Data Sheet

Material Name: SAFETY-KLEEN HEAVY DUTY LACQUER THINNER 6782

SDS ID: 82343

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

CAS	Component	Percent
63231-51-6	Aromatic hydrocarbons	30-75
*MIXTURE	Ketones	0-60
**MIXTURE	Aliphatic hydrocarbons	0-60
***MIXTURE	Acetates	0-17
763-69-9	Ethyl 3-ethoxypropanoate	0-17
68475-56-9	Alcohols, C1-3	0-12
****MIXTURE	Other alcohols	0-10
****MIXTURE	Chlorinated solvents	0-1

Component Information/Information on Non-Hazardous Components

- *Mixture of 67-64-1, 78-93-3, 108-10-1, 110-43-0, 107-87-9
- **Mixture of 64741-89-5, 8030-6
- ***Mixture of 123-86-4, 110-19-0, 108-21-4, 108-65-6, 141-78-6
- ****Mixture of 71-36-3, 75-65-0
- ****Mixture of 75-09-2, 127-18-4, 71-55-6

Section 4 - FIRST AID MEASURES

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or doctor/physician.

Skin

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician.

Ingestion

IF SWALLOWED: Aspiration hazard. Do NOT induce vomiting. If vomiting occurs, keep head lower than hips to help prevent aspiration. Rinse mouth. Immediately call a POISON CENTER or doctor/physician.

Most Important Symptoms/Effects

Acute

May be fatal if swallowed and enters airways. Fatal if inhaled. Harmful if swallowed or in contact with skin. Causes skin irritation, central nervous system damage, liver damage, respiratory tract irritation, central nervous system depression, eye burns, kidney damage, blood damage, lung damage (from aspiration).

Delayed

Mutagenic effects, cancer, reproductive effects, and central nervous system, nervous system, kidney, liver, blood, respiratory system, and lung damage.

Indication of any immediate medical attention and special treatment needed

IF exposed: Call a POISON CENTER or doctor/physician. Treat symptomatically and supportively.

Safety Data Sheet

Material Name: SAFETY-KLEEN HEAVY DUTY LACQUER THINNER 6782

SDS ID: 82343

Section 5 - FIRE FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media

Carbon dioxide, regular foam, dry chemical, water spray, or water fog.

Unsuitable Extinguishing Media

Do not use high-pressure water streams.

Special Hazards Arising from the Chemical

Highly flammable liquid and vapor. Vapors may form explosive mixture with air. Vapors are heavier than air and may travel along the ground to some distant source of ignition and flash back. Fire may produce irritating, poisonous and/or corrosive fumes. Runoff may create fire or explosion hazard. Empty product containers may retain product residue and can be dangerous. Containers may rupture or explode.

Hazardous Combustion Products

Burning may produce: Phosgene, chlorides, chloroacetylenes, formaldehyde, peracetic acid, carbon monoxide and unidentified organic compounds.

Fire Fighting Measures

Keep storage containers cool with water spray. Move container from fire area if it can be done without risk. Cool containers with water from unmanned hose holder or monitor nozzles until well after fire is out. Stay away from the ends of tanks. Do not scatter spilled material with high-pressure water streams. Apply water from a protected location or from a safe distance. Avoid inhalation of material or combustion by-products. Let the fire burn. Withdraw immediately in case of rising sound from venting safety device or any discoloration of tanks due to fire. For tank, rail car or tank truck, evacuation radius: 800 meters (1/2 mile). Stay upwind and keep out of low areas. Dike for later disposal.

Special Protective Equipment and Precautions for Firefighters

Wear full protective fire fighting gear including self contained breathing apparatus (SCBA) for protection against possible exposure.

Section 6 - ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Wear personal protective clothing and equipment, see Section 8. Avoid release to the environment.

Methods and Materials for Containment and Cleaning Up

Remove all ignition sources. Do not touch or walk through spilled product. Stop leak if you can do it without risk. Wear protective equipment and provide engineering controls as specified in SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Ventilate area and avoid breathing vapor or mist. A vapor suppressing foam may be used to reduce vapors. Contain spill away from surface water and sewers. Contain spill as a liquid for possible recovery, or sorb with compatible sorbent material and shovel with a clean, sparkproof tool into a sealable container for disposal. Additionally, for large spills: Water spray may reduce vapor, but may not prevent ignition in closed spaces. Dike far ahead of liquid spill for collection and later disposal. There may be specific federal regulatory reporting requirements associated with spills, leaks, or releases of this product. Also see SECTION 15: REGULATORY INFORMATION.

Section 7 - HANDLING AND STORAGE

Precautions for Safe Handling

Keep away from heat, sparks, or flame. Where flammable mixtures may be present, equipment safe for such locations should be used. Use clean, sparkproof tools and explosion-proof equipment. When transferring large quantities of product, metal containers, including trucks and tank cars, should be grounded and bonded.

Safety Data Sheet

Material Name: SAFETY-KLEEN HEAVY DUTY LACQUER THINNER 6782

SDS ID: 82343

Do not breathe vapor or mist. Use in a well ventilated area. Avoid contact with eyes Skin clothing shoes. Do not smoke while using this product. Wash thoroughly after handling.

Conditions for Safe Storage, Including any Incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up.

Keep containers away from heat, flame, sparks, static electricity, or other sources of ignition. Store in a dry place. Do not pressurize, cut, weld, braze, solder, drill, or grind containers. Empty product containers may retain product residue and can be dangerous. See SECTION 14: TRANSPORTATION INFORMATION for Packing Group information.

Incompatible Materials

Combustible materials, strong acids, strong oxidizing materials, alkalis, reducing agents, reactive halogens, reactive metals.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION
--

Component Exposure Limits

Toluene	108-88-3
ACGIH:	20 ppm TWA
NIOSH:	100 ppm TWA ; 375 mg/m3 TWA; 150 ppm STEL ; 560 mg/m3 STEL 500 ppm IDLH
OSHA (US):	200 ppm TWA; 300 ppm Ceiling
Alberta	50 ppm TWA ; 188 mg/m3 TWA Substance may be readily absorbed through intact skin
British Columbia, Nova Scotia, Ontario, Prince Edward Island	20 ppm TWA
Manitoba	20 ppm TWA; Skin - potential for cutaneous absorption
New Brunswick	50 ppm TWA ; 188 mg/m3 TWA; Skin - potential for cutaneous absorption
Northwest Territories, Nunavut	50 ppm TWA; 60 ppm STEL; Skin notation
Quebec	50 ppm TWAEV ; 188 mg/m3 TWAEV; Skin designation
Saskatchewan	50 ppm TWA; 60 ppm STEL; Potentially harmful after absorption through skin or mucous membranes
Yukon	100 ppm TWA ; 375 mg/m3 TWA; 150 ppm STEL ; 560 mg/m3 STEL Skin notation
Naphtha	8030-30-6
NIOSH:	100 ppm TWA ; 400 mg/m3 TWA; 1000 ppm IDLH (10% LEL)
OSHA (US):	100 ppm TWA ; 400 mg/m3 TWA
Alberta, New Brunswick	400 ppm TWA ; 1590 mg/m3 TWA

Safety Data Sheet

Material Name: SAFETY-KLEEN HEAVY DUTY LACQUER THINNER 6782

SDS ID: 82343

British Columbia	(reciprocal calculation method - see OHS Guideline G5.48-12)
Northwest Territories; Nunavut; Saskatchewan	400 ppm TWA; 500 ppm STEL
Quebec	400 ppm TWAEV ; 1590 mg/m3 TWAEV
Yukon	400 ppm TWA (Rubber solvent and Coal tar); 1800 mg/m3 TWA (Rubber solvent and Coal tar) 500 ppm STEL (Rubber solvent and Coal tar); 2250 mg/m3 STEL (Rubber solvent and Coal tar)
2-Pentanone, 4-methyl-	108-10-1
ACGIH:	20 ppm TWA; 75 ppm STEL
NIOSH:	50 ppm TWA ; 205 mg/m3 TWA; 75 ppm STEL ; 300 mg/m3 STEL 500 ppm IDLH
OSHA (US):	100 ppm TWA ; 410 mg/m3 TWA
Alberta, New Brunswick	50 ppm TWA ; 205 mg/m3 TWA; 75 ppm STEL ; 307 mg/m3 STEL
British Columbia, Nova Scotia, Ontario, Prince Edward Island	20 ppm TWA; 75 ppm STEL
Manitoba	20 ppm TWA
Northwest Territories, Nunavut, Saskatchewan	50 ppm TWA; 75 ppm STEL
Quebec	50 ppm TWAEV ; 205 mg/m3 TWAEV; 75 ppm STEV ; 307 mg/m3 STEV
Yukon	100 ppm TWA ; 410 mg/m3 TWA; 125 ppm STEL ; 510 mg/m3 STEL Skin notation
Methyl n-amyl ketone	110-43-0
ACGIH:	50 ppm TWA
NIOSH:	100 ppm TWA ; 465 mg/m3 TWA; 800 ppm IDLH
OSHA (US):	100 ppm TWA ; 465 mg/m3 TWA
Alberta, New Brunswick	50 ppm TWA ; 233 mg/m3 TWA
British Colombia, Manitoba, Nova Scotia, Prince Edward Island	50 ppm TWA
Northwest Territories, Nunavut, Saskatchewan	50 ppm TWA; 60 ppm STEL
Ontario	25 ppm TWA ; 115 mg/m3 TWA
Quebec	50 ppm TWAEV ; 233 mg/m3 TWAEV
Yukon	100 ppm TWA ; 465 mg/m3 TWA; 150 ppm STEL ; 710 mg/m3 STEL

Safety Data Sheet

Material Name: SAFETY-KLEEN HEAVY DUTY LACQUER THINNER 6782

SDS ID: 82343

Methyl ethyl ketone	78-93-3
ACGIH:	200 ppm TWA; 300 ppm STEL
NIOSH:	200 ppm TWA ; 590 mg/m ³ TWA; 300 ppm STEL ; 885 mg/m ³ STEL; 3000 ppm IDLH
OSHA (US):	200 ppm TWA ; 590 mg/m ³ TWA
Alberta, New Brunswick	200 ppm TWA ; 590 mg/m ³ TWA; 300 ppm STEL ; 885 mg/m ³ STEL
British Columbia	50 ppm TWA; 100 ppm STEL
Manitoba	200 ppm TWA
Northwest Territories, Nova Scotia, Nunavut, Ontario, Prince Edward Island, Saskatchewan	200 ppm TWA; 300 ppm STEL
Quebec	50 ppm TWAEV ; 150 mg/m ³ TWAEV; 100 ppm STEV ; 300 mg/m ³ STEV
Yukon	200 ppm TWA ; 590 mg/m ³ TWA; 250 ppm STEL ; 740 mg/m ³ STEL
Methyl propyl ketone	107-87-9
ACGIH:	150 ppm STEL
NIOSH:	150 ppm TWA ; 530 mg/m ³ TWA; 1500 ppm IDLH
OSHA (US):	200 ppm TWA ; 700 mg/m ³ TWA
Alberta, New Brunswick	200 ppm TWA ; 705 mg/m ³ TWA; 250 ppm STEL ; 881 mg/m ³ STEL
British Columbia	150 ppm TWA; 250 ppm STEL
Northwest Territories, Nunavut, Saskatchewan	200 ppm TWA; 250 ppm STEL
Nova Scotia, Ontario, Prince Edward Island	150 ppm STEL
Quebec	150 ppm TWAEV ; 530 mg/m ³ TWAEV
Yukon	200 ppm TWA ; 700 mg/m ³ TWA; 250 ppm STEL ; 875 mg/m ³ STEL
Acetone	67-64-1
ACGIH:	250 ppm TWA; 500 ppm STEL
NIOSH:	250 ppm TWA ; 590 mg/m ³ TWA; 2500 ppm IDLH (10% LEL)
OSHA (US):	1000 ppm TWA ; 2400 mg/m ³ TWA
Alberta	500 ppm TWA ; 1200 mg/m ³ TWA; 750 ppm STEL ; 1800 mg/m ³ STEL
British Columbia, Nova Scotia, Prince Edward Island	250 ppm TWA; 500 ppm STEL

Safety Data Sheet

Material Name: SAFETY-KLEEN HEAVY DUTY LACQUER THINNER 6782

SDS ID: 82343

Manitoba	250 ppm TWA
New Brunswick	500 ppm TWA ; 1188 mg/m3 TWA; 750 ppm STEL ; 1782 mg/m3 STEL
Northwest Territories, Nunavut, Ontario, Saskatchewan	500 ppm TWA; 750 ppm STEL
Quebec	500 ppm TWAEV ; 1190 mg/m3 TWAEV; 1000 ppm STEV ; 2380 mg/m3 STEV
Yukon	1000 ppm TWA ; 2400 mg/m3 TWA; 1250 ppm STEL ; 3000 mg/m3 STEL
Ethyl 3-ethoxypropanoate	763-69-9
Ontario	50 ppm TWA ; 300 mg/m3 TWA
Ethyl acetate	141-78-6
ACGIH:	400 ppm TWA
NIOSH:	400 ppm TWA ; 1400 mg/m3 TWA; 2000 ppm IDLH (10% LEL)
OSHA (US):	400 ppm TWA ; 1400 mg/m3 TWA
Alberta, New Brunswick	400 ppm TWA ; 1440 mg/m3 TWA
British Columbia	150 ppm TWA
Manitoba, Nova Scotia, Ontario, Prince Edward Island	400 ppm TWA
Northwest Territories, Nunavut, Saskatchewan	400 ppm TWA; 500 ppm STEL
Quebec	400 ppm TWAEV ; 1440 mg/m3 TWAEV
Yukon	400 ppm TWA ; 1400 mg/m3 TWA; 400 ppm STEL ; 1400 mg/m3 STEL
Propylene glycol monomethyl ether acetate	108-65-6
British Columbia	50 ppm TWA; 75 ppm STEL
Ontario	50 ppm TWA ; 270 mg/m3 TWA
Isopropyl acetate	108-21-4
ACGIH:	100 ppm TWA; 200 ppm STEL
NIOSH:	1800 ppm IDLH
OSHA (US):	250 ppm TWA ; 950 mg/m3 TWA
Alberta	100 ppm TWA ; 416 mg/m3 TWA; 200 ppm STEL ; 832 mg/m3 STEL
British Columbia, Northwest Territories, Nova Scotia, Nunavut, Ontario, Prince Edward Island, Saskatchewan	100 ppm TWA; 200 ppm STEL
Manitoba	100 ppm TWA

Safety Data Sheet

Material Name: SAFETY-KLEEN HEAVY DUTY LACQUER THINNER 6782

SDS ID: 82343

New Brunswick	250 ppm TWA ; 1040 mg/m3 TWA; 310 ppm STEL ; 1290 mg/m3 STEL
Quebec	250 ppm TWAEV; 1040 mg/m3 TWAEV; 310 ppm STEV; 1290 mg/m3 STEV
Yukon	250 ppm TWA ; 950 mg/m3 TWA; 310 ppm STEL ; 1185 mg/m3 STEL
n-Butyl acetate	123-86-4
ACGIH:	50 ppm TWA; 150 ppm STEL
NIOSH:	150 ppm TWA ; 710 mg/m3 TWA; 200 ppm STEL ; 950 mg/m3 STEL; 1700 ppm IDLH (10% LEL)
OSHA (US):	150 ppm TWA ; 710 mg/m3 TWA
Alberta, New Brunswick	150 ppm TWA ; 713 mg/m3 TWA; 200 ppm STEL ; 950 mg/m3 STEL
British Colombia	20 ppm TWA
Manitoba	50 ppm TWA
Northwest Territories, Nunavut, Ontario, Saskatchewan	150 ppm TWA; 200 ppm STEL
Nova Scotia, Prince Edward Island	50 ppm TWA; 150 ppm STEL
Quebec	150 ppm TWAEV ; 713 mg/m3 TWAEV 200 ppm STEV ; 950 mg/m3 STEV
Yukon	150 ppm TWA ; 710 mg/m3 TWA 200 ppm STEL ; 950 mg/m3 STEL
Isobutyl acetate	110-19-0
ACGIH:	50 ppm TWA; 150 ppm STEL
NIOSH:	150 ppm TWA ; 700 mg/m3 TWA; 1300 ppm IDLH (10% LEL)
OSHA (US):	150 ppm TWA ; 700 mg/m3 TWA
Alberta, New Brunswick,	150 ppm TWA ; 713 mg/m3 TWA
British Columbia, Ontario	150 ppm TWA
Manitoba	50 ppm TWA
Northwest Territories, Nunavut, Saskatchewan	150 ppm TWA; 188 ppm STEL
Nova Scotia, Prince Edward Island	50 ppm TWA; 150 ppm STEL
Quebec	150 ppm TWAEV ; 713 mg/m3 TWAEV
Yukon	150 ppm TWA ; 700 mg/m3 TWA; 187 ppm STEL ; 875 mg/m3 STEL
tert-Butyl alcohol	75-65-0

Safety Data Sheet

Material Name: SAFETY-KLEEN HEAVY DUTY LACQUER THINNER 6782

SDS ID: 82343

ACGIH:	100 ppm TWA
NIOSH:	100 ppm TWA ; 300 mg/m3 TWA; 150 ppm STEL ; 450 mg/m3 STEL; 1600 ppm IDLH
OSHA (US):	100 ppm TWA ; 300 mg/m3 TWA
Alberta, New Brunswick	100 ppm TWA ; 303 mg/m3 TWA
British Columbia, Manitoba, Nova Scotia, Ontario, Prince Edward Island	100 ppm TWA
Northwest Territories, Nunavut, Saskatchewan	100 ppm TWA; 125 ppm STEL
Quebec	100 ppm TWAEV ; 303 mg/m3 TWAEV
Yukon	100 ppm TWA ; 300 mg/m3 TWA; 150 ppm STEL ; 450 mg/m3 STEL
1-Butanol	71-36-3
ACGIH:	20 ppm TWA
NIOSH:	50 ppm Ceiling ; 150 mg/m3 Ceiling; potential for dermal absorption; 1400 ppm IDLH (10% LEL)
OSHA (US):	100 ppm TWA ; 300 mg/m3 TWA
Alberta	20 ppm TWA ; 60 mg/m3 TWA
British Columbia	15 ppm TWA; 30 ppm Ceiling
Manitoba	20 ppm TWA; Skin - potential for cutaneous absorption
New Brunswick	50 ppm Ceiling ; 152 mg/m3 Ceiling; Skin - potential for cutaneous absorption
Northwest Territories, Nunavut, Saskatchewan	20 ppm TWA; 30 ppm STEL
Nova Scotia, Ontario, Prince Edward Island	20 ppm TWA
Quebec	50 ppm Ceiling ; 152 mg/m3 Ceiling; Skin designation
Yukon	Skin notation
Tetrachloroethylene	127-18-4
ACGIH:	25 ppm TWA; 100 ppm STEL
NIOSH:	150 ppm IDLH
OSHA (US):	100 ppm TWA; 200 ppm Ceiling
Alberta	25 ppm TWA ; 170 mg/m3 TWA; 100 ppm STEL ; 678 mg/m3 STEL

Safety Data Sheet

Material Name: SAFETY-KLEEN HEAVY DUTY LACQUER THINNER 6782

SDS ID: 82343

British Columbia, Northwest Territories, Nova Scotia, Nunavut, Ontario, Prince Edward Island, Saskatchewan	25 ppm TWA; 100 ppm STEL
Manitoba	25 ppm TWA
New Brunswick	25 ppm TWA ; 170 mg/m3 TWA;100 ppm STEL ; 685 mg/m3 STEL
Quebec	25 ppm TWAEV ; 170 mg/m3 TWAEV; 100 ppm STEV ; 685 mg/m3 STEV
Yukon	100 ppm TWA ; 670 mg/m3 TWA; 150 ppm STEL ; 1000 mg/m3 STEL Skin notation
Methylene chloride	75-09-2
ACGIH:	50 ppm TWA
NIOSH:	2300 ppm IDLH
OSHA (US):	25 ppm TWA; 125 ppm STEL (See 29 CFR 1910.1052) 15 min ; 12.5 ppm Action Level (See 29 CFR 1910.1052); 25 ppm TWA (See 29 CFR 1910.1052); 125 ppm STEL (see 29 CFR 1910.1052)
Alberta, New Brunswick	50 ppm TWA ; 174 mg/m3 TWA
British Colombia	25 ppm TWA
Manitoba, Nova Scotia, Ontario, Prince Edward Island	50 ppm TWA
Northwest Territories, Nunavut, Saskatchewan	50 ppm TWA; 75 ppm STEL (regulated under Dichloromethane); 63 ppm STEL
Quebec	50 ppm TWAEV ; 174 mg/m3 TWAEV
Yukon	200 ppm TWA ; 700 mg/m3 TWA ; 720 mg/m3 TWA (regulated under Dichloromethane); 250 ppm STEL ; 870 mg/m3 STEL ; 200 ppm STEL (regulated under Dichloromethane); 720 mg/m3 STEL (regulated under Dichloromethane)
1,1,1-Trichloroethane	71-55-6
ACGIH:	350 ppm TWA; 450 ppm STEL
NIOSH:	350 ppm Ceiling 15 min ; 1900 mg/m3 Ceiling 15 min 700 ppm IDLH
OSHA (US):	350 ppm TWA ; 1900 mg/m3 TWA
Alberta, New Brunswick	350 ppm TWA ; 1910 mg/m3 TWA; 450 ppm STEL ; 2460 mg/m3 STEL
British Columbia, Northwest Territories, Nova Scotia, Nunavut, Ontario, Prince Edward Island, Saskatchewan	350 ppm TWA; 450 ppm STEL
Manitoba	350 ppm TWA

Safety Data Sheet

Material Name: SAFETY-KLEEN HEAVY DUTY LACQUER THINNER 6782

SDS ID: 82343

Quebec	350 ppm TWAEV ; 1910 mg/m ³ TWAEV; 450 ppm STEV ; 2460 mg/m ³ STEV
Yukon	350 ppm TWA ; 1900 mg/m ³ TWA; 440 ppm STEL ; 2400 mg/m ³ STEL

ACGIH - Threshold Limit Values - Biological Exposure Indices (BEI)

Toluene (108-88-3)

0.02 mg/L Medium: blood Time: prior to last shift of workweek Parameter: Toluene ; 0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene ; 0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background)

2-Pentanone, 4-methyl- (108-10-1)

1 mg/L Medium: urine Time: end of shift Parameter: MIBK

Methyl ethyl ketone (78-93-3)

2 mg/L Medium: urine Time: end of shift Parameter: MEK (nonspecific)

Acetone (67-64-1)

25 mg/L Medium: urine Time: end of shift Parameter: Acetone (nonspecific)

Tetrachloroethylene (127-18-4)

3 ppm Medium: end-exhaled air Time: prior to shift Parameter: Tetrachloroethylene ; 0.5 mg/L Medium: blood Time: prior to shift Parameter: Tetrachloroethylene

Methylene chloride (75-09-2)

0.3 mg/L Medium: urine Time: end of shift Parameter: Dichloromethane (semi-quantitative)

1,1,1-Trichloroethane (71-55-6)

40 ppm Medium: end-exhaled air Time: prior to last shift of workweek Parameter: Methyl chloroform ; 10 mg/L Medium: urine Time: end of workweek Parameter: Trichloroacetic acid (nonspecific, semi-quantitative) ; 30 mg/L Medium: urine Time: end of shift at end of workweek Parameter: Total trichloroethanol (nonspecific, semi-quantitative) ; 1 mg/L Medium: blood Time: end of shift at end of workweek Parameter: Total trichloroethanol (nonspecific)

Engineering Controls

Provide general ventilation needed to maintain concentration of vapor or mist below applicable exposure limits. Where adequate general ventilation is unavailable, use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below applicable exposure limits. Use explosion-proof equipment. Ensure compliance with applicable exposure limits.

Individual Protection Measures, such as Personal Protective Equipment

Eye/face protection

Wear splash resistant safety goggles with a faceshield. Additional protection like goggles, face shields, or respirators may be needed dependent upon anticipated use and concentrations of mists or vapors. Provide an emergency eye wash fountain and quick drench shower in the immediate work area. Contact lens use is not recommended.

Skin Protection

To avoid prolonged or repeated contact where spills and splashes are likely, wear appropriate chemical-resistant faceshield, boots, apron, whole body suits, or other protective clothing.

Respiratory Protection

A respiratory protection program which meets USA's OSHA General Industry Standard 29 CFR 1910.134 or Canada's CSA Standard Z94.4-M1982 requirements must be followed whenever workplace conditions warrant a respirator's use. Consult a qualified Industrial Hygienist or Safety Professional for respirator selection guidance.

Glove Recommendations

Where skin contact is likely, wear chemical impervious protective gloves; use of natural rubber (latex), polyvinyl chloride (PVC), neoprene or equivalent gloves is not recommended.

Protective Materials

Personal protective equipment should be selected based upon the conditions under which this material is used. A hazard assessment of the work area for PPE requirements should be conducted by a qualified

Safety Data Sheet

Material Name: SAFETY-KLEEN HEAVY DUTY LACQUER THINNER 6782

SDS ID: 82343

professional pursuant to regulatory requirements. The following PPE should be considered the minimum required: Safety glasses, gloves, lab coat or apron.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Clear liquid.	Physical State	Liquid
Odor	Solvent odor.	Color	Colorless.
Odor Threshold	Not available	pH	Not available
Melting Point	-129 - -22 °C (-200 - -8 °F)	Boiling Point	56 - 172 °C (133 - 342 °F)
Boiling Point Range	Not available	Freezing point	Not available
Evaporation Rate	3.7 (Similar product Butyl acetate = 1)	Flammability (solid, gas)	Flammable.
Autoignition Temperature	427 °C (800 °F)	Flash Point	<21 °C [Closed Cup.] (70 °F)
Lower Explosive Limit	1 vol% (Approximate)	Decomposition temperature	Not available
Upper Explosive Limit	13 vol% (Approximate)	Vapor Pressure	86 mm Hg @ 68 °F (20 °C.)
Vapor Density (air=1)	2.2 - 3.9 (Approximate Air = 1)	Specific Gravity (water=1)	0.83 (Approximate Water = 1)
Water Solubility	(Slight)	Partition coefficient: n-octanol/water	Not available
Viscosity	Not available	Solubility (Other)	Not available
Density	6.9 lb/gal (US Approximate)	Physical Form	Liquid.
Volatility	80 - 100 wt% (as per 40 CFR part 51.100(s))	Molecular Weight	Not available
OSHA Flammability Class	Flammable		
Volatile Organic Compounds (As regulated)	Up to 100 WT %; 6.9 LB/US gal; 830 g/l As per 40 CFR Part 51.100(s) Photochemically reactive (up to 100% by volume) VOC VP = 86 mm Hg @ 20°C (approx.) Consult your state or local air district regulations for location specific information.		

Other Information

No additional information is available.

Section 10 - STABILITY AND REACTIVITY

Reactivity

No reactivity hazard is expected.

Chemical Stability

Stable under normal temperatures and pressures.

Safety Data Sheet

Material Name: SAFETY-KLEEN HEAVY DUTY LACQUER THINNER 6782

SDS ID: 82343

Possibility of Hazardous Reactions

Will not polymerize under normal temperature and pressure conditions.

Conditions to Avoid

Avoid heat, flames, sparks and other sources of ignition Avoid contact with incompatible materials.

Incompatible Materials

Acids, alkalis, oxidizing agents, reducing agents, reactive halogens, or reactive metals.

Hazardous decomposition products

Not applicable under normal conditions of use and storage. See also SECTION 5: HAZARDOUS COMBUSTION PRODUCTS.

Section 11 - TOXICOLOGICAL INFORMATION

Information on Likely Routes of Exposure

Inhalation

Fatal if inhaled. May cause irritation, nausea, central nervous system effects. May cause drowsiness or dizziness. May cause respiratory irritation.

Skin Contact

Harmful in contact with skin. Causes skin irritation.

Eye Contact

Causes serious eye damage.

Ingestion

May be fatal if swallowed and enters airways. Aspiration Hazard. Harmful if swallowed. May cause, throat irritation, nausea, vomiting, diarrhea.

Acute and Chronic Toxicity

Component Analysis - LD50/LC50

The components of this material have been reviewed in various sources and the following selected endpoints are published:

Toluene (108-88-3)

Oral LD50 Rat 2600 mg/kg; Dermal LD50 Rabbit 12000 mg/kg; Inhalation LC50 Rat 12.5 mg/L 4 h

Distillates, petroleum, solvent-refined light paraffinic (64741-89-5)

Oral LD50 Rat >15 g/kg; Dermal LD50 Rabbit >5 g/kg; Inhalation LC50 Rat 2.18 mg/L 4 h

Naphtha (8030-30-6)

Oral LD50 Rat >5 g/kg

2-Pentanone, 4-methyl- (108-10-1)

Oral LD50 Rat 2080 mg/kg; Dermal LD50 Rabbit 3000 mg/kg; Inhalation LC50 Rat 2000-4000 ppm L 4 h

Methyl n-amyl ketone (110-43-0)

Oral LD50 Rat 1600 mg/kg; Dermal LD50 Rabbit 12.6 mL/kg; Inhalation LC50 Rat 2000 - 4000 ppm 6 h

Methyl ethyl ketone (78-93-3)

Oral LD50 Rat 2483 mg/kg; Dermal LD50 Rabbit 5000 mg/kg; Inhalation LC50 Rat 11700 ppm 4 h

Methyl propyl ketone (107-87-9)

Oral LD50 Rat 1600 mg/kg; Dermal LD50 Rabbit 6480 mg/kg; Inhalation LC50 Rat 2000 - 4000 ppm 4 h

Acetone (67-64-1)

Oral LD50 Rat 5800 mg/kg; Dermal LD50 Rabbit >15700 mg/kg; Inhalation LC50 Rat 50100 mg/m³ 8 h

Ethyl 3-ethoxypropanoate (763-69-9)

Oral LD50 Rat 5 g/kg; Dermal LD50 Rabbit >9500 mg/kg; Inhalation LC50 Rat >5.96 mg/L 6 h (no deaths occurred)

Ethyl acetate (141-78-6)

Oral LD50 Rat 5620 mg/kg; Dermal LD50 Rabbit >18000 mg/kg; Inhalation LC50 Mouse 1500 ppm 4 h

Propylene glycol monomethyl ether acetate (108-65-6)

Oral LD50 Rat 8532 mg/kg; Dermal LD50 Rabbit >5 g/kg

Isopropyl acetate (108-21-4)

Oral LD50 Rat 3000 mg/kg; Dermal LD50 Rabbit >17436 mg/kg; Inhalation LC50 Rat 50600 mg/m³ 8 h

n-Butyl acetate (123-86-4)

Oral LD50 Rat 10768 mg/kg; Dermal LD50 Rabbit >17600 mg/kg; Inhalation LC50 Rat 390 ppm 4 h

Isobutyl acetate (110-19-0)

Safety Data Sheet

Material Name: SAFETY-KLEEN HEAVY DUTY LACQUER THINNER 6782

SDS ID: 82343

Oral LD50 Rat 15400 mg/kg; Dermal LD50 Rabbit >17400 mg/kg

tert-Butyl alcohol (75-65-0)

Oral LD50 Rat 2200 mg/kg; Dermal LD50 Rabbit >2 g/kg (no deaths occurred); Inhalation LC50 Rat >10000 ppm 4 h

1-Butanol (71-36-3)

Oral LD50 Rat 700 mg/kg; Dermal LD50 Rabbit 3402 mg/kg; Inhalation LC50 Rat >8000 ppm 4 h

Tetrachloroethylene (127-18-4)

Oral LD50 Rat 2629 mg/kg; Dermal LD50 Mouse 2800 mg/kg; Inhalation LC50 Rat 27.8 mg/L 4 h

Methylene chloride (75-09-2)

Oral LD50 Rat 1600 mg/kg; Inhalation LC50 Rat 53 mg/L 6 h

1,1,1-Trichloroethane (71-55-6)

Oral LD50 Rat 9600 mg/kg; Dermal LD50 Rabbit >15800 mg/kg; Inhalation LC50 Rat 18000 ppm 4 h

Product Toxicity Data

Acute Toxicity Estimate

Dermal	1555.2924 mg/kg
Inhalation - Vapor	1.2614 mg/L
Oral	555.5845 mg/kg

Immediate Effects

Fatal if inhaled, Harmful in contact with skin. harmful if swallowed, eye burns, skin irritation, respiratory tract irritation, aspiration hazard, central nervous system damage, central nervous system depression, respiratory system damage, liver damage, kidney damage, lung damage (from aspiration).

Delayed Effects

Mutagenic effects, cancer, reproductive effects, central nervous system damage, nervous system damage, kidney damage, liver damage, respiratory system damage, blood damage, lung damage.

Irritation/Corrosivity Data

Eye burns, skin irritation, respiratory tract irritation.

Respiratory Sensitization

No information available for the product.

Dermal Sensitization

No information available for the product.

Component Carcinogenicity

Toluene	108-88-3
ACGIH:	A4 - Not Classifiable as a Human Carcinogen
IARC:	Monograph 71 [1999]; Monograph 47 [1989] (Group 3 (not classifiable))
2-Pentanone, 4-methyl-	108-10-1
ACGIH:	A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans
IARC:	Monograph 101 [2013] (Group 2B (possibly carcinogenic to humans))
OSHA:	Present
Acetone	67-64-1
ACGIH:	A4 - Not Classifiable as a Human Carcinogen
tert-Butyl alcohol	75-65-0

Safety Data Sheet

Material Name: SAFETY-KLEEN HEAVY DUTY LACQUER THINNER 6782

SDS ID: 82343

ACGIH:	A4 - Not Classifiable as a Human Carcinogen
Tetrachloroethylene	127-18-4
ACGIH:	A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans
IARC:	Monograph 106 [2014] ; Monograph 63 [1995] ; Supplement 7 [1987] (Group 2A (probably carcinogenic to humans))
NTP:	Reasonably Anticipated To Be A Human Carcinogen
DFG:	Category 3B (could be carcinogenic for man)
OSHA:	Present
NIOSH:	potential occupational carcinogen
Methylene chloride	75-09-2
ACGIH:	A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans
IARC:	Monograph 110 [in preparation] ; Monograph 71 [1999] (Group 2A (probably carcinogenic to humans))
NTP:	Reasonably Anticipated To Be A Human Carcinogen
DFG:	Category 5 (low carcinogenic potency)
OSHA:	Present
OSHA:	see 29 CFR 1910.1052
NIOSH:	potential occupational carcinogen
1,1,1-Trichloroethane	71-55-6
ACGIH:	A4 - Not Classifiable as a Human Carcinogen
IARC:	Monograph 71 [1999] ; Supplement 7 [1987] ; Monograph 20 [1979] (Group 3 (not classifiable))

May cause cancer.

Germ Cell Mutagenicity

May cause genetic defects.

Tumorigenic Data

No data available

Reproductive Toxicity

Available data characterizes this substance as a reproductive hazard.

Specific Target Organ Toxicity - Single Exposure

Central nervous system, respiratory system.

Specific Target Organ Toxicity - Repeated Exposure

Nervous system, kidneys, liver, blood,

Aspiration hazard

This material is an aspiration hazard.

Safety Data Sheet

Material Name: SAFETY-KLEEN HEAVY DUTY LACQUER THINNER 6782

SDS ID: 82343

Medical Conditions Aggravated by Exposure

Blood disorders, central nervous system disorders, eye disorders, hearing or inner ear disorders, kidney disorders, liver disorders, nervous system disorders, respiratory disorders, skin disorders, heart disorders, systemic disorders.

Section 12 - ECOLOGICAL INFORMATION
--

Ecotoxicity

Harmful to aquatic life with long lasting effects.

Component Analysis - Aquatic Toxicity

Toluene	108-88-3
Fish:	LC50 96 h Pimephales promelas 15.22 - 19.05 mg/L [flow-through] (1 day old); LC50 96 h Pimephales promelas 12.6 mg/L [static]; LC50 96 h Oncorhynchus mykiss 5.89 - 7.81 mg/L [flow-through]; LC50 96 h Oncorhynchus mykiss 14.1 - 17.16 mg/L [static]; LC50 96 h Oncorhynchus mykiss 5.8 mg/L [semi-static]; LC50 96 h Lepomis macrochirus 11 - 15 mg/L [static]; LC50 96 h Oryzias latipes 54 mg/L [static]; LC50 96 h Poecilia reticulata 28.2 mg/L [semi-static]; LC50 96 h Poecilia reticulata 50.87 - 70.34 mg/L [static]
Algae:	EC50 96 h Pseudokirchneriella subcapitata >433 mg/L IUCLID ; EC50 72 h Pseudokirchneriella subcapitata 12.5 mg/L [static] EPA
Invertebrate:	EC50 48 h Daphnia magna 5.46 - 9.83 mg/L [Static] EPA ; EC50 48 h Daphnia magna 11.5 mg/L IUCLID
Distillates, petroleum, solvent-refined light paraffinic	64741-89-5
Fish:	LC50 96 h Oncorhynchus mykiss >5000 mg/L
Invertebrate:	EC50 48 h Daphnia magna >1000 mg/L IUCLID
Naphtha	8030-30-6
Fish:	LC50 96 h Lepomis macrochirus 9.2 mg/L [static]
Algae:	EC50 72 h Pseudokirchneriella subcapitata 4700 mg/L IUCLID
2-Pentanone, 4-methyl-	108-10-1
Fish:	LC50 96 h Pimephales promelas 496 - 514 mg/L [flow-through]
Algae:	EC50 96 h Pseudokirchneriella subcapitata 400 mg/L IUCLID
Invertebrate:	EC50 48 h Daphnia magna 170 mg/L IUCLID
Methyl n-amyl ketone	110-43-0
Fish:	LC50 96 h Pimephales promelas 126 - 137 mg/L [flow-through]
Methyl ethyl ketone	78-93-3
Fish:	LC50 96 h Pimephales promelas 3130 - 3320 mg/L [flow-through]

Safety Data Sheet

Material Name: SAFETY-KLEEN HEAVY DUTY LACQUER THINNER 6782

SDS ID: 82343

Invertebrate:	EC50 48 h Daphnia magna >520 mg/L IUCLID ; EC50 48 h Daphnia magna 5091 mg/L IUCLID ; EC50 48 h Daphnia magna 4025 - 6440 mg/L [Static] EPA
Methyl propyl ketone	107-87-9
Fish:	LC50 96 h Pimephales promelas 1190 - 1290 mg/L [flow-through]
Acetone	67-64-1
Fish:	LC50 96 h Oncorhynchus mykiss 4.74 - 6.33 mL/L; LC50 96 h Pimephales promelas 6210 - 8120 mg/L [static] ; LC50 96 h Lepomis macrochirus 8300 mg/L
Invertebrate:	EC50 48 h Daphnia magna 10294 - 17704 mg/L [Static] EPA ; EC50 48 h Daphnia magna 12600 - 12700 mg/L IUCLID
Ethyl 3-ethoxypropanoate	763-69-9
Fish:	LC50 96 h Pimephales promelas 62 mg/L [static]
Invertebrate:	EC50 48 h Daphnia magna 970 mg/L IUCLID
Ethyl acetate	141-78-6
Fish:	LC50 96 h Pimephales promelas 220 - 250 mg/L [flow-through] ; LC50 96 h Oncorhynchus mykiss 484 mg/L [flow-through] ; LC50 96 h Oncorhynchus mykiss 352 - 500 mg/L [semi-static]
Invertebrate:	EC50 48 h Daphnia magna 560 mg/L [Static] EPA
Propylene glycol monomethyl ether acetate	108-65-6
Fish:	LC50 96 h Pimephales promelas 161 mg/L [static]
Invertebrate:	EC50 48 h Daphnia magna >500 mg/L IUCLID
n-Butyl acetate	123-86-4
Fish:	LC50 96 h Lepomis macrochirus 100 mg/L [static] ; LC50 96 h Pimephales promelas 17 - 19 mg/L [flow-through]
Algae:	EC50 72 h Desmodesmus subspicatus 674.7 mg/L IUCLID
tert-Butyl alcohol	75-65-0
Fish:	LC50 96 h Pimephales promelas 6130 - 6700 mg/L [flow-through]
Algae:	EC50 72 h Desmodesmus subspicatus >1000 mg/L IUCLID
Invertebrate:	EC50 48 h Daphnia magna 933 mg/L IUCLID ; EC50 48 h Daphnia magna 4607 - 6577 mg/L [Static] EPA
1-Butanol	71-36-3

Safety Data Sheet

Material Name: SAFETY-KLEEN HEAVY DUTY LACQUER THINNER 6782

SDS ID: 82343

Fish:	LC50 96 h Pimephales promelas 1730 - 1910 mg/L [static]; LC50 96 h Pimephales promelas 1740 mg/L [flow-through]; LC50 96 h Lepomis macrochirus 100000 - 500000 µg/L [static]; LC50 96 h Pimephales promelas 1910000 µg/L [static]
Algae:	EC50 96 h Desmodesmus subspicatus >500 mg/L IUCLID ; EC50 72 h Desmodesmus subspicatus >500 mg/L IUCLID
Invertebrate:	EC50 48 h Daphnia magna 1983 mg/L IUCLID ; EC50 48 h Daphnia magna 1897 - 2072 mg/L [Static] EPA
Tetrachloroethylene	127-18-4
Fish:	LC50 96 h Pimephales promelas 12.4 - 14.4 mg/L [flow-through]; LC50 96 h Pimephales promelas 8.6 - 13.5 mg/L [static]; LC50 96 h Lepomis macrochirus 11 - 15 mg/L [static]; LC50 96 h Oncorhynchus mykiss 4.73 - 5.27 mg/L [flow-through]
Algae:	EC50 96 h Pseudokirchneriella subcapitata >500 mg/L EPA
Invertebrate:	EC50 48 h Daphnia magna 6.1 - 9 mg/L [Static] EPA
Methylene chloride	75-09-2
Fish:	LC50 96 h Pimephales promelas 140.8 - 277.8 mg/L [flow-through]; LC50 96 h Pimephales promelas 262 - 855 mg/L [static]; LC50 96 h Lepomis macrochirus 193 mg/L [static]; LC50 96 h Lepomis macrochirus 193 mg/L [flow-through]
Algae:	EC50 96 h Pseudokirchneriella subcapitata >500 mg/L EPA ; EC50 72 h Pseudokirchneriella subcapitata >500 mg/L EPA
Invertebrate:	EC50 48 h Daphnia magna 1532 - 1847 mg/L [Static] EPA ; EC50 48 h Daphnia magna 190 mg/L IUCLID
1,1,1-Trichloroethane	71-55-6
Fish:	LC50 96 h Pimephales promelas 35.2 - 50.7 mg/L [flow-through]; LC50 96 h Lepomis macrochirus 57 - 90 mg/L [static] (juvenile); LC50 96 h Cyprinus carpio 56 mg/L [flow-through]; LC50 96 h Poecilia reticulata 52.9 mg/L [flow-through]; LC50 96 h Poecilia reticulata 69.7 mg/L [static]; LC50 96 h Pimephales promelas 91 - 126 mg/L [static]; LC50 96 h Oncorhynchus mykiss 46 - 59 mg/L [static]
Algae:	EC50 96 h Pseudokirchneriella subcapitata >500 mg/L EPA
Invertebrate:	LC50 48 h Daphnia magna >530 mg/L IUCLID ; EC50 48 h Daphnia magna 2384 mg/L IUCLID ; EC50 48 h Daphnia magna 9.7 - 12.8 mg/L [Static] EPA

Invertebrate Toxicity

No additional information is available.

Persistence and Degradability

No information available for the product.

Bioaccumulative Potential

No information available for the product.

Mobility

No information available for the product.

Other Toxicity

No additional information is available.

Safety Data Sheet

Material Name: SAFETY-KLEEN HEAVY DUTY LACQUER THINNER 6782

SDS ID: 82343

Section 13 - DISPOSAL CONSIDERATIONS

Disposal Methods

Dispose of in accordance with all applicable federal, state and local regulations. Regulations may also apply to empty containers. The responsibility for proper waste disposal lies with the owner of the waste. Contact Safety-Kleen regarding proper recycling or disposal. D001, D018, D035, D039. Based on available data, this information applies to the product as supplied to the user. Processing, use, or contamination by the user may change the waste code applicable to the disposal of this product.

Section 14 - TRANSPORT INFORMATION

US DOT Information:

Shipping Name: PAINT RELATED MATERIAL

Hazard Class: 3

UN/NA #: UN1263

Packing Group: II

Required Label(s): 3 FLAMMABLE LIQUID

IATA Information:

Shipping Name: PAINT RELATED MATERIAL

Hazard Class: 3

UN#: UN1263

Packing Group: II

Required Label(s): 3 FLAMMABLE LIQUID

TDG Information:

Shipping Name: PAINT RELATED MATERIAL

Hazard Class: 3

UN#: UN1263

Packing Group: II

Required Label(s): 3 FLAMMABLE LIQUID

Additional information

Emergency Response Guide Number 128 Reference .North American Emergency Response Guidebook

Section 15 - REGULATORY INFORMATION

U.S. Federal Regulations

This material contains one or more of the following chemicals required to be identified under SARA Section 302 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), CERCLA (40 CFR 302.4), TSCA 12(b), and/or require an OSHA process safety plan.

Toluene (108-88-3), 1-Butanol (71-36-3), Methylene Chloride (75-09-2), 1,1,1-Trichlorethylene (71-55-6)	
SARA 313:	1 % de minimis concentration
CERCLA:	1000 lb final RQ ; 454 kg final RQ
2-Pentanone, 4-methyl- 108-10-1	
SARA 313:	1 % de minimis concentration

Safety Data Sheet

Material Name: SAFETY-KLEEN HEAVY DUTY LACQUER THINNER 6782

SDS ID: 82343

CERCLA:	5000 lb final RQ ; 2270 kg final RQ
Methyl ethyl ketone (78-93-3), Acetone (67-64-1), Ethyl Acetate (141-78-6), n-Butyl acetate (123-86-4), Isobutyl acetate (110-19-0)	
CERCLA:	5000 lb final RQ ; 2270 kg final RQ
tert-Butyl alcohol (75-65-0),	
SARA 313:	1 % de minimis concentration
Tetrachloroethylene (127-18-4)	
SARA 313:	0.1 % de minimis concentration
CERCLA:	100 lb final RQ ; 45.4 kg final RQ

SARA Section 311/312 (40 CFR 370 Subparts B and C) 2016 reporting categories

Acute Health: Yes **Chronic Health:** Yes **Fire:** Yes **Pressure:** No **Reactivity:** No

SARA Section 311/312 (40 CFR 370 Subparts B and C) 2017 reporting categories

Flammable; Carcinogenicity; Acute toxicity; Reproductive Toxicity; Skin Corrosion/Irritation; Serious Eye Damage/Eye Irritation; Specific Target Organ Toxicity; Aspiration Hazard; Germ Cell Mutagenicity

U.S. State Regulations

The following components appear on one or more of the following state hazardous substances lists:

Component	CA	MA	MN	NJ	PA
Naphtha (8030-30-6), 2-Pentanone, 4-methyl-(108-10-1) Methyl n-amyl ketone (110-43-0), Methyl ethyl ketone (78-93-3), Methyl propyl ketone (107-87-9), Acetone (67-64-1), Ethyl acetate (141-78-6), Isopropyl acetate (108-21-4), n-Butyl acetate (123-86-4) Isobutyl acetate(110-19-0), tert-Butyl alcohol (75-65-0), 1-Butanol (71-36-3),Tetrachloroethylene (127-18-4), Methylene chloride (75-09-2),1,1,1-Trichloroethane (71-55-6)	Yes	Yes	Yes	Yes	Yes
Distillates, petroleum, solvent-refined light paraffinic (64741-89-5)	No	Yes	No	No	No

THIS PRODUCT IS NOT FOR SALE OR USE IN THE STATE OF CALIFORNIA.

Canada Regulations

Canadian WHMIS Ingredient Disclosure List (IDL)

Components of this material have been checked against the Canadian WHMIS Ingredients Disclosure List. The List is composed of chemicals which must be identified on MSDSs if they are included in products which meet WHMIS criteria specified in the Controlled Products Regulations and are present above the threshold limits listed on the IDL

Toluene (108-88-3), 2-Pentanone, 4-methyl- (108-10-1), Methyl n-amyl ketone (110-43-0), Methyl ethyl ketone (78-93-3), Methyl propyl ketone (107-87-9), Acetone (67-64-1), Ethyl acetate (141-78-6), Isopropyl acetate (108-21-4), n-Butyl acetate (123-86-4), Isobutyl acetate (110-19-0), tert-Butyl alcohol (75-65-0), 1-Butanol (71-36-3), Tetrachloroethylene (127-18-4), Methylene chloride (75-09-2), 1,1,1-Trichloroethane (71-55-6)
1 %

Component Analysis - Inventory

Safety Data Sheet

Material Name: SAFETY-KLEEN HEAVY DUTY LACQUER THINNER 6782

SDS ID: 82343

Hydrocarbons, aromatic (63231-51-6) Toluene (108-88-3), Distillates, petroleum, solvent-refined light paraffinic (64741-89-5), Naphtha (8030-30-6), 2-Pentanone, 4-methyl- (108-10-1), Methyl n-amyl ketone (110-43-0), Methyl ethyl ketone (78-93-3), Methyl propyl ketone (107-87-9), Acetone (67-64-1), Alcohols, C1-3 (68475-56-9), Ethyl 3-ethoxypropanoate (763-69-9), Ethyl acetate (141-78-6), Propylene glycol monomethyl ether acetate (108-65-6), Isopropyl acetate (108-21-4), n-Butyl acetate (123-86-4), Isobutyl acetate (110-19-0), tert-Butyl alcohol (75-65-0), 1-Butanol (71-36-3), Tetrachloroethylene (127-18-4), Methylene chloride (75-09-2), 1,1,1-Trichloroethane (71-55-6)

US	CA
No	No

Section 16 - OTHER INFORMATION

NFPA Ratings

Health: 4 Fire: 3 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

Summary of Changes

Revision to Section 11.

Key / Legend

ACGIH - American Conference of Governmental Industrial Hygienists; BOD - Biochemical Oxygen Demand; C - Celsius; CA - Canada; CA/MA/MN/NJ/PA - California/Massachusetts/Minnesota/New Jersey/Pennsylvania*; CAS - Chemical Abstracts Service; CFR - Code of Federal Regulations (US); CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CLP - Classification, Labelling, and Packaging; CPR - Controlled Products Regulations; DOT - Department of Transportation; DSL - Domestic Substances List; EPA - Environmental Protection Agency; F - Fahrenheit; IDL - Ingredient Disclosure List; IDLH - Immediately Dangerous to Life and Health; IMDG - International Maritime Dangerous Goods; LEL - Lower Explosive Limit; LLV - Level Limit Value; LOLI - List Of Lists™ - ChemADVISOR's Regulatory Database; MAK - Maximum Concentration Value in the Workplace; MEL - Maximum Exposure Limits; NDSL - Non-Domestic Substance List (Canada); NFPA - National Fire Protection Agency; NIOSH - National Institute for Occupational Safety and Health; NJTSR - New Jersey Trade Secret Registry; NTP - National Toxicology Program; OSHA - Occupational Safety and Health Administration; PEL - Permissible Exposure Limit; RCRA - Resource Conservation and Recovery Act; SARA - Superfund Amendments and Reauthorization Act; STEL - Short-term Exposure Limit; TDG - Transportation of Dangerous Goods; TLV - Threshold Limit Value; TSCA - Toxic Substances Control Act; TWA - Time Weighted Average; UEL - Upper Explosive Limit; UN/NA - United Nations /North American; US - United States; WHMIS - Workplace Hazardous Materials Information System (Canada).

Other Information

Disclaimer:

User assumes all risks incident to the use of this product. To the best of our knowledge, the information contained herein is accurate. However, Safety-Kleen assumes no liability whatsoever for the accuracy or completeness of the information contained herein. No representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose or of any other nature are made hereunder with respect to the information or the product to which the information refers. The data contained on this sheet apply to the product as supplied to the user.