



## Safety Data Sheet

Material Name: HEAVY DUTY 550 CLEANING SOLVENT

SDS ID: 82509

### Section 1 - PRODUCT AND COMPANY IDENTIFICATION

**Material Name**

HEAVY DUTY 550 CLEANING SOLVENT

**Product Code**

6864, 585821, 585826

**Synonyms**

None

**Product Use**

For cleaning coating equipment (e.g. paint spray guns). If this product is used in combination with other products, refer to the Material Safety Data Sheet for those products.

**Restrictions on Use**

THIS PRODUCT IS NOT FOR SALE OR USE IN THE STATE OF CALIFORNIA

**Manufacturer Information**

**MANUFACTURER**

Safety-Kleen Systems, Inc.  
2600 North Central Expressway  
Suite 200  
Richardson, TX 75080  
www.safety-kleen.com

**SUPPLIER**

Safety-Kleen Canada, Inc.  
25 Regan Road  
Brampton, Ontario, Canada L1A 1B2

Phone: 1-800-669-5740

Emergency Phone #: 1-800-468-1760

**Issue Date**

June 12, 2019

**Supersedes Issue Date**

February 7, 2017

**Original Issue Date**

August 2, 2005

### Section 2 - HAZARDS IDENTIFICATION

**Classification in accordance with Schedule 1 of Canada's Hazardous Products Regulations (HPR) (SOR/2015-17) and paragraph (d) of 29 CFR 1910.1200 in the United States**

- Flammable Liquids - Category 2
- Aspiration Hazard - Category 1
- Acute Toxicity - Inhalation - Vapor - Category 3
- Skin Corrosion/Irritation - Category 2
- Serious Eye Damage/Eye Irritation - Category 2A
- Germ Cell Mutagenicity - Category 1B
- Carcinogenicity - Category 1B
- Reproductive Toxicity - Category 2
- Specific target organ toxicity - Single exposure - Category 3

# Safety Data Sheet

Material Name: HEAVY DUTY 550 CLEANING SOLVENT

SDS ID: 82509

## GHS Label Elements

### Symbol(s)



### Signal Word

Danger

### Hazard Statement(s)

- Highly flammable liquid and vapor.
- May be fatal if swallowed and enters airways.
- Toxic if inhaled.
- Causes skin irritation and serious eye irritation.
- May cause genetic defects and cancer.
- Suspected of damaging fertility or the unborn child.
- May cause respiratory irritation, drowsiness or dizziness.

### Precautionary Statement(s)

#### Prevention

Do not handle until all safety precautions have been read and understood. Keep container tightly closed. Keep away from heat/sparks/open flame/hot surfaces - No smoking. Ground/Bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Take precautionary measures against static discharge. Use only non-sparking tools. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapors/spray. Wear protective gloves/protective clothing/eye protection/face protection. Wash thoroughly after handling.

#### Response

In case of fire: Use appropriate media to extinguish. IF exposed or concerned: Get medical advice/attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician. IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. IF SWALLOWED: Aspiration hazard. Immediately call a POISON CENTER/doctor. Do NOT induce vomiting.

#### Storage

Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up.

#### Disposal

Dispose of in accordance with all applicable federal, state and local regulations.

#### Statement(s) of Unknown Acute Toxicity

0% of the mixture consists of ingredient(s) of unknown acute toxicity.

#### Other Hazards

None known.

# Safety Data Sheet

Material Name: HEAVY DUTY 550 CLEANING SOLVENT

SDS ID: 82509

## Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

CAS	Component	Percent
63231-51-6	Aromatic Hydrocarbons	15-80
67-64-1	Acetone	40-80
*MIXTURE	Ketones	3-35
***MIXTURE	Acetates	0-30
**MIXTURE	Aliphatic hydrocarbons	0-25
68475-56-9	Alcohols, C1-3	0-20
***MIXTURE	Other Alcohols	0-10
763-69-9	Ethyl 3-ethoxypropanoate	0-5
<b>Component Information/Information on Non-Hazardous Components</b>		
*Mixture of 78-93-3, 108-10-1, 110-43-0, 107-87-9		
**Mixture of 64741-89-5, 8030-30-6		
***Mixture of 123-86-4, 110-19-0, 108-21-4, 108-65-6, 141-78-6		
****Mixture of 71-36-3, 75-65-0		

## Section 4 - FIRST AID MEASURES

### Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician.

### Skin

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention.

### Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician.

### Ingestion

IF SWALLOWED: Aspiration hazard. Do NOT induce vomiting. If vomiting occurs, keep head lower than hips to help prevent aspiration. Call a poison control center or doctor immediately for treatment advice.

### Most Important Symptoms/Effects

#### Acute

Toxic if inhaled. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye damage. May cause drowsiness or dizziness and respiratory irritation.

#### Delayed

May cause cancer. May cause genetic defects. Suspected of damaging fertility or the unborn child.

### Indication of any immediate medical attention and special treatment needed

IF exposed: Call a POISON CENTER or doctor/physician. Treat symptomatically and supportively. Call 1-800-468-1760 for additional information.

## Section 5 - FIRE FIGHTING MEASURES

### Extinguishing Media

#### Suitable Extinguishing Media

Media to use includes water spray, carbon dioxide, dry chemical or alcohol-resistant foam.

#### Unsuitable Extinguishing Media

Do not use high-pressure water streams.

### Special Hazards Arising from the Chemical

Product may be sensitive to static discharge, which could result in fire or explosion. Highly flammable liquid and vapor. Vapors may form explosive mixture with air. Vapors are heavier than air and may travel along the

# Safety Data Sheet

Material Name: HEAVY DUTY 550 CLEANING SOLVENT

SDS ID: 82509

ground to some distant source of ignition and flash back. Fire may produce irritating, poisonous and/or corrosive fumes. Runoff may create fire or explosion hazard. Empty product containers may retain product residue and can be dangerous. Containers may rupture or explode.

## **Hazardous Combustion Products**

Decomposition and combustion materials may be toxic. Burning may produce formaldehyde, peracetic acid, carbon monoxide, unidentified organic compounds.

## **Fire Fighting Measures**

Keep storage containers cool with water spray. Move container from fire area if it can be done without risk. Cool containers with water from unmanned hose holder or monitor nozzles until well after fire is out. Stay away from the ends of tanks. For fires in cargo or storage area: Do not scatter spilled material with high-pressure water streams. Apply water from a protected location or from a safe distance. Avoid inhalation of material or combustion by-products. Let the fire burn. Withdraw immediately in case of rising sound from venting safety device or any discoloration of tanks due to fire. For tank, rail car or tank truck, evacuation radius: 800 meters (1/2 mile). Stay upwind and keep out of low areas. Dike for later disposal.

## **Special Protective Equipment and Precautions for Firefighters**

Wear full protective fire fighting gear including self contained breathing apparatus (SCBA) for protection against possible exposure.

## **Section 6 - ACCIDENTAL RELEASE MEASURES**

### **Personal Precautions, Protective Equipment and Emergency Procedures**

Wear personal protective clothing and equipment, see Section 8. Avoid release to the environment.

### **Methods and Materials for Containment and Cleaning Up**

Remove all ignition sources. Do not touch or walk through spilled product. Stop leak if you can do it without risk. Wear protective equipment and provide engineering controls as specified in SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Ventilate area and avoid breathing vapor or mist. A vapor suppressing foam may be used to reduce vapors. Contain spill away from surface water and sewers. Contain spill as a liquid for possible recovery, or sorb with compatible sorbent material and shovel with a clean, sparkproof tool into a sealable container for disposal. Additionally, for large spills: Water spray may reduce vapor, but may not prevent ignition in closed spaces. Dike far ahead of liquid spill for collection and later disposal. There may be specific regulatory reporting requirements associated with spills, leaks, or releases of this product. Also see SECTION 15: REGULATORY INFORMATION.

## **Section 7 - HANDLING AND STORAGE**

### **Precautions for Safe Handling**

Keep away from heat, sparks, or flame. Where flammable mixtures may be present, equipment safe for such locations should be used. Use clean, sparkproof tools and explosion-proof equipment. When transferring product, metal containers, including trucks and tank cars, should be grounded and bonded. Do not breathe vapor or mist. Use in a well ventilated area. Avoid contact with eyes, skin, clothing, shoes. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.

### **Conditions for Safe Storage, Including any Incompatibilities**

Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up. Keep containers away from heat, flame, sparks, static electricity, or other sources of ignition. Do not pressurize, cut, weld, braze, solder, drill, or grind containers. Empty product containers may retain product residue and can be dangerous. See SECTION 14: TRANSPORTATION INFORMATION for Packing Group information.

### **Incompatible Materials**

Avoid strong oxidizing materials, combustible materials, strong acids, alkalis, reducing agents, reactive halogens, reactive metals.

## Safety Data Sheet

**Material Name: HEAVY DUTY 550 CLEANING SOLVENT**

**SDS ID: 82509**

<b>Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION</b>
--

**Component Exposure Limits**

<b>Acetone</b>	<b>67-64-1</b>
ACGIH:	250 ppm TWA; 500 ppm STEL
NIOSH:	250 ppm TWA ; 590 mg/m3 TWA; 2500 ppm IDLH (10% LEL )
OSHA (US):	1000 ppm TWA ; 2400 mg/m3 TWA
Alberta	500 ppm TWA ; 1200 mg/m3 TWA; 750 ppm STEL ; 1800 mg/m3 STEL
British Columbia; Nova Scotia; Prince Edward Island	250 ppm TWA; 500 ppm STEL
Manitoba	250 ppm TWA
New Brunswick	500 ppm TWA ; 1188 mg/m3 TWA 750 ppm STEL ; 1782 mg/m3 STEL
Northwest Territories, Nunavut; Ontario; Saskatchewan	500 ppm TWA; 750 ppm STEL
Quebec	500 ppm TWAEV ; 1190 mg/m3 TWAEV 1000 ppm STEV ; 2380 mg/m3 STEV
Yukon	1000 ppm TWA ; 2400 mg/m3 TWA 1250 ppm STEL ; 3000 mg/m3 STEL
<b>Methyl ethyl ketone</b>	<b>78-93-3</b>
ACGIH:	200 ppm TWA; 300 ppm STEL
NIOSH:	200 ppm TWA ; 590 mg/m3 TWA; 300 ppm STEL ; 885 mg/m3 STEL; 3000 ppm IDLH
OSHA (US):	200 ppm TWA ; 590 mg/m3 TWA
Alberta; New Brunswick	200 ppm TWA ; 590 mg/m3 TWA 300 ppm STEL ; 885 mg/m3 STEL
British Columbia	50 ppm TWA; 100 ppm STEL
Manitoba	200 ppm TWA
Northwest Territories ; Nova Scotia; Nunavut; Ontario; Prince Edward Island; Saskatchewan	200 ppm TWA; 300 ppm STEL
Quebec	50 ppm TWAEV ; 150 mg/m3 TWAEV 100 ppm STEV ; 300 mg/m3 STEV
Yukon	200 ppm TWA ; 590 mg/m3 TWA 250 ppm STEL ; 740 mg/m3 STEL

## Safety Data Sheet

**Material Name: HEAVY DUTY 550 CLEANING SOLVENT**

**SDS ID: 82509**

<b>Naphtha</b>	<b>8030-30-6</b>
NIOSH:	100 ppm TWA ; 400 mg/m3 TWA 1000 ppm IDLH (10% LEL )
OSHA (US):	100 ppm TWA ; 400 mg/m3 TWA
Alberta; New Brunswick;	400 ppm TWA ; 1590 mg/m3 TWA
British Columbia	(reciprocal calculation method - see OHS Guideline G5.48-12 )
Northwest Territories; Nunavut; Saskatchewan	400 ppm TWA; 500 ppm STEL
Quebec	400 ppm TWAEV ; 1590 mg/m3 TWAEV
Yukon	400 ppm TWA (Rubber solvent and Coal tar ) ; 1800 mg/m3 TWA (Rubber solvent and Coal tar ) 500 ppm STEL (Rubber solvent and Coal tar ) ; 2250 mg/m3 STEL (Rubber solvent and Coal tar )
<b>n-Butyl acetate</b>	<b>123-86-4</b>
ACGIH:	50 ppm TWA; 150 ppm STEL
NIOSH:	150 ppm TWA ; 710 mg/m3 TWA; 200 ppm STEL ; 950 mg/m3 STEL; 1700 ppm IDLH (10% LEL )
OSHA (US):	150 ppm TWA ; 710 mg/m3 TWA
Alberta; New Brunswick	150 ppm TWA ; 713 mg/m3 TWA 200 ppm STEL ; 950 mg/m3 STEL
British Columbia	20 ppm TWA
Manitoba	50 ppm TWA
Northwest Territories; Nunavut; Ontario; Saskatchewan	150 ppm TWA; 200 ppm STEL
Nova Scotia; Prince Edward Island	50 ppm TWA; 150 ppm STEL
Quebec	150 ppm TWAEV ; 713 mg/m3 TWAEV 200 ppm STEV ; 950 mg/m3 STEV
Yukon	150 ppm TWA; 710 mg/m3 TWA; 200 ppm STEL; 950 mg/m3 STEL
<b>Isobutyl acetate</b>	<b>110-19-0</b>
ACGIH:	50 ppm TWA; 150 ppm STEL
NIOSH:	150 ppm TWA ; 700 mg/m3 TWA; 1300 ppm IDLH (10% LEL )
OSHA (US):	150 ppm TWA ; 700 mg/m3 TWA

## Safety Data Sheet

**Material Name: HEAVY DUTY 550 CLEANING SOLVENT**

**SDS ID: 82509**

Alberta; New Brunswick	150 ppm TWA ; 713 mg/m3 TWA
British Columbia; Ontario	150 ppm TWA
Manitoba	50 ppm TWA
Northwest Territories; Nunavut; Saskatchewan	150 ppm TWA; 188 ppm STEL
Nova Scotia; Prince Edward Island	50 ppm TWA; 150 ppm STEL
Quebec	150 ppm TWAEV ; 713 mg/m3 TWAEV
Yukon	150 ppm TWA ; 700 mg/m3 TWA; 187 ppm STEL ; 875 mg/m3 STEL
<b>2-Pentanone, 4-methyl-</b>	<b>108-10-1</b>
ACGIH:	20 ppm TWA; 75 ppm STEL
NIOSH:	50 ppm TWA ; 205 mg/m3 TWA; 75 ppm STEL ; 300 mg/m3 STEL; 500 ppm IDLH
OSHA (US):	100 ppm TWA ; 410 mg/m3 TWA
Alberta; New Brunswick	50 ppm TWA ; 205 mg/m3 TWA; 75 ppm STEL ; 307 mg/m3 STEL
British Columbia; Nova Scotia; Ontario; Prince Edward Island	20 ppm TWA; 75 ppm STEL
Manitoba	20 ppm TWA
Northwest Territories; Nunavut; Saskatchewan	50 ppm TWA; 75 ppm STEL
Quebec	50 ppm TWAEV ; 205 mg/m3 TWAEV 75 ppm STEV ; 307 mg/m3 STEV
Yukon	100 ppm TWA ; 410 mg/m3 TWA; 125 ppm STEL ; 510 mg/m3 STEL; Skin notation
<b>Isopropyl acetate</b>	<b>108-21-4</b>
ACGIH:	100 ppm TWA; 200 ppm STEL
NIOSH:	1800 ppm IDLH
OSHA (US):	250 ppm TWA ; 950 mg/m3 TWA
Alberta	100 ppm TWA ; 416 mg/m3 TWA; 200 ppm STEL ; 832 mg/m3 STEL
British Columbia; Northwest Territories; Nova Scotia; Nunavut; Ontario; Prince Edward Island; Saskatchewan	100 ppm TWA; 200 ppm STEL

## Safety Data Sheet

**Material Name: HEAVY DUTY 550 CLEANING SOLVENT**

**SDS ID: 82509**

Manitoba	100 ppm TWA
New Brunswick	250 ppm TWA ; 1040 mg/m3 TWA 310 ppm STEL ; 1290 mg/m3 STEL
Quebec	250 ppm TWAEV ; 1040 mg/m3 TWAEV 310 ppm STEV ; 1290 mg/m3 STEV
Yukon	250 ppm TWA ; 950 mg/m3 TWA 310 ppm STEL ; 1185 mg/m3 STEL
<b>Propylene glycol monomethyl ether acetate</b>	<b>108-65-6</b>
British Columbia	50 ppm TWA;75 ppm STEL
Ontario	50 ppm TWA ; 270 mg/m3 TWA
<b>Methyl n-amyl ketone</b>	<b>110-43-0</b>
ACGIH:	50 ppm TWA
NIOSH:	100 ppm TWA ; 465 mg/m3 TWA; 800 ppm IDLH
OSHA (US):	100 ppm TWA ; 465 mg/m3 TWA
Alberta; New Brunswick	50 ppm TWA ; 233 mg/m3 TWA
British Columbia, Manitoba; Nova Scotia; Prince Edward Island	50 ppm TWA
Northwest Territories; Nunavut; Saskatchewan	50 ppm TWA ;60 ppm STEL
Ontario	25 ppm TWA ; 115 mg/m3 TWA
Quebec	50 ppm TWAEV ; 233 mg/m3 TWAEV
Yukon	100 ppm TWA ; 465 mg/m3 TWA 150 ppm STEL ; 710 mg/m3 STEL
<b>1-Butanol</b>	<b>71-36-3</b>
ACGIH:	20 ppm TWA
NIOSH:	50 ppm Ceiling ; 150 mg/m3 Ceiling ; Potential for dermal absorption ; 1400 ppm IDLH (10% LEL )
OSHA (US):	100 ppm TWA ; 300 mg/m3 TWA
Alberta	20 ppm TWA ; 60 mg/m3 TWA
British Columbia	15 ppm TWA; 30 ppm Ceiling
Manitoba	20 ppm TWA Skin - potential for cutaneous absorption



## Safety Data Sheet

**Material Name: HEAVY DUTY 550 CLEANING SOLVENT**

**SDS ID: 82509**

New Brunswick	50 ppm Ceiling ; 152 mg/m <sup>3</sup> Ceiling; Skin - potential for cutaneous absorption
Nova Scotia; Ontario; Prince Edward Island	20 ppm TWA
Nunavut; Saskatchewan; Northwest Territories	20 ppm TWA; 30 ppm STEL
Quebec	50 ppm Ceiling ; 152 mg/m <sup>3</sup> Ceiling Skin designation
Yukon	Skin notation
<b>tert-Butyl alcohol</b>	<b>75-65-0</b>
ACGIH:	100 ppm TWA
NIOSH:	100 ppm TWA ; 300 mg/m <sup>3</sup> TWA; 150 ppm STEL ; 450 mg/m <sup>3</sup> STEL; 1600 ppm IDLH
OSHA (US):	100 ppm TWA ; 300 mg/m <sup>3</sup> TWA
Alberta; New Brunswick	100 ppm TWA ; 303 mg/m <sup>3</sup> TWA
British Columbia ; Manitoba, Nova Scotia; Ontario; Prince Edward Island	100 ppm TWA
Northwest Territories; Nunavut; Saskatchewan	100 ppm TWA; 125 ppm STEL
Quebec	100 ppm TWAEV ; 303 mg/m <sup>3</sup> TWAEV
Yukon	100 ppm TWA ; 300 mg/m <sup>3</sup> TWA 150 ppm STEL ; 450 mg/m <sup>3</sup> STEL
<b>Ethyl 3-ethoxypropanoate</b>	<b>763-69-9</b>
Ontario	50 ppm TWA ; 300 mg/m <sup>3</sup> TWA
<b>Ethyl acetate</b>	<b>141-78-6</b>
ACGIH:	400 ppm TWA
NIOSH:	400 ppm TWA ; 1400 mg/m <sup>3</sup> TWA; 2000 ppm IDLH (10% LEL )
OSHA (US):	400 ppm TWA ; 1400 mg/m <sup>3</sup> TWA
Alberta; New Brunswick	400 ppm TWA ; 1440 mg/m <sup>3</sup> TWA
British Columbia	150 ppm TWA
Manitoba; Nova Scotia; Ontario; Prince Edward Island	400 ppm TWA
Northwest Territories; Nunavut; Saskatchewan	400 ppm TWA; 500 ppm STEL
Quebec	400 ppm TWAEV ; 1440 mg/m <sup>3</sup> TWAEV

# Safety Data Sheet

**Material Name: HEAVY DUTY 550 CLEANING SOLVENT**

**SDS ID: 82509**

Yukon	400 ppm TWA ; 1400 mg/m3 TWA 400 ppm STEL ; 1400 mg/m3 STEL
<b>Methyl propyl ketone</b>	<b>107-87-9</b>
ACGIH:	150 ppm STEL
NIOSH:	150 ppm TWA ; 530 mg/m3 TWA; 1500 ppm IDLH
OSHA (US):	200 ppm TWA ; 700 mg/m3 TWA
Alberta; New Brunswick	200 ppm TWA ; 705 mg/m3 TWA 250 ppm STEL ; 881 mg/m3 STEL
British Columbia	150 ppm TWA; 250 ppm STEL
Nova Scotia; Prince Edward Island; Ontario	150 ppm STEL
Quebec	150 ppm TWAEV ; 530 mg/m3 TWAEV
Saskatchewan, Northwest Territories, Nunavut	200 ppm TWA; 250 ppm STEL
Yukon	200 ppm TWA ; 700 mg/m3 TWA 250 ppm STEL ; 875 mg/m3 STEL

**ACGIH - Threshold Limit Values - Biological Exposure Indices (BEI)**

**Acetone (67-64-1)**

25 mg/L Medium: urine Time: end of shift Parameter: Acetone (nonspecific )

**Methyl ethyl ketone (78-93-3)**

2 mg/L Medium: urine Time: end of shift Parameter: MEK (nonspecific )

**2-Pentanone, 4-methyl- (108-10-1)**

1 mg/L Medium: urine Time: end of shift Parameter: MIBK

**ACGIH - Threshold Limit Values - Biological Exposure Indices (BEI)**

**Acetone (67-64-1)**

25 mg/L Medium: urine Time: end of shift Parameter: Acetone (nonspecific )

**Methyl ethyl ketone (78-93-3)**

2 mg/L Medium: urine Time: end of shift Parameter: MEK (nonspecific )

**2-Pentanone, 4-methyl- (108-10-1)**

1 mg/L Medium: urine Time: end of shift Parameter: MIBK

**Engineering Controls**

Provide general ventilation needed to maintain concentration of vapor or mist below applicable exposure limits. Where adequate general ventilation is unavailable, use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below applicable exposure limits. Where explosive mixtures may be present, equipment safe for such locations should be used.

**Individual Protection Measures, such as Personal Protective Equipment**

**Eye/face protection**

Wear safety glasses. Additional protection like goggles, face shields, or respirators may be needed dependent upon anticipated use and concentrations of mists or vapors. Eye wash fountain and emergency showers are recommended. Contact lens use is not recommended.

**Respiratory Protection**

A respiratory protection program which meets USA's OSHA General Industry Standard 29 CFR 1910.134 or Canada's CSA Standard Z94.4-M1982 requirements must be followed whenever workplace conditions warrant a respirator's use. Consult a qualified Industrial Hygienist or Safety Professional for respirator selection guidance.

# Safety Data Sheet

Material Name: HEAVY DUTY 550 CLEANING SOLVENT

SDS ID: 82509

## Glove Recommendations

To avoid prolonged or repeated contact where spills and splashes are likely, wear appropriate chemical-resistant faceshield, boots, apron, whole body suits, or other protective clothing.

## Protective Materials

Personal protective equipment should be selected based upon the conditions under which this material is used. A hazard assessment of the work area for PPE requirements should be conducted by a qualified professional pursuant to regulatory requirements. The following PPE should be considered the minimum required: Safety glasses, Gloves, and Lab coat or apron.

## Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance</b>	Clear, colorless liquid	<b>Physical State</b>	Liquid
<b>Odor</b>	Solvent	<b>Color</b>	Clear, colorless
<b>Odor Threshold</b>	Not available	<b>pH</b>	Not available
<b>Melting Point</b>	Not available	<b>Boiling Point</b>	56.2 °C (133 °F Initial )
<b>Boiling Point Range</b>	Not available	<b>Freezing point</b>	Not available
<b>Evaporation Rate</b>	Not available	<b>Flammability (solid, gas)</b>	Not available
<b>Autoignition Temperature</b>	427 °C (800 °F Approximate )	<b>Flash Point</b>	-18 °C (0 °F Minimum Acetone )
<b>Lower Explosive Limit</b>	1 vol% (Approximate )	<b>Decomposition temperature</b>	Not available
<b>Upper Explosive Limit</b>	13 vol% (Approximate )	<b>Vapor Pressure</b>	108 mmHg @ 68 °F (20 °C Approximate )
<b>Vapor Density (air=1)</b>	>1 (Air = 1 )	<b>Specific Gravity (water=1)</b>	0.82 (Approximate Water = 1 )
<b>Water Solubility</b>	(Slight )	<b>Partition coefficient: n-octanol/water</b>	Not available
<b>Viscosity</b>	Not available	<b>Solubility (Other)</b>	Not available
<b>Density</b>	6.8 lb/gal (US Approximate )	<b>Molecular Weight</b>	Not applicable
<b>Volatile Organic Compounds (As regulated)</b>	Up to 60 WT%; 4 LB/US gallon; 500g/l (maximum) As per 40 CFR Part 51.100(s). Photochemically reactive (up to 60% by volume) VOC VP = 108 mmHg @ 68°F (20°C) (approx.) Consult your state or local air district regulations for location specific information.		

## Other Information

No additional information is available.

## Section 10 - STABILITY AND REACTIVITY

# Safety Data Sheet

Material Name: HEAVY DUTY 550 CLEANING SOLVENT

SDS ID: 82509

## Reactivity

No reactivity hazard is expected.

## Chemical Stability

Stable under normal temperatures and pressures.

## Possibility of Hazardous Reactions

Will not polymerize under normal temperature and pressure conditions.

## Conditions to Avoid

Avoid heat, flames, sparks and other sources of ignition. Avoid contact with incompatible materials.

## Incompatible Materials

Avoid strong oxidizing materials, combustible materials, strong acids, alkalis, reducing agents, reactive halogens, reactive metals.

## Hazardous decomposition products

Burning may produce formaldehyde, acetic acid, carbon monoxide, unidentified organic compounds.

## Section 11 - TOXICOLOGICAL INFORMATION

### Information on Likely Routes of Exposure

#### Inhalation

Toxic if inhaled. May cause irritation, nausea, headache. May cause drowsiness or dizziness.

#### Skin Contact

Causes skin irritation.

#### Eye Contact

Causes serious eye damage.

#### Ingestion

May be fatal if swallowed and enters airways. May cause throat irritation, nausea, vomiting, diarrhea.

### Acute and Chronic Toxicity

#### Component Analysis - LD50/LC50

The components of this material have been reviewed in various sources and the following selected endpoints are published:

##### Acetone (67-64-1)

Oral LD50 Rat 5800 mg/kg; Dermal LD50 Rabbit >15700 mg/kg; Inhalation LC50 Rat 50100 mg/m<sup>3</sup> 8 h

##### Methyl ethyl ketone (78-93-3)

Oral LD50 Rat 2483 mg/kg; Dermal LD50 Rabbit 5000 mg/kg; Inhalation LC50 Rat 11700 ppm 4 h

##### Distillates, petroleum, solvent-refined light paraffinic (64741-89-5)

Oral LD50 Rat >15 g/kg; Dermal LD50 Rabbit >5 g/kg; Inhalation LC50 Rat 2.18 mg/L 4 h

##### Naphtha (8030-30-6)

Oral LD50 Rat >5 g/kg

##### n-Butyl acetate (123-86-4)

Oral LD50 Rat 10768 mg/kg; Dermal LD50 Rabbit >17600 mg/kg; Inhalation LC50 Rat 390 ppm 4 h

##### Isobutyl acetate (110-19-0)

Oral LD50 Rat 15400 mg/kg; Dermal LD50 Rabbit >17400 mg/kg

##### 2-Pentanone, 4-methyl- (108-10-1)

Oral LD50 Rat 2080 mg/kg; Dermal LD50 Rabbit 3000 mg/kg; Inhalation LC50 Rat 2000 – 4000 mg/L 4 h

##### Isopropyl acetate (108-21-4)

Oral LD50 Rat 3000 mg/kg; Dermal LD50 Rabbit >17436 mg/kg; Inhalation LC50 Rat 50600 mg/m<sup>3</sup> 8 h

##### Propylene glycol monomethyl ether acetate (108-65-6)

Oral LD50 Rat 8532 mg/kg; Dermal LD50 Rabbit >5 g/kg

##### Methyl n-amyl ketone (110-43-0)

Oral LD50 Rat 1600 mg/kg; Dermal LD50 Rabbit 12.6 mL/kg; Inhalation LC50 Rat 2000 - 4000 ppm 6 h

##### 1-Butanol (71-36-3)

# Safety Data Sheet

Material Name: HEAVY DUTY 550 CLEANING SOLVENT

SDS ID: 82509

Oral LD50 Rat 700 mg/kg; Dermal LD50 Rabbit 3402 mg/kg; Inhalation LC50 Rat >8000 ppm 4 h

**tert-Butyl alcohol (75-65-0)**

Oral LD50 Rat 2200 mg/kg; Dermal LD50 Rabbit >2 g/kg (no deaths occurred); Inhalation LC50 Rat >10000 ppm 4 h

**Ethyl 3-ethoxypropanoate (763-69-9)**

Oral LD50 Rat 5 g/kg; Dermal LD50 Rabbit >9500 mg/kg; Inhalation LC50 Rat >5.96 mg/L 6 h (no deaths occurred)

**Ethyl acetate (141-78-6)**

Oral LD50 Rat 5620 mg/kg; Dermal LD50 Rabbit >18000 mg/kg; Inhalation LC50 Mouse 1500 ppm 4 h

**Methyl propyl ketone (107-87-9)**

Oral LD50 Rat 1600 mg/kg; Dermal LD50 Rat 6480 mg/kg; Inhalation LC50 Rat 2000 - 4000 ppm 4 h

## Product Toxicity Data

### Acute Toxicity Estimate

Dermal	> 2000 mg/kg
Inhalation - Vapor	4.6826 mg/L
Oral	> 2000 mg/kg

### Immediate Effects

Toxic if inhaled. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation. May cause drowsiness or dizziness.

### Delayed Effects

May cause cancer. May cause genetic defects. Suspected of damaging fertility or the unborn child.

### Irritation/Corrosivity Data

Causes serious eye damage, skin irritation, respiratory tract irritation.

### Respiratory Sensitization

No information available for the product.

### Dermal Sensitization

No information available for the product.

### Component Carcinogenicity

<b>Acetone</b>	<b>67-64-1</b>
ACGIH:	A4 - Not Classifiable as a Human Carcinogen
<b>2-Pentanone, 4-methyl-</b>	<b>108-10-1</b>
ACGIH:	A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans
IARC:	Monograph 101 [2013] (Group 2B (possibly carcinogenic to humans))
OSHA:	Present
<b>tert-Butyl alcohol</b>	<b>75-65-0</b>
ACGIH:	A4 - Not Classifiable as a Human Carcinogen

May cause cancer.

### Germ Cell Mutagenicity

May cause genetic defects.

### Tumorigenic Data

No data available

# Safety Data Sheet

**Material Name: HEAVY DUTY 550 CLEANING SOLVENT**

**SDS ID: 82509**

**Reproductive Toxicity**

Available data characterizes this substance as a reproductive hazard.

**Specific Target Organ Toxicity - Single Exposure**

Central nervous system respiratory system

**Specific Target Organ Toxicity - Repeated Exposure**

No significant target effects reported.

**Aspiration hazard**

This material is an aspiration hazard.

**Medical Conditions Aggravated by Exposure**

Medical conditions may include respiratory disorders, eye disorders, skin disorders, blood system disorders, central nervous system disorders, kidney disorders, and liver disorders.

**Additional Data**

No additional information is available.

<b>Section 12 - ECOLOGICAL INFORMATION</b>
--

**Ecotoxicity**

Harmful to aquatic life.

**Component Analysis - Aquatic Toxicity**

<b>Acetone</b>	<b>67-64-1</b>
Fish:	LC50 96 h Oncorhynchus mykiss 4.74 - 6.33 mL/L; LC50 96 h Pimephales promelas 6210 - 8120 mg/L [static ]; LC50 96 h Lepomis macrochirus 8300 mg/L
Invertebrate:	EC50 48 h Daphnia magna 10294 - 17704 mg/L [Static ] EPA ; EC50 48 h Daphnia magna 12600 - 12700 mg/L IUCLID
<b>Methyl ethyl ketone</b>	<b>78-93-3</b>
Fish:	LC50 96 h Pimephales promelas 3130 - 3320 mg/L [flow-through ]
Invertebrate:	EC50 48 h Daphnia magna >520 mg/L IUCLID ; EC50 48 h Daphnia magna 5091 mg/L IUCLID ; EC50 48 h Daphnia magna 4025 - 6440 mg/L [Static ] EPA
<b>Distillates, petroleum, solvent-refined light paraffinic</b>	<b>64741-89-5</b>
Fish:	LC50 96 h Oncorhynchus mykiss >5000 mg/L
Invertebrate:	EC50 48 h Daphnia magna >1000 mg/L IUCLID
<b>Naphtha</b>	<b>8030-30-6</b>
Fish:	LC50 96 h Lepomis macrochirus 9.2 mg/L [static ]
Algae:	EC50 72 h Pseudokirchneriella subcapitata 4700 mg/L IUCLID
<b>n-Butyl acetate</b>	<b>123-86-4</b>
Fish:	LC50 96 h Lepomis macrochirus 100 mg/L [static ]; LC50 96 h Pimephales promelas 17 - 19 mg/L [flow-through ]
Algae:	EC50 72 h Desmodesmus subspicatus 674.7 mg/L IUCLID

## Safety Data Sheet

**Material Name: HEAVY DUTY 550 CLEANING SOLVENT**

**SDS ID: 82509**

<b>2-Pentanone, 4-methyl-</b>	<b>108-10-1</b>
Fish:	LC50 96 h Pimephales promelas 496 - 514 mg/L [flow-through ]
Algae:	EC50 96 h Pseudokirchneriella subcapitata 400 mg/L IUCLID
Invertebrate:	EC50 48 h Daphnia magna 170 mg/L IUCLID
<b>Propylene glycol monomethyl ether acetate</b>	<b>108-65-6</b>
Fish:	LC50 96 h Pimephales promelas 161 mg/L [static ]
Invertebrate:	EC50 48 h Daphnia magna >500 mg/L IUCLID
<b>Methyl n-amyl ketone</b>	<b>110-43-0</b>
Fish:	LC50 96 h Pimephales promelas 126 - 137 mg/L [flow-through ]
<b>1-Butanol</b>	<b>71-36-3</b>
Fish:	LC50 96 h Pimephales promelas 1730 - 1910 mg/L [static ]; LC50 96 h Pimephales promelas 1740 mg/L [flow-through ]; LC50 96 h Lepomis macrochirus 100000 - 500000 µg/L [static ]; LC50 96 h Pimephales promelas 1910000 µg/L [static ]
Algae:	EC50 96 h Desmodesmus subspicatus >500 mg/L IUCLID ; EC50 72 h Desmodesmus subspicatus >500 mg/L IUCLID
Invertebrate:	EC50 48 h Daphnia magna 1983 mg/L IUCLID ; EC50 48 h Daphnia magna 1897 - 2072 mg/L [Static ] EPA
<b>tert-Butyl alcohol</b>	<b>75-65-0</b>
Fish:	LC50 96 h Pimephales promelas 6130 - 6700 mg/L [flow-through ]
Algae:	EC50 72 h Desmodesmus subspicatus >1000 mg/L IUCLID
Invertebrate:	EC50 48 h Daphnia magna 933 mg/L IUCLID ; EC50 48 h Daphnia magna 4607 - 6577 mg/L [Static ] EPA
<b>Ethyl 3-ethoxypropanoate</b>	<b>763-69-9</b>
Fish:	LC50 96 h Pimephales promelas 62 mg/L [static ]
Invertebrate:	EC50 48 h Daphnia magna 970 mg/L IUCLID
<b>Ethyl acetate</b>	<b>141-78-6</b>
Fish:	LC50 96 h Pimephales promelas 220 - 250 mg/L [flow-through ]; LC50 96 h Oncorhynchus mykiss 484 mg/L [flow-through ]; LC50 96 h Oncorhynchus mykiss 352 - 500 mg/L [semi-static ]
Invertebrate:	EC50 48 h Daphnia magna 560 mg/L [Static ] EPA
<b>Methyl propyl ketone</b>	<b>107-87-9</b>

# Safety Data Sheet

Material Name: HEAVY DUTY 550 CLEANING SOLVENT

SDS ID: 82509

Fish:	LC50 96 h Pimephales promelas 1190 - 1290 mg/L [flow-through ]
-------	--

## Persistence and Degradability

No information available for the product.

## Bioaccumulative Potential

No information available for the product.

## Mobility

No information available for the product.

## Other Toxicity

No additional information is available.

## Section 13 - DISPOSAL CONSIDERATIONS

### Disposal Methods

Dispose of in accordance with all applicable federal, state and local regulations. If discarded, this product is considered a RCRA ignitable waste, D001. Regulations may also apply to empty containers. The responsibility for proper waste disposal lies with the owner of the waste. Processing, use, or contamination by the user may change the waste code(s) applicable to the disposal of this product. Contact Safety-Kleen regarding proper recycling or disposal.

## Section 14 - TRANSPORT INFORMATION

### US DOT Information:

**Shipping Name:** PAINT

**Hazard Class:** 3

**UN/NA #:** UN1263

**Packing Group:** II

**Required Label(s):** 3 FLAMMABLE LIQUID

### IATA Information:

**Shipping Name:** PAINT

**Hazard Class:** 3

**UN#:** UN1263

**Packing Group:** II

**Required Label(s):** 3 FLAMMABLE LIQUID

### TDG Information:

**Shipping Name:** PAINT

**Hazard Class:** 3

**UN#:** UN1263

**Packing Group:** II

**Required Label(s):** 3 FLAMMABLE LIQUID

### Additional information

ERG: 128, Reference: North American Emergency Response Guidebook

## Section 15 - REGULATORY INFORMATION

### U.S. Federal Regulations

This material contains one or more of the following chemicals required to be identified under SARA Section 302 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), CERCLA (40 CFR 302.4), TSCA 12(b), and/or require an OSHA process safety plan.



# Safety Data Sheet

**Material Name: HEAVY DUTY 550 CLEANING SOLVENT**

**SDS ID: 82509**

<b>Acetone (67-64-1); Methyl ethyl ketone (78-93-3); n-Butyl acetate (123-86-4); Isobutyl acetate (110-19-0); Ethyl acetate (141-78-6)</b>	
CERCLA:	5000 lb final RQ ; 2270 kg final RQ
<b>2-Pentanone, 4-methyl-(108-10-1); 1-Butanol (71-36-3)</b>	
SARA 313:	1 % de minimis concentration
CERCLA:	5000 lb final RQ ; 2270 kg final RQ
<b>tert-Butyl alcohol (75-65-0)</b>	
SARA 313:	1 % de minimis concentration

**SARA Section 311/312 (40 CFR 370 Subparts B and C) 2016 reporting categories**

**Acute Health:** Yes **Chronic Health:** Yes **Fire:** Yes **Pressure:** No **Reactivity:** No

**SARA Section 311/312 (40 CFR 370 Subparts B and C) 2017 reporting categories**

Flammable; Carcinogenicity; Acute toxicity; Reproductive Toxicity; Skin Corrosion/Irritation; Serious Eye Damage/Eye Irritation; Specific Target Organ Toxicity; Aspiration Hazard; Germ Cell Mutagenicity

**U.S. State Regulations**

The following components appear on one or more of the following state hazardous substances lists:

Component	CAS	CA	MA	MN	NJ	PA
<b>Acetone (67-64-1); Methyl ethyl ketone (78-93-3); Naphtha (030-30-6) n-Butyl acetate (123-86-4); Isobutyl acetate (110-19-0); 2-Pentanone, 4-methyl-(108-10-1); Isopropyl acetate (108-21-4); Methyl n-amyl ketone (110-43-0); 1-Butanol (71-36-3); tert-Butyl alcohol (75-65-0); Ethyl acetate (141-78-6); Methyl propyl ketone (107-87-9)</b>		Yes	Yes	Yes	Yes	Yes
		Yes	Yes	Yes	Yes	Yes
<b>Distillates, petroleum, solvent-refined light paraffinic (64741-89-5)</b>		No	Yes	No	No	No

**THIS PRODUCT IS NOT FOR SALE OR USE IN THE STATE OF CALIFORNIA.**

<b>2-Pentanone, 4-methyl-</b>	<b>108-10-1</b>
Carc:	carcinogen , 11/4/2011
Repro/Dev. Tox	developmental toxicity , 3/28/2014

**Canada Regulations**

**Canadian WHMIS Ingredient Disclosure List (IDL)**

Components of this material have been checked against the Canadian WHMIS Ingredients Disclosure List. The List is composed of chemicals which must be identified on MSDSs if they are included in products which meet WHMIS criteria specified in the Controlled Products Regulations and are present above the threshold limits listed on the IDL

<b>Acetone (67-64-1); Methyl ethyl ketone (78-93-3); n-Butyl acetate (123-86-4); Isobutyl acetate (110-19-0); 2-Pentanone, 4-methyl-(108-10-1); Isopropyl acetate (108-21-4); Methyl n-amyl ketone (110-43-0); 1-Butanol (71-36-3); tert-Butyl alcohol (75-65-0) Ethyl acetate (141-78-6);Methyl propyl ketone (107-87-9)</b>	1%
---	----

# Safety Data Sheet

Material Name: HEAVY DUTY 550 CLEANING SOLVENT

SDS ID: 82509

## Component Analysis - Inventory

Acetone (67-64-1); Hydrocarbons, aromatic (63231-51-6) Methyl ethyl ketone (78-93-3); Alcohols, C1-3 (68475-56-9) Distillates, petroleum, solvent-refined light paraffinic (64741-89-5) Naphtha (8030-30-6) n-Butyl acetate (123-86-4) Isobutyl acetate (110-19-0) 2-Pentanone, 4-methyl- (108-10-1) Isopropyl acetate (108-21-4) Propylene glycol monomethyl ether acetate (108-65-6) ; Methyl n-amyl ketone (110-43-0) ;1-Butanol (71-36-3) ;tert-Butyl alcohol (75-65-0); Ethyl 3-ethoxypropanoate (763-69-9); Ethyl acetate (141-78-6); Methyl propyl ketone (107-87-9)

US	CA
Yes	DSL

## Section 16 - OTHER INFORMATION

### NFPA Ratings

Health: 3 Fire: 3 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

### Summary of Changes

Regulatory review and update. Revision to Section 11.

### Key / Legend

ACGIH - American Conference of Governmental Industrial Hygienists; BOD - Biochemical Oxygen Demand; C - Celsius; CA - Canada; CA/MA/MN/NJ/PA - California/Massachusetts/Minnesota/New Jersey/Pennsylvania\*; CAS - Chemical Abstracts Service; CFR - Code of Federal Regulations (US); CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CLP - Classification, Labelling, and Packaging; CPR - Controlled Products Regulations; DOT - Department of Transportation; DSL - Domestic Substances List; EPA - Environmental Protection Agency; F - Fahrenheit; IDL - Ingredient Disclosure List; IDLH - Immediately Dangerous to Life and Health; IMDG - International Maritime Dangerous Goods; LEL - Lower Explosive Limit; LLV - Level Limit Value; LOLI - List Of Lists™ - ChemADVISOR's Regulatory Database; MAK - Maximum Concentration Value in the Workplace; MEL - Maximum Exposure Limits; NDSL - Non-Domestic Substance List (Canada); NFPA - National Fire Protection Agency; NIOSH - National Institute for Occupational Safety and Health; NJTSR - New Jersey Trade Secret Registry; NTP - National Toxicology Program; OSHA - Occupational Safety and Health Administration; PEL- Permissible Exposure Limit; RCRA - Resource Conservation and Recovery Act; SARA - Superfund Amendments and Reauthorization Act; STEL - Short-term Exposure Limit; TDG - Transportation of Dangerous Goods; TLV - Threshold Limit Value; TSCA - Toxic Substances Control Act; TWA - Time Weighted Average; UEL - Upper Explosive Limit; UN/NA - United Nations /North American; US - United States; WHMIS - Workplace Hazardous Materials Information System (Canada).  
Other Information

### Disclaimer:

User assumes all risks incident to the use of this product. To the best of our knowledge, the information contained herein is accurate. However, Safety-Kleen assumes no liability whatsoever for the accuracy or completeness of the information contained herein. No representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose or of any other nature are made hereunder with respect to the information or the product to which the information refers. The data contained on this sheet apply to the product as supplied to the user.