

Material Name: ArmaKleen Paint and Ink Remover: Part A SDS ID: 82976

Section 1 - PRODUCT AND COMPANY IDENTIFICATION

Material Name

ArmaKleen Paint and Ink Remover: Part A

Product Code

6363, 6463

Formula Code 42000128

Product Use

Organic paint and ink remover that is one part of a two part coating removal process. This is designed to remove paints and inks from aluminum and steel. If this product is used in combination with other products, refer to the Safety Data Sheet for those products.

Restrictions on Use

For professional use only.

MANUFACTURER

Church & Dwight

The ArmaKleenTM Company

469 North Harrison Street

Princeton, NJ 08543

Phone: (800) 332-5424

www.churchdwight.com

SUPPLIER (in the U.S.A)

Safety-Kleen Systems, Inc.

42 Longwater Drive Norwell, MA 02061-9149

U.S.A.

Phone: 1-800-669-5740

www.safety-kleen.com

SUPPLIER (in Canada)

Safety-Kleen Canada Inc.

25 Regan Road

Brampton, Ontario, L7A 1B2

Canada

Phone: 1-800-669-5740

Emergency Telephone Number

Medical: 1-888-234-1828 Chemical: 1-800-424-9300 (CHEMTREC)

Issue Date

May 15, 2020

Supersedes Issue Date

March 6, 2017

Original Issue Date

September 1, 2004

Section 2 - HAZARDS IDENTIFICATION

Classification in accordance with Schedule 1 of Hazardous Products Regulations (HPR) (SOR/2015-17)

Acute Toxicity - Oral - Category 4

Acute Toxicity - Inhalation - Vapor - Category 4

Serious Eye Damage/Eye Irritation - Category 1

GHS Label Elements

Symbol(s)



Material Name: ArmaKleen Paint and Ink Remover: Part A SDS ID: 82976

Signal Word

Danger.

Hazard Statement(s)

Harmful if swallowed.

Harmful if inhaled.

Causes serious eye damage.

Precautionary Statement(s)

Prevention

Avoid breathing vapor or mist. Use only outdoors or in a well-ventilated area. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Wear eye protection/face protection.

Response

IF SWALLOWED: Call a POISON CENTER or doctor/physician. Do NOT induce vomiting. Rinse mouth. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.

Storage

None needed according to classification criteria.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

CAS	Component Name	Percent		
100-51-6	Benzyl alcohol	71-70		
67784-80-9	Soybean oil, methyl ester	19-21		
34398-01-1	Poly(oxy-1,2-ethanediyl), .alphaundecylomega hydroxy-	2.0-2.6		
68439-46-3	Alcohols, C9-11, ethoxylated	2.0-2.6		

Section 4 - FIRST AID MEASURES

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician.

Skin

IF ON SKIN: Wash with plenty of soap and water. Call a POISON CENTER or doctor if you feel unwell.

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting. Rinse mouth.

Most Important Symptoms/Effects

Acute

Harmful if swallowed. Harmful if inhaled. Causes eye burns. May cause respiratory tract irritation and skin irritation.

Page 2 of 9 Rev. 05/20

Material Name: ArmaKleen Paint and Ink Remover: Part A SDS ID: 82976

Delayed

No information on significant adverse effects.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically and supportively.

Section 5 - FIRE FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media

Use alcohol foam, carbon dioxide or dry chemical.

Unsuitable Extinguishing Media

Do not use high-pressure water streams. Water or foam may cause frothing.

Special Hazards Arising from the Chemical

Negligible fire hazard.

Hazardous Combustion Products

Decomposition and combustion materials may be toxic. Burning may produce Carbon monoxide.

Advice for firefighters

Risk of explosion if heated under confinement.

Fire Fighting Measures

Move container from fire area if it can be done without risk. Keep storage containers cool with water spray. Heated containers may rupture. "Empty" containers may retain residue and can be dangerous. Product is not sensitive to mechanical impact or static discharge.

Special Protective Equipment and Precautions for Firefighters

A positive-pressure, self-contained breathing apparatus (SCBA) and full-body protective equipment are required for fire emergencies.

Section 6 - ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Wear personal protective clothing and equipment, see Section 8.

Methods and Materials for Containment and Cleaning Up

Remove all ignition sources. Do not touch or walk through spilled product. Keep unnecessary and unprotected personnel from entering. Ventilate area and avoid breathing vapor or mist. Contain spill as a liquid for possible recovery, or sorb with compatible sorbent material and shovel with a clean, spark proof tool into a sealable container for disposal. Additionally, for large spills: Dike far ahead of liquid spill for collection and later disposal.

Section 7 - HANDLING AND STORAGE

Precautions for Safe Handling

Keep away from sparks or flame. Avoid breathing vapor or mist. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. Wash thoroughly after handling.

Conditions for Safe Storage, Including any Incompatibilities

None needed according to classification criteria.

Keep container tightly closed when not in use and during transport. Store containers in a cool, dry place. Do not pressurize, cut, weld, braze, solder, drill, or grind containers. Keep containers away from heat, flame, sparks, static electricity, or other sources of ignition. Empty product containers may retain product residue and can be dangerous.

Incompatible Materials

Avoid oxidizing agents and reducing agents, strong acids.

Page 3 of 9 Rev. 05/20

Material Name: ArmaKleen Paint and Ink Remover: Part A SDS ID: 82976

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Component Exposure Limits

Canada and ACGIH have not developed exposure limits for any of this product's components.

ACGIH - Threshold Limit Values - Biological Exposure Indices (BEI)

There are no biological limit values for any of this product's components.

Engineering Controls

Provide general ventilation needed to maintain concentration of vapor or mist below applicable exposure limits. Where adequate general ventilation is unavailable, use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below applicable exposure limits.

Individual Protection Measures, such as Personal Protective Equipment

Eye/face protection

Wear splash resistant safety goggles with a faceshield. Provide an emergency eye wash fountain and quick drench shower in the immediate work area. Contact lens use is not recommended.

Respiratory Protection

A respiratory protection program which meets USA's OSHA General Industry Standard 29 CFR 1910.134 or Canada's CSA Standard Z94.4-M1982 requirements must be followed whenever workplace conditions warrant a respirator's use. Consult a qualified Industrial Hygienist or Safety Professional for respirator selection guidance.

Skin Protection/Glove Recommendations

Where skin contact is likely, wear gloves impervious to product; use of natural rubber (latex) or equivalent gloves is not recommended. To avoid prolonged or repeated contact where spills and splashes are likely, wear appropriate chemical-resistant face shield, boots, apron, whole body suits or other protective clothing. When product is heated and skin contact is likely, wear heat-resistant gloves, boots, and other protective clothing.

Protective Materials

Personal protective equipment should be selected based upon the conditions under which this material is used. A hazard assessment of the work area for PPE requirements should be conducted by a qualified professional pursuant to regulatory requirements. The following PPE should be considered the minimum required: Safety glasses, Gloves, Lab coat or apron.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Clear, colorless liquid	Physical State	Liquid
Odor	Aromatic	Color	colorless
Odor Threshold	Not available	pH	6.6 (5% solution)
Melting Point	<-0.40°F(<-18 °C)	Boiling Point	249.8°F (>121 °C)
Boiling Point Range	Not available	Freezing point	Not available
Evaporation Rate	(equal to water.)	Flammability (solid, gas)	Not available
Autoignition Temperature	Not available	Flash Point	228°F (>109 °C)
Lower Explosive Limit	Not available	Decomposition temperature	Not available
Upper Explosive Limit	Not available	Vapor Pressure	Not available
Vapor Density (air=1)	Not available	Specific Gravity (water=1)	1.009

Page 4 of 9 Rev. 05/20

Material Name: ArmaKleen Paint and Ink Remover: Part A SDS ID: 82976

Water Solubility Not available Partition coefficient: n-Not available

octanol/water

Viscosity Not available Kinematic viscosity Not available

Solubility (Other) Not available Density Not available

Molecular Weight Not available

76.7 WT%; 6.44 LB/US gal; 772 g/L; As per 40 CFR Part 51.100(s)

VOC Composite Partial Pressure @20°C = 0.002 mmHG

Compounds (As

This product does not contain an ingredient that meets the definition of a
'Photochemically Reactive Solvent' as found in California's South Coast Air

Overline Management District Puls 102 Definition of Target Consultances.

Quality Management District Rule 102 – Definition of Terms. Consult your state or

local air district regulations for location specific information.

Section 10 - STABILITY AND REACTIVITY

Reactivity

No reactivity hazard is expected.

Chemical Stability

Stable under normal temperatures and pressures.

Possibility of Hazardous Reactions

Polymerization is not known to occur under normal temperature and pressures. Not reactive with water.

Conditions to Avoid

Avoid sparks or flame, direct sunlight.

Incompatible Materials

Avoid oxidizing agents, reducing agents, strong acids.

Hazardous decomposition products

None under normal temperatures and pressures. See also SECTION 5: HAZARDOUS COMBUSTION PRODUCTS.

Thermal decomposition products

Carbon monoxide.

Section 11 - TOXICOLOGICAL INFORMATION

Information on Likely Routes of Exposure

Inhalation

Harmful if inhaled. May cause irritation.

Skin Contact

May cause skin irritation.

Eve Contact

Causes serious eye damage.

Ingestion

Harmful if swallowed. May cause irritation.

Acute and Chronic Toxicity

Component Analysis - LD50/LC50

The components of this material have been reviewed in various sources and the following selected endpoints are published:

Benzyl alcohol (100-51-6)

Oral LD50 Rat 1230 mg/kg; Dermal LD50 Rabbit 2 g/kg; Inhalation LC50 Rat 8.8 mg/L 4 h

Alcohols, C9-11, ethoxylated (68439-46-3)

Oral LD50 Rat 1400 mg/kg

Page 5 of 9 Rev. 05/20

Material Name: ArmaKleen Paint and Ink Remover: Part A SDS ID: 82976

Product Toxicity Data

Product Analysis LD/LC 50 Toxicity Values

Oral LD50: 1	475 mg/kg
--------------	-----------

Acute Toxicity Estimate

No data available.

Immediate Effects

Harmful if swallowed. Harmful if inhaled. Causes serious eye damage. May cause respiratory tract irritation and skin irritation.

Delayed Effects

No information on significant adverse effects.

Irritation/Corrosivity Data

Causes serious eye damage. May cause respiratory tract irritation and skin irritation.

Respiratory Sensitization

Based on best current information, there is no known human sensitization associated with this product.

Dermal Sensitization

No information on significant adverse effects.

Component Carcinogenicity

None of this product's components are listed by ACGIH, IARC, NTP, DFG or OSHA.

Germ Cell Mutagenicity

Based on best current information, there is no known teratogenicity associated with this product.

Experimental evidence suggests that this product does not cause mutagenesis.

Tumorigenic Data

No data available

Reproductive Toxicity

Based on best current information, there is no known reproductive toxicity associated with this product.

Specific Target Organ Toxicity - Single Exposure

No target organs identified.

Specific Target Organ Toxicity - Repeated Exposure

No target organs identified.

Aspiration hazard

Based on available data, the classification criteria are not met.

Medical Conditions Aggravated by Exposure

Individuals with pre-existing respiratory tract (nose, throat, and lungs), eye, and/or skin disorders may have increased susceptibility to the effects of exposure.

Section 12 - ECOLOGICAL INFORMATION

Component Analysis - Aquatic Toxicity

Benzyl alcohol	100-51-6
Fish:	LC50 96 h Pimephales promelas 460 mg/L [static]; LC50 96 h Lepomis macrochirus 10 mg/L [static]
Invertebrate:	EC50 48 h water flea 23 mg/L

Invertebrate Toxicity

No additional information is available.

Page 6 of 9 Rev. 05/20

Material Name: ArmaKleen Paint and Ink Remover: Part A SDS ID: 82976

Persistence and Degradability

No information available for the product.

Bioaccumulative Potential

No information available for the product.

Mobility

No information available for the product.

Section 13 - DISPOSAL CONSIDERATIONS

Disposal Methods

Dispose in accordance with federal, state, provincial, and local regulations. Regulations may also apply to empty containers. The responsibility for proper waste disposal lies with the owner of the waste. Contact ArmaKleen regarding proper recycling or disposal.

Section 14 - TRANSPORT INFORMATION

US DOT Information: Not regulated for transport. IATA Information: Not regulated for transport. TDG Information: Not regulated for transport.

International Bulk Chemical Code

This material contains one or more of the following chemicals required by the IBC Code to be identified as dangerous chemicals in bulk.

Benzyl alcohol	100-51-6
IBC Code:	Category Y
Alcohols, C9-11, ethoxylated	68439-46-3
IBC Code:	Category Y

Section 15 - REGULATORY INFORMATION

Canada Regulations

CEPA - Priority Substances List

None of this product's components are on the list.

Ozone Depleting Substances

None of this product's components are on the list.

Council of Ministers of the Environment - Soil Quality Guidelines

None of this product's components are on the list.

Council of Ministers of the Environment - Water Quality Guidelines

None of this product's components are on the list.

U.S. Federal Regulations

None of this product's components are listed under SARA Sections 302/304 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), CERCLA (40 CFR 302.4), TSCA 12(b), or require an OSHA process safety plan.

SARA Section 311/312 (40 CFR 370 Subparts B and C) 2016 reporting categories

Acute Health: Yes Chronic Health: No Fire: No Pressure: No Reactivity: No

Not listed under California Proposition 65.

Page 7 of 9 Rev. 05/20

Material Name: ArmaKleen Paint and Ink Remover: Part A SDS ID: 82976

Component Analysis - Inventory Benzyl alcohol (100-51-6)

Denzyl arconol (100-51-0)											
US	CA	AU	CN	I E	EU	JP - ENCS	JP - ISHL		KR KECI - Annex 1	KR KECI - Annex 2	
Yes	DSL	Yes	Ye	s E	EIN	Yes	Yes		Yes	No	
KR -	KR - REACH CCA		MX	NZ	PH	TH- TECI	TW	VN (Draft)			
No			Yes	Yes	Yes	Yes	Yes	Yes			

Poly(oxy-1,2-ethanediyl), .alpha.-undecyl-.omega.-hydroxy- (34398-01-1)

US	CA	AU	C	CN EU		U	JP - ENCS	JP - ISHL		JP - ISHL KR KECI - Annex 1	
Yes	DSL	Yes	Y	es	No No No		No		Yes	No	
KR -	KR - REACH CCA		M	X	NZ	PH	TH- TECI	TW	VN (Draft)		
No		No No Yes			Yes	No	Yes	Yes			

Alcohols, C9-11, ethoxylated (68439-46-3)

US	CA	AU	CN	EU		JP - ENCS	JP - ISHL		KR KECI - Annex 1	KR KECI - Annex 2
Yes	DSL	Yes	Yes	Yes No		No	No		Yes	No
KR - REACH CCA		1	MX	NZ	PH	TH- TECI	TW	VN (Draft)		
No			Yes	Yes	Yes	Yes	Yes	Yes		

Section 16 - OTHER INFORMATION

NFPA Ratings

Health: 2 Fire: 0 Instability: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

Summary of Changes

Regulatory review and update. Update to VOC information.

Key / Legend

ACGIH - American Conference of Governmental Industrial Hygienists; ADR - European Road Transport; AU - Australia; BOD - Biochemical Oxygen Demand; C - Celsius; CA - Canada; CA/MA/MN/NJ/PA - California/Massachusetts/Minnesota/New Jersey/Pennsylvania*; CAS - Chemical Abstracts Service; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CFR - Code of Federal Regulations (US); CLP - Classification, Labelling, and Packaging; CN - China; CPR - Controlled Products Regulations; DFG - Deutsche Forschungsgemeinschaft; DOT - Department of Transportation; DSD - Dangerous Substance Directive; DSL - Domestic Substances List; EC – European Commission; EEC -

Page 8 of 9 Rev. 05/20

Material Name: ArmaKleen Paint and Ink Remover: Part A SDS ID: 82976

European Economic Community; EIN - European Inventory of (Existing Commercial Chemical Substances); EINECS - European Inventory of Existing Commercial Chemical Substances; ENCS - Japan Existing and New Chemical Substance Inventory; EPA - Environmental Protection Agency; EU - European Union; F -Fahrenheit; F - Background (for Venezuela Biological Exposure Indices); IARC - International Agency for Research on Cancer: IATA - International Air Transport Association: ICAO - International Civil Aviation Organization; IDL - Ingredient Disclosure List; IDLH - Immediately Dangerous to Life and Health; IMDG -International Maritime Dangerous Goods; ISHL - Japan Industrial Safety and Health Law; IUCLID -International Uniform Chemical Information Database; JP - Japan; Kow - Octanol/water partition coefficient; KR KECI Annex 1 - Korea Existing Chemicals Inventory (KECI) / Korea Existing Chemicals List (KECL); KR KECI Annex 2 - Korea Existing Chemicals Inventory (KECI) / Korea Existing Chemicals List (KECL), KR - Korea; LD50/LC50 - Lethal Dose/ Lethal Concentration; LEL - Lower Explosive Limit; LLV - Level Limit Value; LOLI - List Of LIstsTM - ChemADVISOR's Regulatory Database; MAK -Maximum Concentration Value in the Workplace; MEL - Maximum Exposure Limits; MX - Mexico; Ne-Non-specific; NFPA - National Fire Protection Agency; NIOSH - National Institute for Occupational Safety and Health; NJTSR - New Jersey Trade Secret Registry; Nq - Non-quantitative; NSL - Non-Domestic Substance List (Canada); NTP - National Toxicology Program; NZ - New Zealand; OSHA - Occupational Safety and Health Administration; PEL- Permissible Exposure Limit; PH - Philippines; RCRA - Resource Conservation and Recovery Act; REACH- Registration, Evaluation, Authorisation, and restriction of Chemicals; RID - European Rail Transport; SARA - Superfund Amendments and Reauthorization Act; Sc -Semi-quantitative; STEL - Short-term Exposure Limit; TCCA - Korea Toxic Chemicals Control Act; TDG -Transportation of Dangerous Goods; TLV - Threshold Limit Value; TSCA - Toxic Substances Control Act; TW - Taiwan; TWA - Time Weighted Average; UEL - Upper Explosive Limit; UN/NA - United Nations /North American; US - United States; VLE - Exposure Limit Value (Mexico); VN (Draft) - Vietnam (Draft); WHMIS - Workplace Hazardous Materials Information System (Canada).

Other Information

Disclaimer:

User assumes all risks incident to the use of this product. To the best of our knowledge, the information contained herein is accurate. However, ArmaKleen assumes no liability whatsoever for the accuracy or completeness of the information contained herein. No representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose or of any other nature are made hereunder with respect to the information or the product to which the information refers. The data contained on this sheet apply to the product as supplied to the user.

Page 9 of 9 Rev. 05/20