

Performance PlusTransmission Fluid TO-4 10W

Safety Data Sheet

SDS ID: 820324

Section 1 - PRODUCT AND COMPANY IDENTIFICATION

Material Name

Performance Plus Transmission Fluid TO-4 10W

Product Code

Prefix 24

Synonyms

Drive Train TO-4 SAE 10 Blend

Product Use

Lubricating oils. If this product is used in combination with other products, refer to the Safety Data Sheet for those products.

Restrictions on Use

FOR PRODUCT MANUFACTURED IN THE U.S.A.:

MANUFACTURERSUPPLIER (in Canada)Safety-Kleen Systems, Inc.Safety-Kleen Canada, Inc.

42 Longwater Drive 25 Regan Road

Norwell, MA 02061-9149 Brampton, Ontario, Canada L7A 1B2

U.S.A.

FOR PRODUCT MANUFACTURED IN CANADA:

MANUFACTURERSUPPLIER (In the U.S.A.)Safety-Kleen Canada, Inc.Safety-Kleen Systems, Inc.25 Regan Road42 Longwater Drive

Brampton, Ontario, Canada L7A 1B2 Norwell, MA 02061-9149

U.S.A.

www.safety-kleen.com Phone: 1-800-669-5740

Emergency Phone #: 1-800-468-1760

Issue Date

August 26, 2019

Supersedes Issue Date

October 9, 2017

Original Issue Date

October 9, 2017

Section 2 - HAZARDS IDENTIFICATION

Classification in accordance with paragraph (d) of 29 CFR 1910.1200.

None needed according to classification criteria.

GHS Label Elements

Symbol(s)

None needed according to classification criteria.

Signal Word

None needed according to classification criteria

Hazard Statement(s)

None needed according to classification criteria.

Precautionary Statement(s)

Prevention

None needed according to classification criteria.

Response

None needed according to classification criteria.

Material Name: Performance Plus Transmission Fluid TO-4 10W

Storage

None needed according to classification criteria.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

SDS ID: 820324

CAS	Component Name	Percent
64741-88-4	Distillates, petroleum, solvent-refined heavy paraffinic	78-100
8012-95-1	Paraffin oils	4-10

Section 4 - FIRST AID MEASURES

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention, if needed.

Skin

IF ON SKIN: Wash with plenty of soap and water. Get medical attention, if needed.

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention, if needed.

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.

Most Important Symptoms/Effects

Acute

May cause mild skin irritation. Contact with the eyes may be slightly irritating.

Delayed

No information on significant adverse effects.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically and supportively.

Section 5 - FIRE FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media

Carbon dioxide, regular foam, dry chemical, water spray, or water fog. Water or foam may cause frothing.

Unsuitable Extinguishing Media

Water may be an ineffective extinguishing medium but should be used to cool fire-exposed containers.

Special Hazards Arising from the Chemical

Dense black smoke occurs during fire. Vapors are heavier than air and may travel along the ground to some distant source of ignition and flash back.

Hazardous Combustion Products

Decomposition and combustion materials may be toxic. Burning may produce carbon monoxide and other organic compounds. oxides of carbon, oxides of phosphorus, oxides of sulfur, hydrogen sulfide, alkyl Mercaptan, other sulfides

Advice for firefighters

Directly spraying water or foam onto hot burning product may cause frothing.

Page 2 of 9 Rev. 08/19

Material Name: Performance Plus Transmission Fluid TO-4 10W SDS ID: 820324

Fire Fighting Measures

Move container from fire area if it can be done without risk. Cool containers with water spray until well after the fire is out. Stay away from the ends of tanks. Fight fire from maximum distance or use unmanned hose holders or monitor nozzles. Keep unnecessary people away, isolate hazard area, and deny entry.

Special Protective Equipment and Precautions for Firefighters

A positive-pressure, self-contained breathing apparatus (SCBA) and full-body protective equipment are required for fire emergencies.

Section 6 - ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Avoid breathing vapor. Avoid contact with skin, eyes and clothing. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Wear personal protective clothing and equipment, see Section 8.

Methods and Materials for Containment and Cleaning Up

Remove all ignition sources. Do not touch or walk through spilled product. Stop leak if you can do it without risk. Wear protective equipment and provide engineering controls as specified in SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION. Isolate hazard area. Keep unnecessary people away, isolate hazard area and deny entry. Do not touch or walk through spilled material. Stop leak if you can do it without risk. Contain spill away from surface water and sewers. Contain spill as a liquid for possible recovery, or sorb with compatible sorbent material and shovel with a clean, spark proof tool into a sealable container for disposal. Additionally, for large spills: Dike far ahead of liquid spill for collection and later disposal. There may be specific regulatory reporting requirements associated with spills, leaks, or releases of this product. Also see SECTION 15: REGULATORY INFORMATION.

Section 7 - HANDLING AND STORAGE

Precautions for Safe Handling

Keep away from sparks or flame. Where flammable mixtures may be present, equipment safe for such locations should be used. Use clean tools. When transferring large volumes of product, metal containers, including trucks and tank cars, should be grounded and bonded. These products have a low vapor pressure and are not expected to present an inhalation hazard under normal temperatures and pressures. However, when aerosolizing, misting, or heating these products, do not breathe vapor or mist. Use in a well ventilated area. Avoid contact with: Skin, eyes, clothing, shoes. Wash thoroughly after handling. Do not eat, drink, or smoke when using this product. Read label before use. Do not handle until all safety precautions have been read and understood. Use Personal Protective equipment as required

Conditions for Safe Storage, Including any Incompatibilities

None needed according to classification criteria.

Further information: Keep container tightly closed and properly labeled. Store in a cool, dry, well-ventilated area. Store away from heat and direct sunlight. Avoid contact with strong oxidizers. Keep container sealed when not in use. Keep container sealed when not in use. Store and handle in accordance with all current regulations and standards. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Empty product containers may retain product residue and can be dangerous.

Incompatible Materials

Acids, oxidizing materials

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Component Exposure Limits Distillates, petroleum, solvent-refined heavy paraffinic 64741-88-4

Page 3 of 9 Rev. 08/19

SDS ID: 820324

Material Name: Performance Plus Transmission Fluid TO-4 10W

ACGIH:	Exposure by all routes should be carefully controlled to levels as low as possible (related to Untreated and mildly-treated oils)
NIOSH:	350 mg/m3 TWA (related to Petroleum distillates, n.o.s.) 1800 mg/m3 Ceiling 15 min (related to Petroleum distillates, n.o.s.) 1100 ppm IDLH (10% LEL) (related to Petroleum distillates, n.o.s.)
OSHA (US):	500 ppm TWA; 2000 mg/m3 TWA (related to Petroleum distillates, n.o.s.)
Paraffin oils	8012-95-1
ACGIH:	5 mg/m3 TWA (excluding metal working fluids, highly & severely refined) inhalable particulate matter
NIOSH:	5 mg/m3 TWA; 10 mg/m3 STEL; 2500 mg/m3 IDLH
OSHA (US):	5 mg/m3 TWA

ACGIH - Threshold Limit Values - Biological Exposure Indices (BEI)

There are no biological limit values for any of this product's components.

Engineering Controls

Provide general ventilation. Where adequate general ventilation is unavailable, use process enclosures, local exhaust ventilation, or other engineering controls.

Individual Protection Measures, such as Personal Protective Equipment **Eve/face protection**

Wear safety glasses. Additional protection like goggles, face shields, or respirators may be needed dependent upon anticipated use and concentrations of mists or vapors. Eye wash fountain and emergency showers are recommended. Contact lens use is not recommended.

Respiratory Protection

A respiratory protection program which meets USA's OSHA General Industry Standard 29 CFR 1910.134 or Canada's CSA Standard Z94.4-M1982 requirements must be followed whenever workplace conditions warrant a respirator's use. Consult a qualified Industrial Hygienist or Safety Professional for respirator selection guidance.

Glove Recommendations

Where skin contact is likely, wear chemical impervious protective gloves; use of natural rubber or equivalent gloves is not recommended. When products are heated and skin contact is likely, wear heat-resistant gloves, boots, and other protective clothing. To avoid prolonged or repeated contact where spills and splashes are likely, wear appropriate chemical-resistant faceshield, boots, apron, coveralls, long sleeve shirts, or other protective clothing.

Protective Materials

Personal protective equipment should be selected based upon the conditions under which this material is used. A hazard assessment of the work area for PPE requirements should be conducted by a qualified professional pursuant to regulatory requirements. The following PPE should be considered the minimum required: Safety glasses. Gloves. Lab coat or apron.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES Clear, amber liquid **Physical State** Not available **Appearance** Mild ,petroleum ,hydrocarbon odor Odor Color Not available **Odor Threshold** Not available pН Not available

Page 4 of 9 Rev. 08/19

Material Name: Performance Plus Transmission Fluid TO-4 10W SDS ID: 820324

Melting Point	Not available	Boiling Point	>260 °C
Wiching I offit	Not available	Doming 1 omt	(Approximate)

Boiling Point Not available Freezing point Not available Range

Evaporation Rate (Negligible at ambient conditions) Flammability (solid, gas) Not available

Autoignition Not available Flash Point 218 °C (424°F) **Temperature**

Lower Explosive Not available **Decomposition temperature** Not available Limit

Upper Explosive (Negligible at

Not available Vapor Pressure Limit ambient conditions)

Vapor Density >1 at STP Specific Gravity (water=1) 0.872 (air=1)

Partition coefficient: n-Not available Water Solubility (Negligible) octanol/water

Viscosity 33.66 cSt 40 °C (5.59 cSt @100 C) Kinematic viscosity Not available

Solubility (Other) Not available Density 7.277 lb/gal

VOC Molecular Weight Not available 91.532 % (6.661 lb/gal)

Percent Solids by

7.191 % Weight

Section 10 - STABILITY AND REACTIVITY

Reactivity

No reactivity hazard is expected.

Chemical Stability

Stable under normal temperatures and pressures.

Possibility of Hazardous Reactions

Will not occur.

Conditions to Avoid

Avoid direct sunlight, temperature extremes.

Incompatible Materials

Acids, oxidizing materials

Hazardous decomposition products

Smoke, carbon monoxide, carbon dioxide, aldehydes, oxides of carbon, oxides of phosphorus, oxides of sulfur, alkyl mercaptans, other sulfides.

Section 11 - TOXICOLOGICAL INFORMATION

Information on Likely Routes of Exposure

Inhalation

May cause nausea, headache, or weakness.

Page 5 of 9 Rev. 08/19

Material Name: Performance Plus Transmission Fluid TO-4 10W

Skin Contact

May cause mild irritation.

Eye Contact

Contact with the eyes may be slightly irritating.

Ingestion

No information on significant adverse effects.

Acute and Chronic Toxicity

Component Analysis - LD50/LC50

The components of this material have been reviewed in various sources and the following selected endpoints are published:

SDS ID: 820324

Distillates, petroleum, solvent-refined heavy paraffinic (64741-88-4)

Oral LD50 Rat >5000 mg/kg; Dermal LD50 Rabbit >2000 mg/kg; Inhalation LC50 Rat >5530 mg/m3 4 h (no deaths occurred)

Paraffin oils (8012-95-1)

Oral LD50 Rat >24 g/kg; Inhalation LC50 Rat 2062 ppm 4 h

Product Toxicity Data

Acute Toxicity Estimate

Dermal	> 2000 mg/kg
Oral	> 2000 mg/kg

Immediate Effects

May cause mild skin irritation. Contact with the eyes may be slightly irritating.

Delayed Effects

No information on significant adverse effects.

Irritation/Corrosivity Data

May cause mild skin irritation. Contact with the eyes may be slightly irritating.

Respiratory Sensitization

Hot vapors may cause irritation.

Dermal Sensitization

Repeated and prolonged contact may lead to skin sensitization.

Component Carcinogenicity

Distillates, petroleum, solvent-refined heavy paraffinic	64741-88-4
ACGIH:	A2 - Suspected Human Carcinogen (related to Untreated and mildly-treated oils)
IARC:	Monograph 100F [2012]; Supplement 7 [1987]; Monograph 33 [1984] (related to Untreated and mildly-treated oils) (Group 1 (carcinogenic to humans))
NTP:	Known Human Carcinogen (related to Untreated and mildly-treated oils)
OSHA:	Present (related to Untreated and mildly-treated oils)
Paraffin oils	8012-95-1
ACGIH:	A4 - Not Classifiable as a Human Carcinogen (highly and severely refined); A2 - Suspected Human Carcinogen (poorly and mildly refined)

Page 6 of 9 Rev. 08/19

Material Name: Performance Plus Transmission Fluid TO-4 10W SDS ID: 820324

Germ Cell Mutagenicity

No information available for the product.

Tumorigenic Data

No information available for the product.

Reproductive Toxicity

No information available for the product.

Specific Target Organ Toxicity - Single Exposure

No target organs identified.

Specific Target Organ Toxicity - Repeated Exposure

No target organs identified.

Aspiration hazard

No information available for the product.

Medical Conditions Aggravated by Exposure

No data available.

Section 12 - ECOLOGICAL INFORMATION

Ecotoxicity

No data available.

Component Analysis - Aquatic Toxicity

Distillates, petroleum, solvent-refined heavy paraffinic	64741-88-4				
Fish:	LC50 96 h Oncorhynchus mykiss >5000 mg/L				
Invertebrate:	EC50 48 h Daphnia magna >1000 mg/L IUCLID				

Persistence and Degradability

No data available.

Bioaccumulative Potential

No data available.

Mobility

No data available.

Other Toxicity

No data available.

Section 13 - DISPOSAL CONSIDERATIONS

Disposal Methods

Dispose in accordance with all applicable federal, state/regional and local laws and regulations. Regulations may also apply to empty containers. The responsibility for proper waste disposal lies with the owner of the waste. Contact Safety-Kleen regarding proper recycling or disposal.

Component Waste Numbers

The U.S. EPA has not published waste numbers for this product's components.

Section 14 - TRANSPORT INFORMATION

US DOT Information: Not regulated for transportation. IATA Information: Not regulated for transportation. IMDG Information: Not regulated for transportation.

Page 7 of 9 Rev. 08/19

Material Name: Performance Plus Transmission Fluid TO-4 10W SDS ID: 820324

TDG Information: Not regulated for transportation.

International Bulk Chemical Code

This material does not contain any chemicals required by the IBC Code to be identified as dangerous chemicals in bulk.

Section 15 - REGULATORY INFORMATION

U.S. Federal Regulations

None of this product's components are listed under SARA Sections 302/304 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), CERCLA (40 CFR 302.4), TSCA 12(b), or require an OSHA process safety plan.

SARA Section 311/312 (40 CFR 370 Subparts B and C) reporting categories

No hazard categories applicable.

U.S. State Regulations

The following components appear on one or more of the following state hazardous substances lists:

Component	CAS	CA	MA	MN	NJ	PA
Distillates, petroleum, solvent-refined heavy paraffinic	64741-88-4	No	No	No	No	Yes
Paraffin oils	8012-95-1	Yes	Yes	Yes	Yes	Yes

California Safe Drinking Water and Toxic Enforcement Act (Proposition 65)

Not listed under California Proposition 65.

Component Analysis - Inventory

Distillates, petroleum, solvent-refined heavy paraffinic (64741-88-4)

US	CA	LAU II CN II EU - II I		CN E		JP - ISHL		KR KECI - Annex 1	KR KECI - Annex 2		
Yes	DSL	Yes	Y	es	EIN	N	No	No		Yes	No
KR -	KR - REACH CCA		١	M	X	NZ	PH	TH- TECI	TW	VN (Draft)	
No			Ye	es	Yes	Yes	No	Yes	Yes		

Paraffin oils (8012-95-1)

1 mm ons (0012 % 1)												
US	CA	AU	CN	E	U	JP - ENCS	JP - ISHL		KR KECI - Annex 1	KR KECI - Annex 2		
Yes	DSL	Yes	Yes	E	IN	No	No		No Ye		Yes	No
KR - REACH CCA		N	ИΧ	NZ	PH	TH- TECI	TW	VN (Draft)				
No		7	l'es	Yes	Yes	Yes	Yes	Yes				

Page 8 of 9 Rev. 08/19

Material Name: Performance Plus Transmission Fluid TO-4 10W

Section 16 - OTHER INFORMATION

SDS ID: 820324

NFPA Ratings

Health: 2 Fire: 1 Instability: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

Summary of Changes

Regulatory review and update.

Key / Legend

ACGIH - American Conference of Governmental Industrial Hygienists; ADR - European Road Transport; AU - Australia; BOD - Biochemical Oxygen Demand; C - Celsius; CA - Canada; CA/MA/MN/NJ/PA -California/Massachusetts/Minnesota/New Jersey/Pennsylvania*; CAS - Chemical Abstracts Service; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CFR - Code of Federal Regulations (US); CLP - Classification, Labelling, and Packaging; CN - China; CPR - Controlled Products Regulations; DFG - Deutsche Forschungsgemeinschaft; DOT - Department of Transportation; DSD - Dangerous Substance Directive; DSL - Domestic Substances List; EC - European Commission; EEC -European Economic Community; EIN - European Inventory of (Existing Commercial Chemical Substances); EINECS - European Inventory of Existing Commercial Chemical Substances; ENCS - Japan Existing and New Chemical Substance Inventory; EPA - Environmental Protection Agency; EU - European Union; F -Fahrenheit; F - Background (for Venezuela Biological Exposure Indices); IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; ICAO - International Civil Aviation Organization; IDL - Ingredient Disclosure List; IDLH - Immediately Dangerous to Life and Health; IMDG -International Maritime Dangerous Goods; ISHL - Japan Industrial Safety and Health Law; IUCLID -International Uniform Chemical Information Database; JP - Japan; Kow - Octanol/water partition coefficient; KR KECI Annex 1 - Korea Existing Chemicals Inventory (KECI) / Korea Existing Chemicals List (KECL); KR KECI Annex 2 - Korea Existing Chemicals Inventory (KECI) / Korea Existing Chemicals List (KECL), KR - Korea; LD50/LC50 - Lethal Dose/ Lethal Concentration; LEL - Lower Explosive Limit; LLV - Level Limit Value; LOLI - List Of LIstsTM - ChemADVISOR's Regulatory Database; MAK -Maximum Concentration Value in the Workplace; MEL - Maximum Exposure Limits; MX - Mexico; Ne-Non-specific; NFPA - National Fire Protection Agency; NIOSH - National Institute for Occupational Safety and Health; NJTSR - New Jersey Trade Secret Registry; Nq - Non-quantitative; NSL - Non-Domestic Substance List (Canada); NTP - National Toxicology Program; NZ - New Zealand; OSHA - Occupational Safety and Health Administration; PEL- Permissible Exposure Limit; PH - Philippines; RCRA - Resource Conservation and Recovery Act; REACH- Registration, Evaluation, Authorisation, and restriction of Chemicals; RID - European Rail Transport; SARA - Superfund Amendments and Reauthorization Act; Sc -Semi-quantitative; STEL - Short-term Exposure Limit; TCCA - Korea Toxic Chemicals Control Act; TDG -Transportation of Dangerous Goods; TLV - Threshold Limit Value; TSCA - Toxic Substances Control Act; TW - Taiwan; TWA - Time Weighted Average; UEL - Upper Explosive Limit; UN/NA - United Nations /North American; US - United States; VLE - Exposure Limit Value (Mexico); VN (Draft) - Vietnam (Draft); WHMIS - Workplace Hazardous Materials Information System (Canada).

Other Information

Disclaimer:

User assumes all risks incident to the use of this product. To the best of our knowledge, the information contained herein is accurate. However, Safety-Kleen assumes no liability whatsoever for the accuracy or completeness of the information contained herein. No representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose or of any other nature are made hereunder with respect to the information or the product to which the information refers. The data contained on this sheet apply to the product as supplied to the user.

Page 9 of 9 Rev. 08/19