SDS ID: 820328

Section 1 - PRODUCT AND COMPANY IDENTIFICATION

Material Name

Performance Plus Full Synthetic Heavy Duty Automatic Transmission Fluid

Product Code

Prefix 24

Synonyms

None known.

Product Use

Automatic Transmission Fluid. If this product is used in combination with other products, refer to the Safety Data Sheet for those products.

Restrictions on Use

None known.

FOR PRODUCT MANUFACTURED IN THE U.S.A.:

MANUFACTURERSUPPLIER (in Canada)Safety-Kleen Systems, Inc.Safety-Kleen Canada, Inc.

42 Longwater Drive 25 Regan Road

Norwell, MA 02061-9149 Brampton, Ontario, L7A 1B2

U.S.A. Canada

FOR PRODUCT MANUFACTURED IN CANADA:

MANUFACTURER SUPPLIER (in the U.S.A.)

Safety-Kleen Canada, Inc.

Safety-Kleen Systems, Inc.

25 Regan Road

42 Longwater Drive

Brampton, Ontario, L7A 1B2

Norwell, MA 02061-9149

Canada U.S.A.

Issue Date

October 28, 2019

Supersedes Issue Date

July 26, 2019

Original Issue Date

October 9, 2017

Section 2 - HAZARDS IDENTIFICATION

www.safety-kleen.comPhone: 1-800-669-5740
Emergency Phone #: 1-800-468-1760

Classification in accordance with Schedule 1 of Canada's Hazardous Products Regulations (HPR) (SOR/2015-17) and paragraph (d) of 29 CFR 1910.1200 in the United States

None needed according to classification criteria.

GHS Label Elements

Symbol(s)

None needed according to classification criteria.

Signal Word

None needed according to classification criteria.

Hazard Statement(s)

None needed according to classification criteria.

Precautionary Statement(s)

Prevention

None needed according to classification criteria.

Material Name: Performance Plus Full Synthetic Heavy Duty Automatic Transmission Fluid SDS ID: 820328

Response

None needed according to classification criteria.

Storage

None needed according to classification criteria.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

CAS	Component Name	Percent					
64742-54-7	Distillates, petroleum, hydrotreated heavy paraffinic	75-90					
64742-55-8	Distillates, petroleum, hydrotreated light paraffinic	40-50					
64742-65-0	Distillates, petroleum, solvent-dewaxed heavy paraffinic	10-25					
72623-86-0	3-86-0 Lubricating oils, petroleum, C15-30, hydrotreated neutral oil-based						
64742-56-9	Distillates, petroleum, solvent-dewaxed light paraffinic	1-5					
64742-53-6	Distillates, petroleum, hydrotreated light naphthenic	<3					
Proprietary	Alky acetamide	0.5-1					
Proprietary	Substituted hydrocarbyl sulfide	0.1-0.5					
Proprietary	Long chain hydroxyalkylamine	0.1-0.5					

Section 4 - FIRST AID MEASURES

Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get medical attention, if needed.

Skin

IF ON SKIN: Wash with plenty of soap and water. Get medical attention, if needed.

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention, if needed.

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.

Most Important Symptoms/Effects

Acute

No information on significant adverse effects.

Delayed

Repeated exposure may cause dryness or cracking.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically and supportively.

Page 2 of 11 Rev. 10/19

Material Name: Performance Plus Full Synthetic Heavy Duty Automatic Transmission Fluid

Section 5 - FIRE FIGHTING MEASURES

SDS ID: 820328

Extinguishing Media

Suitable Extinguishing Media

Use alcohol foam, carbon dioxide or dry chemical. Water or foam may cause frothing.

Unsuitable Extinguishing Media

Do not use high pressure streams.

Special Hazards Arising from the Chemical

Slight fire hazard.

Hazardous Combustion Products

Carbon monoxide, smoke

Advice for firefighters

Directly spraying water or foam onto hot burning product may cause frothing.

Fire Fighting Measures

Isolate immediate hazard area and keep unauthorized personnel out. Stop and contain spill/release if it can be done safely. If this cannot be done, allow fire to burn under control. Move undamaged containers from immediate hazard area if it can be done safely. Use water to cool fire-exposed containers, structures and to protect personnel. A positive-pressure, self-contained breathing apparatus (SCBA) and full-body protective equipment are required for fire emergencies.

Special Protective Equipment and Precautions for Firefighters

Wear full protective fire fighting gear including self contained breathing apparatus (SCBA) for protection against possible exposure.

Section 6 - ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Avoid breathing vapor. Avoid contact with skin, eyes and clothing. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Wear personal protective clothing and equipment, see Section 8.

Methods and Materials for Containment and Cleaning Up

Remove all ignition sources. Do not touch or walk through spilled product. Stop leak if you can do it without risk. Wear protective equipment and provide engineering controls as specified in SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION. Isolate hazard area. Keep unnecessary people away, isolate hazard area and deny entry. Do not touch or walk through spilled material. Stop leak if you can do it without risk. Contain spill away from surface water and sewers. Contain spill as a liquid for possible recovery, or sorb with compatible sorbent material and shovel with a clean, spark proof tool into a sealable container for disposal. Additionally, for large spills: Dike far ahead of liquid spill for collection and later disposal. There may be specific regulatory reporting requirements associated with spills, leaks, or releases of this product. Also see SECTION 15: REGULATORY INFORMATION.

Section 7 - HANDLING AND STORAGE

Precautions for Safe Handling

Keep away from sparks or flame. Where flammable mixtures may be present, equipment safe for such locations should be used. Use clean tools. When transferring large volumes of product, metal containers, including trucks and tank cars, should be grounded and bonded. These products have a low vapor pressure and are not expected to present an inhalation hazard under normal temperatures and pressures. However, when aerosolizing, misting, or heating these products, do not breathe vapor or mist. Use in a well ventilated area. Avoid contact with: Skin, eyes, clothing, shoes.

Page 3 of 11 Rev. 10/19

Material Name: Performance Plus Full Synthetic Heavy Duty Automatic Transmission Fluid SDS ID: 820328

Conditions for Safe Storage, Including any Incompatibilities

Keep container tightly closed when not in use and during transport. Store in a cool, dry, place. Do not pressurize, cut, weld, braze, solder, drill, or grind containers. Keep containers away from flame, sparks, static electricity, or other sources of ignition.

Incompatible Materials

Strong oxidizing agents.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Component Exposure Limits

Canada, ACGIH, OSHA, and NIOSH have not developed exposure limits for any of this product's components.

ACGIH - Threshold Limit Values - Biological Exposure Indices (BEI)

There are no biological limit values for any of this product's components.

Engineering Controls

Provide general ventilation. Where adequate general ventilation is unavailable, use process enclosures, local exhaust ventilation, or other engineering controls

Individual Protection Measures, such as Personal Protective Equipment

Eye/face protection

Wear safety glasses. Additional protection like goggles, face shields, or respirators may be needed dependent upon anticipated use and concentrations of mists or vapors. Eye wash fountain and emergency showers are recommended. Contact lens use is not recommended.

Respiratory Protection

A respiratory protection program which meets USA's OSHA General Industry Standard 29 CFR 1910.134 or Canada's CSA Standard Z94.4-M1982 requirements must be followed whenever workplace conditions warrant a respirator's use. Consult a qualified Industrial Hygienist or Safety Professional for respirator selection guidance.

Glove Recommendations

Where skin contact is likely, wear chemical impervious protective gloves; use of natural rubber or equivalent gloves is not recommended. When products are heated and skin contact is likely, wear heat-resistant gloves, boots, and other protective clothing. To avoid prolonged or repeated contact where spills and splashes are likely, wear appropriate chemical-resistant faceshield, boots, apron, coveralls, long sleeve shirts, or other protective clothing.

Protective Materials

Personal protective equipment should be selected based upon the conditions under which this material is used. A hazard assessment of the work area for PPE requirements should be conducted by a qualified professional pursuant to regulatory requirements. The following PPE should be considered the minimum required: Safety glasses, gloves, lab coat or apron.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Red liquid	Physical State	Not available
Odor	Hydrocarbon.	Color	Red
Odor Threshold	Not available	рН	Not available
Melting Point	Not available	Boiling Point	Not available.
Boiling Point Range	Not available	Freezing point	Not available
Evaporation Rate	Not available	Flammability (solid, gas)	Not available
Autoignition Temperature	Not available	Flash Point	190 °C (374 °F)

Page 4 of 11 Rev. 10/19

Material Name: Performance Plus Full Synthetic Heavy Duty Automatic Transmission Fluid SDS ID: 820328

Lower Explosive Limit	Not available	Decomposition temperature	Not available
Upper Explosive Limit	Not available	Vapor Pressure	Not available
Vapor Density (air=1)	Not available	Specific Gravity (water=1)	Not available
Water Solubility	0-1 % (Negligible)	Partition coefficient: n-octanol/water	Not available
Viscosity	32.01 cSt 40 °C	Kinematic viscosity	Not available
Solubility (Other)	Not available	Density	0.85
VOC	0	Molecular Weight	Not available

Section 10 - STABILITY AND REACTIVITY

Reactivity

No reactivity hazard is expected.

Chemical Stability

Stable under normal temperatures and pressure.

Possibility of Hazardous Reactions

Will not occur.

Conditions to Avoid

Avoid flames, sparks and other sources of ignition.

Incompatible Materials

Strong oxidizing agents.

Hazardous decomposition products

Carbon monoxide, smoke.

Section 11 - TOXICOLOGICAL INFORMATION

Information on Likely Routes of Exposure

Inhalation

No information on significant adverse effects.

Skin Contact

No information on significant adverse effects.

Eye Contact

No information on significant adverse effects.

Ingestion

No information on significant adverse effects.

Acute and Chronic Toxicity

Component Analysis - LD50/LC50

The components of this material have been reviewed in various sources and the following selected endpoints are published:

Distillates, petroleum, hydrotreated heavy paraffinic (64742-54-7)

Oral LD50 Rat >15 g/kg (no deaths occurred); Dermal LD50 Rabbit >5000 mg/kg (no deaths occurred)

Distillates, petroleum, hydrotreated light paraffinic (64742-55-8)

Inhalation LC50 Rat 3900 mg/m3 4 h

Distillates, petroleum, solvent-dewaxed heavy paraffinic (64742-65-0)

Oral LD50 Rat >15000 mg/kg (no deaths occurred); Dermal LD50 Rabbit >5000 mg/kg (no deaths occurred) Inhalation LC50 Rat >2400 mg/m3 4 h (no deaths occurred)

Page 5 of 11 Rev. 10/19

Material Name: Performance Plus Full Synthetic Heavy Duty Automatic Transmission Fluid SDS ID: 820328

Lubricating oils, petroleum, C15-30, hydrotreated neutral oil-based (72623-86-0)

Oral LD50 Rat >5000 mg/kg; Dermal LD50 Rabbit >2000 mg/kg; Inhalation LC50 Rat 2.18 mg/L 4 h

Distillates, petroleum, solvent-dewaxed light paraffinic (64742-56-9)

Oral LD50 Rat >5000 mg/kg (no deaths occurred); Dermal LD50 Rabbit >5000 mg/kg

Inhalation LC50 Rat >5399 mg/m3 4 h (no deaths occurred)

Distillates, petroleum, hydrotreated light naphthenic (64742-53-6)

Oral LD50 Rat >5000 mg/kg (no deaths occurred); Dermal LD50 Rabbit >2000 mg/kg (no deaths occurred)

Inhalation LC50 Rat 2180 mg/m3 4 h

Product Toxicity Data

Acute Toxicity Estimate

Dermal	> 2000 mg/kg
Oral	> 2000 mg/kg

Immediate Effects

No information on significant adverse effects.

Delayed Effects

No information on significant adverse effects.

Irritation/Corrosivity Data

May be slightly irritating to the skin.

Respiratory Sensitization

No information available for the product.

Dermal Sensitization

No information on significant adverse effects.

Component Carcinogenicity

None of this product's components are listed by ACGIH, IARC, NTP, DFG or OSHA.

It is not considered a carcinogen.

Germ Cell Mutagenicity

No information available for the product.

Tumorigenic Data

No information available for the product.

Reproductive Toxicity

No information available for the product.

Specific Target Organ Toxicity - Single Exposure

No target organs identified.

Specific Target Organ Toxicity - Repeated Exposure

No target organs identified.

Aspiration hazard

No information on significant adverse effects.

Medical Conditions Aggravated by Exposure

No data available.

Section 12 - ECOLOGICAL INFORMATION

Component Analysis - Aquatic Toxicity

Distillates, petroleum, hydrotreated heavy paraffinic	64742-54-7
Fish:	LC50 96 h Oncorhynchus mykiss >5000 mg/L

Page 6 of 11 Rev. 10/19

Material Name: Performance Plus Full Synthetic Heavy Duty Automatic Transmission Fluid SDS ID: 820328

Invertebrate:	EC50 48 h Daphnia magna >1000 mg/L IUCLID
Distillates, petroleum, hydrotreated light paraffinic	64742-55-8
Fish:	LC50 96 h Oncorhynchus mykiss >5000 mg/L
Invertebrate:	EC50 48 h Daphnia magna >1000 mg/L IUCLID
Distillates, petroleum, solvent-dewaxed heavy paraffinic	64742-65-0
Fish:	LC50 96 h Oncorhynchus mykiss >5000 mg/L
Invertebrate:	EC50 48 h Daphnia magna >1000 mg/L IUCLID
Lubricating oils, petroleum, C15-30, hydrotreated neutral oil-based	72623-86-0
Fish:	LC50 96 h Oncorhynchus mykiss >5000 mg/L
Invertebrate:	EC50 48 h Daphnia magna >1000 mg/L IUCLID
Distillates, petroleum, solvent-dewaxed light paraffinic	64742-56-9
Fish:	LC50 96 h Oncorhynchus mykiss >5000 mg/L
Invertebrate:	EC50 48 h Daphnia magna >1000 mg/L IUCLID
Distillates, petroleum, hydrotreated light naphthenic	64742-53-6
Fish:	LC50 96 h Oncorhynchus mykiss >5000 mg/L
Invertebrate:	EC50 48 h Daphnia magna >1000 mg/L IUCLID

Persistence and Degradability

No information for product is available.

Bioaccumulative Potential

No information available for the product.

Mobility

Expected to have low mobility in soil.

Other Toxicity

No information available for the product.

Page 7 of 11 Rev. 10/19

Material Name: Performance Plus Full Synthetic Heavy Duty Automatic Transmission Fluid

Section 13 - DISPOSAL CONSIDERATIONS

Disposal Methods

Dispose of contents/container in accordance with local/regional/national/international regulations. Regulations may also apply to empty containers. The responsibility for proper waste disposal lies with the owner of the waste. Contact Kleen Performance Products regarding proper recycling or disposal.

SDS ID: 820328

Section 14 - TRANSPORT INFORMATION

US DOT Information: Not regulated for transportation. IATA Information: Not regulated for transportation. IMDG Information: Not regulated for transportation. TDG Information: Not regulated for transportation.

International Bulk Chemical Code

This material does not contain any chemicals required by the IBC Code to be identified as dangerous chemicals in bulk.

Section 15 - REGULATORY INFORMATION

U.S. Federal Regulations

None of this product's components are listed under SARA Sections 302/304 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), CERCLA (40 CFR 302.4), TSCA 12(b), or require an OSHA process safety plan.

SARA Section 311/312 (40 CFR 370 Subparts B and C) reporting categories

No hazard categories applicable.

U.S. State Regulations

The following components appear on one or more of the following state hazardous substances lists:

Component	CAS	CA	MA	MN	NJ	PA
Distillates, petroleum, hydrotreated light paraffinic	64742-55-8	No	Yes	No	No	No
Distillates, petroleum, solvent-dewaxed light paraffinic	64742-56-9	No	Yes	No	No	No
Distillates, petroleum, hydrotreated light naphthenic	64742-53-6	No	Yes	No	No	No

California Safe Drinking Water and Toxic Enforcement Act (Proposition 65)

Not listed under California Proposition 65.

Canada Regulations

CEPA - Priority Substances List

None of this product's components are on the list.

Ozone Depleting Substances

None of this product's components are on the list.

Council of Ministers of the Environment - Soil Quality Guidelines

None of this product's components are on the list.

Council of Ministers of the Environment - Water Quality Guidelines

None of this product's components are on the list.

Page 8 of 11 Rev. 10/19

Material Name: Performance Plus Full Synthetic Heavy Duty Automatic Transmission Fluid SDS ID: 820328

Component Analysis - Inventory

Distillates, petroleum, hydrotreated heavy paraffinic (64742-54-7)

DISHII	ares, pe	ti vicu	1111, 11	yuı	υu	<u> </u>	u neavy para	111111C (04/-	14-34-1		
US	CA	AU	CN	1]	EU	J	JP - ENCS	JP - ISHL		KR KECI - Annex 1	KR KECI - Annex 2
Yes	DSL	Yes	Yes	s l	EIN	N	Yes	Yes		Yes	No
KR -	REAC:	REACH CCA MX NZ PH TH-TECI TW				TW	VN (Draft)	·			
No				Yes	S	Yes	Yes	No	Yes	Yes	
Distilla	ates, pe	troleu	m, h	ydr	oti	reate	d light paraf	finic (64742	2-55-8)		
US	CA	AU	CN	1]	EU	ſ	JP - ENCS	JP - ISHL		KR KECI - Annex 1	KR KECI - Annex 2
Yes	DSL	Yes	Yes	s 1	ΕIN	N	Yes	Yes		Yes	No
KR -	REAC	H CCA	A	MX		NZ	РН	TH-TECI	TW	VN (Draft)	
No				No		Yes	Yes	No	Yes	Yes	
Distilla	ates, pe	troleu	m, s	olve	ent	-dew	axed heavy p	oaraffinic (6	4742-	65-0)	
US	CA	AU	CN	1]	EU	Ţ	JP - ENCS	JP - ISHL		KR KECI - Annex 1	KR KECI - Annex 2
Yes	DSL	Yes	Yes	s l	EIN	N	No	No		Yes	No
KR -	REAC:	Н ССА	A	ΜX		NZ	РН	TH-TECI	TW	VN (Draft)	·
No				Yes Yes		Yes	Yes	No	Yes	Yes	
Lubric	cating o	oils, pe	trole	eum	ı, C	C 15-3	0, hydrotrea	ted neutral	oil-ba	sed (72623-86-0)	
US	CA	AU	CN	1]	EU	Ţ	JP - ENCS	JP - ISHL		KR KECI - Annex 1	KR KECI - Annex 2
Yes	DSL	Yes	Yes	s l	EIN	N	Yes	Yes		Yes	No
KR -	REAC	Н ССА	A	ΜX		NZ	PH	TH-TECI	TW	VN (Draft)	
No		Yes Yes Yes No Yes		Yes	Yes						
Distillates, petroleum, solvent-dew				-dew	axed light pa	raffinic (64	742-50	6-9)			
US	CA	AU	CN]	EU	Ţ	JP - ENCS	JP - ISHL		KR KECI - Annex 1	KR KECI - Annex 2
Yes	Yes DSL Yes Yes EIN No No				No		Yes	No			
KR -	R - REACH CCA MX NZ PH TH-TECI TW					PH	VN (Draft)	·			
No				No		Yes	Yes	No	Yes	Yes	
											•

Page 9 of 11 Rev. 10/19

Material Name: Performance Plus Full Synthetic Heavy Duty Automatic Transmission Fluid SDS ID: 820328

Distillates,	petroleum,	hydrotreated	light nar	ohthenic ((64742-53-6))

US	CA	AU	CN	N E	U	JP - ENCS	JP - ISHL		KR KECI - Annex 1	KR KECI - Annex 2
Yes	DSL	Yes	Ye	es E	IN	No	No		Yes	No
KR -	REAC:	Н ССА	١	MX	NZ	РН	TH-TECI	TW	VN (Draft)	·
No				No	Yes	Yes	No	Yes	Yes	

Alky acetamide (Proprietary)

US	CA	AU	CN	Е	U	JP - ENCS	JP - ISHL		KR KECI - Annex 1	KR KECI - Annex 2
No	No	No	No	N	o	No	No		No	No
KR -	REAC	СН СС	A	MX	NZ	РН	TH-TECI	TW	VN (Draft)	
No	No			No	No	No	No	No	No	

Substituted hydrocarbyl sulfide (Proprietary)

US	CA	AU	C	N	EU	JP - ENCS	JP - ISHL		KR KECI - Annex 1	KR KECI - Annex 2
No	No	No	N	o	No	No	No		No	No
KR -	REA	СН СС	Α	МΣ	NZ	PH	TH-TECI	TW	VN (Draft)	
No	No No No No		No							

Long chain hydroxyalkylamine (Proprietary)

US	CA	AU C		N E	U	JP - ENCS	JP - ISHL		KR KECI - Annex 1	KR KECI - Annex 2
No	No	o No No 1) N	Го	No	No		No	No
KR - REACH CCA				MX	NZ	РН	TH-TECI	TW	VN (Draft)	
No				No	No	No	No	No	No	

Section 16 - OTHER INFORMATION

NFPA Ratings

Health: 1 Fire: 1 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

Summary of Changes

Revised SDS to new formulation.

Key / Legend

ACGIH - American Conference of Governmental Industrial Hygienists; ADR - European Road Transport; AU - Australia; BOD - Biochemical Oxygen Demand; C - Celsius; CA - Canada; CA/MA/MN/NJ/PA - California/Massachusetts/Minnesota/New Jersey/Pennsylvania*; CAS - Chemical Abstracts Service; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CFR - Code of Federal Regulations (US); CLP - Classification, Labelling, and Packaging; CN - China; CPR - Controlled

Page 10 of 11 Rev. 10/19

Material Name: Performance Plus Full Synthetic Heavy Duty Automatic Transmission Fluid SDS ID: 820328

Products Regulations; DFG - Deutsche Forschungsgemeinschaft; DOT - Department of Transportation; DSD - Dangerous Substance Directive; DSL - Domestic Substances List; EC - European Commission; EEC -European Economic Community; EIN - European Inventory of (Existing Commercial Chemical Substances); EINECS - European Inventory of Existing Commercial Chemical Substances; ENCS - Japan Existing and New Chemical Substance Inventory: EPA - Environmental Protection Agency: EU - European Union: F -Fahrenheit; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; ICAO - International Civil Aviation Organization; IDL - Ingredient Disclosure List; IDLH -Immediately Dangerous to Life and Health; IMDG - International Maritime Dangerous Goods; ISHL - Japan Industrial Safety and Health Law; IUCLID - International Uniform Chemical Information Database; JP -Japan; Kow - Octanol/water partition coefficient; KR KECI Annex 1 - Korea Existing Chemicals Inventory (KECI) / Korea Existing Chemicals List (KECL); KR KECI Annex 2 - Korea Existing Chemicals Inventory (KECI) / Korea Existing Chemicals List (KECL), KR - Korea; LD50/LC50 - Lethal Dose/ Lethal Concentration; LEL - Lower Explosive Limit; LLV - Level Limit Value; LOLI - List Of LIstsTM -ChemADVISOR's Regulatory Database; MAK - Maximum Concentration Value in the Workplace; MEL -Maximum Exposure Limits; MX - Mexico; NDSL - Non-Domestic Substance List (Canada); NFPA -National Fire Protection Agency; NIOSH - National Institute for Occupational Safety and Health; NJTSR -New Jersey Trade Secret Registry; NTP - National Toxicology Program; NZ - New Zealand; OSHA -Occupational Safety and Health Administration; PEL- Permissible Exposure Limit; PH - Philippines; RCRA - Resource Conservation and Recovery Act; REACH- Registration, Evaluation, Authorisation, and restriction of Chemicals; RID - European Rail Transport; SARA - Superfund Amendments and Reauthorization Act; STEL - Short-term Exposure Limit; TCCA - Korea Toxic Chemicals Control Act; TDG - Transportation of Dangerous Goods; TLV - Threshold Limit Value; TSCA - Toxic Substances Control Act; TW - Taiwan; TWA - Time Weighted Average; UEL - Upper Explosive Limit; UN/NA -United Nations /North American; US - United States; VLE - Exposure Limit Value (Mexico); VN NCI (Draft) - Vietnam National Chemicals Inventory (NCI) (Draft); WHMIS - Workplace Hazardous Materials Information System (Canada).

Other Information

Disclaimer:

User assumes all risks incident to the use of this product. To the best of our knowledge, the information contained herein is accurate. However, Kleen Performance Products assumes no liability whatsoever for the accuracy or completeness of the information contained herein. No representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose or of any other nature are made hereunder with respect to the information or the product to which the information refers. The data contained on this sheet apply to the product as supplied to the user.

Page 11 of 11 Rev. 10/19