

## Performance Plus Transmission Fluid TO-4 50W

Safety Data Sheet SDS ID: 820329

#### Section 1 - PRODUCT AND COMPANY IDENTIFICATION

**Material Name** 

Performance Plus Transmission Fluid TO-4 50W

**Product Code** 

Prefix 24

**Synonyms** 

Not Available.

**Recommended Use** 

Lubricating oils. If this product is used in combination with other products, refer to the Safety Data Sheet for those products.

**Restrictions on Use** 

None known.

FOR PRODUCT MANUFACTURED IN THE U.S.A.:

MANUFACTURERSUPPLIER (in Canada)Safety-Kleen Systems, Inc.Safety-Kleen Canada, Inc.

42 Longwater Drive 25 Regan Road

Norwell, MA 02061-9149 Brampton, Ontario, Canada L7A 1B2

U.S.A.

FOR PRODUCT MANUFACTURED IN CANADA:

MANUFACTURER SUPPLIER (in the U.S.A.)

Kleen Performance Products

Safety-Kleen Systems, Inc.

25 Regan Road

42 Longwater Drive

Brampton, Ontario, Canada L7A 1B2 Norwell, MA 02061-9149

U.S.A.

www.safety-kleen.com Phone: 1-800-669-5740

Emergency Phone #: 1-800-468-1760

**Issue Date** 

December 18, 2018

**Supersedes Issue Date** 

October 9, 2017

**Original Issue Date** 

October 9, 2017

#### **Section 2 - HAZARDS IDENTIFICATION**

Classification in accordance with Schedule 1 of Canada's Hazardous Products Regulations (HPR) (SOR/2015-17) and paragraph (d) of 29 CFR 1910.1200 in the United States

None needed according to classification criteria

**GHS Label Elements** 

Symbol(s)

None needed according to classification criteria

Signal Word

None needed according to classification criteria

**Hazard Statement(s)** 

None needed according to classification criteria.

SDS ID: 820329

## **Performance Plus Transmission Fluid TO-4 50W**

#### **Precautionary Statement(s)**

#### **Prevention**

None needed according to classification criteria.

#### Response

None needed according to classification criteria.

#### Storage

None needed according to classification criteria.

#### **Disposal**

Dispose of in accordance with all applicable federal, state and local regulations.

#### Other Hazards

Repeated exposure may cause skin dryness or cracking.

## **Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS**

CAS	Component Name	Percent
Mixture	Base oil	45-65
64742-65-0	Petroleum distillates solvent-dewaxed heavy paraffinic	30-45
Mixture	Mineral Oil	3-5
Proprietary	Calcium long-chain alkylphenate sulfide	1.5-3

## **Section 4 - FIRST AID MEASURES**

#### Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention, if needed.

#### Skin

IF ON SKIN: Wash with plenty of soap and water. Get medical attention, if needed.

#### Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention, if needed.

#### Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting. Rinse mouth.

#### **Most Important Symptoms/Effects**

#### Acute

No information on significant adverse effects.

#### Delayed

Repeated exposure may cause skin dryness or cracking.

## Indication of any immediate medical attention and special treatment needed

Treat symptomatically and supportively.

## **Section 5 - FIRE FIGHTING MEASURES**

#### **Extinguishing Media**

#### Suitable Extinguishing Media

Carbon dioxide, regular foam, dry chemical, water spray, water fog, Water or foam may cause frothing.

Page 2 of 8 Rev. 12/18

## **Performance Plus Transmission Fluid TO-4 50W**

#### **Unsuitable Extinguishing Media**

Do not use high-pressure water streams.

#### **Special Hazards Arising from the Chemical**

Negligible fire hazard. Avoid friction, static electricity and sparks.

#### **Hazardous Combustion Products**

Burning may produce oxides of C, Zn, Ca, P and S. Additional byproducts include hydrogen sulfide, alkyl mercaptan, and other sulfides.

SDS ID: 820329

#### **Fire Fighting Measures**

Move container from fire area if it can be done without risk. Cool containers with water spray until well after the fire is out. Stay away from the ends of tanks. Fight fire from maximum distance or use unmanned hose holders or monitor nozzles. Keep unnecessary people away, isolate hazard area, and deny entry.

#### Special Protective Equipment and Precautions for Firefighters

A positive-pressure, self-contained breathing apparatus (SCBA) and full-body protective equipment are required for fire emergencies.

#### **Section 6 - ACCIDENTAL RELEASE MEASURES**

#### Personal Precautions, Protective Equipment and Emergency Procedures

Wear personal protective clothing and equipment, see Section 8. Avoid release to the environment.

#### Methods and Materials for Containment and Cleaning Up

Remove all ignition sources. Do not touch or walk through spilled product. Stop leak if you can do it without risk. Wear protective equipment and provide engineering controls as specified in SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Ventilate area and avoid breathing vapor or mist. Contain spill away from surface water and sewers. Contain spill as a liquid for possible recovery, or sorb with compatible sorbent material and shovel with a clean, spark proof tool into a sealable container for disposal. Additionally, for large spills: Dike far ahead of liquid spill for collection and later disposal. There may be specific federal regulatory reporting requirements associated with spills, leaks, or releases of this product. Also see SECTION 15: REGULATORY INFORMATION.

## **Section 7 - HANDLING AND STORAGE**

#### **Precautions for Safe Handling**

Keep away from heat, sparks and naked flames. Where flammable mixtures may be present, equipment safe for such locations should be used. Use clean tools and explosion-proof equipment. When transferring large volumes of product, metal containers, including trucks and tank cars, should be grounded and bonded. This product has a low vapor pressure and is not expected to present an inhalation hazard under normal temperatures and pressures. However, when aerosolizing, misting, or heating this product, do not breathe vapor or mist. Use in a well ventilated area. Avoid contact with eyes Skin clothing shoes.

#### Conditions for Safe Storage, Including any Incompatibilities

None needed according to classification criteria.

Additional information: Storage. Keep container tightly closed when not in use and during transport. Store containers in a cool, dry place. Do not pressurize, cut, weld, braze, solder, drill, or grind containers. Keep containers away from flame, sparks, static electricity, or other sources of ignition. Empty product containers may retain product residue and can be dangerous.

#### **Incompatible Materials**

Strong oxidizing materials.

Page 3 of 8 Rev. 12/18

## **Performance Plus Transmission Fluid TO-4 50W**

## Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

SDS ID: 820329

#### **Component Exposure Limits**

Canada, ACGIH, OSHA, and NIOSH have not developed exposure limits for any of this product's components.

#### ACGIH - Threshold Limit Values - Biological Exposure Indices (BEI)

There are no biological limit values for any of this product's components.

#### **Engineering Controls**

Provide general ventilation. Where adequate general ventilation is unavailable, use process enclosures, local exhaust ventilation, or other engineering controls.

# Individual Protection Measures, such as Personal Protective Equipment Eye/face protection

Wear safety glasses. Additional protection like goggles, face shields, or respirators may be needed dependent upon anticipated use and concentrations of vapors or mists. Eye wash fountain and emergency showers are recommended. Contact lens use is not recommended.

#### **Respiratory Protection**

A respiratory protection program which meets USA's OSHA General Industry Standard 29 CFR 1910.134 or Canada's CSA Standard Z94.4-M1982 requirements must be followed whenever workplace conditions warrant a respirator's use. Consult a qualified Industrial Hygienist or Safety Professional for respirator selection guidance..

#### **Glove Recommendations**

Where skin contact is likely, wear gloves impervious to product; use of natural rubber (latex) or equivalent gloves is not recommended. To avoid prolonged or repeated contact where spills and splashes are likely, wear appropriate chemical-resistant face shield, boots, apron, whole body suits or other protective clothing. When product is heated and skin contact is likely, wear heat-resistant gloves, boots, and other protective clothing.

#### **Protective Materials**

Personal protective equipment should be selected based upon the conditions under which this material is used. A hazard assessment of the work area for PPE requirements should be conducted by a qualified professional pursuant to regulatory requirements. The following PPE should be considered the minimum required: Safety glasses, Gloves, and Lab coat or apron.

#### **Section 9 - PHYSICAL AND CHEMICAL PROPERTIES**

Appearance	Liquid.	Physical State	Liquid
Odor	Petroleum	Color	Amber.
Odor Threshold	Not available	pH	Not available
<b>Melting Point</b>	Not available	<b>Boiling Point</b>	129.5 °C (265 °F Minimum )
<b>Boiling Point Range</b>	Not available	Freezing point	Not available
<b>Evaporation Rate</b>	Not available	Flammability (solid, gas)	Not available
Autoignition Temperature	Not available	Flash Point	261 °C (501.8 °F)
Lower Explosive Limit	Not available	Decomposition temperature	Not available

Page 4 of 8 Rev. 12/18

SDS ID: 820329

## **Performance Plus Transmission Fluid TO-4 50W**

<b>Upper Explosive Limit</b>	Not available	Vapor Pressure	<0.1 mmHg @ 68°F °C (20 °C )
Vapor Density (air=1)	Not available	Specific Gravity (water=1)	0.8894 (Approximate Water = 1)
Water Solubility	(Insoluble )	Partition coefficient: n- octanol/water	Not available
Viscosity	196.96 cSt at 40°C, 18.56 cSt at 100°C	Solubility (Other)	Not available
Density	7.411 lb/gal	Physical Form	Liquid.
Pour Point	-18.0 °C (0.40°F)	Molecular Weight	Not available

#### **Section 10 - STABILITY AND REACTIVITY**

#### Reactivity

No reactivity hazard is expected.

#### **Chemical Stability**

Stable under normal temperatures and pressures.

#### **Possibility of Hazardous Reactions**

Will not polymerize.

#### **Conditions to Avoid**

Avoid heat, flames, sparks and other sources of ignition

#### **Incompatible Materials**

Avoid oxidizing agents.

#### Hazardous decomposition products

None under normal temperatures and pressures.

#### **Section 11 - TOXICOLOGICAL INFORMATION**

#### **Information on Likely Routes of Exposure**

#### Inhalation

No information on significant adverse effects.

#### **Skin Contact**

Repeated exposure may cause skin dryness or cracking.

#### **Eve Contact**

No information on significant adverse effects.

#### **Ingestion**

No information on significant adverse effects.

#### **Acute and Chronic Toxicity**

#### Component Analysis - LD50/LC50

The components of this material have been reviewed in various sources and the following selected endpoints are published:

#### Distillates, petroleum, solvent-dewaxed heavy paraffinic (64742-65-0)

Oral LD50 Rat >15000 mg/kg (no deaths occurred); Dermal LD50 Rabbit >5000 mg/kg (no deaths occurred) Inhalation LC50 Rat >2400 mg/m3 4 h (no deaths occurred)

#### **Product Toxicity Data**

#### **Acute Toxicity Estimate**

Not available

Page 5 of 8 Rev. 12/18

SDS ID: 820329

## **Performance Plus Transmission Fluid TO-4 50W**

#### **Immediate Effects**

No information on significant adverse effects.

#### **Delayed Effects**

Repeated exposure may cause skin dryness or cracking.

#### Irritation/Corrosivity Data

May cause slight skin and respiratory irritation.

#### **Respiratory Sensitization**

No information available for the product.

#### **Dermal Sensitization**

No information available for the product.

#### **Component Carcinogenicity**

None of this product's components are listed by ACGIH, IARC, NTP, DFG or OSHA

#### **Germ Cell Mutagenicity**

No information available for the product.

#### **Tumorigenic Data**

No data available

#### **Reproductive Toxicity**

No information available for the product.

## **Specific Target Organ Toxicity - Single Exposure**

No information on significant adverse effects.

#### **Specific Target Organ Toxicity - Repeated Exposure**

No information on significant adverse effects.

#### **Aspiration hazard**

No information available for the product.

#### **Medical Conditions Aggravated by Exposure**

Individuals with pre-existing respiratory tract (nose, throat, and lungs), eye, and/or skin disorders may have increased susceptibility to the effects of exposure.

#### **Section 12 - ECOLOGICAL INFORMATION**

#### **Ecotoxicity**

Toxic to aquatic life.

#### **Component Analysis - Aquatic Toxicity**

Distillates, petroleum, solvent-dewaxed heavy paraffinic	64742-65-0
Fish:	LC50 96 h Oncorhynchus mykiss >5000 mg/L
Invertebrate:	EC50 48 h Daphnia magna >1000 mg/L IUCLID

## Persistence and Degradability

No information available for the product.

#### **Bioaccumulative Potential**

No information available for the product.

#### **Mobility**

No information available for the product.

#### **Other Toxicity**

No additional information is available.

Page 6 of 8 Rev. 12/18

## **Performance Plus Transmission Fluid TO-4 50W**

#### **Section 13 - DISPOSAL CONSIDERATIONS**

SDS ID: 820329

#### **Disposal Methods**

Dispose in accordance with federal, state, provincial, and local regulations. Regulations may also apply to empty containers. The responsibility for proper waste disposal lies with the owner of the waste. Contact Safety-Kleen regarding proper recycling or disposal.

#### **Section 14 - TRANSPORT INFORMATION**

**US DOT Information:** Not regulated for transport. **IATA Information:** Not regulated for transport. **IMDG Information:** Not regulated for transport. **TDG Information:** Not regulated for transport.

#### **International Bulk Chemical Code**

This material does not contain any chemicals required by the IBC Code to be identified as dangerous chemicals in bulk.

#### **Section 15 - REGULATORY INFORMATION**

#### U.S. Federal Regulations

None of this products components are listed under SARA Sections 302/304 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), CERCLA (40 CFR 302.4), TSCA 12(b), or require an OSHA process safety plan.

#### SARA Section 311/312 (40 CFR 370 Subparts B and C)

Acute Health: No Chronic Health: No Fire: No Pressure: No Reactivity: No

#### U.S. State Regulations

No components appear on any state hazardous substances lists:

#### Not listed under California Proposition 65

Canada Regulations

#### Canadian WHMIS Ingredient Disclosure List (IDL)

The components of this product are either not listed on the IDL or are present below the threshold limit listed on the IDL.

#### **Component Analysis - Inventory**

#### Distillates, petroleum, solvent-dewaxed heavy paraffinic (64742-65-0)

US	CA
Yes	DSL

## **Section 16 - OTHER INFORMATION**

## NFPA Ratings

Health: 1 Fire: 1 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

#### **Summary of Changes**

2018-12: Regulatory review and update.

#### Key / Legend

ACGIH - American Conference of Governmental Industrial Hygienists; BOD - Biochemical Oxygen Demand; C - Celsius; CA - Canada; CA/MA/MN/NJ/PA - California/Massachusetts/Minnesota/New Jersey/Pennsylvania\*; CAS - Chemical Abstracts Service; CFR - Code of Federal Regulations (US); CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CLP -

Page 7 of 8 Rev. 12/18

# Safety Data Sheet Performance Plus Transmission Fluid TO-4 50W

Classification, Labelling, and Packaging; CPR - Controlled Products Regulations; DOT - Department of Transportation; DSL - Domestic Substances List; EPA - Environmental Protection Agency; F - Fahrenheit; IDL - Ingredient Disclosure List; IDLH - Immediately Dangerous to Life and Health; IMDG - International Maritime Dangerous Goods; LEL - Lower Explosive Limit; LLV - Level Limit Value; LOLI - List Of LIsts<sup>TM</sup> - ChemADVISOR's Regulatory Database; MAK - Maximum Concentration Value in the Workplace; MEL - Maximum Exposure Limits; NDSL – Non-Domestic Substance List (Canada); NFPA - National Fire Protection Agency; NIOSH - National Institute for Occupational Safety and Health; NJTSR - New Jersey Trade Secret Registry; NTP - National Toxicology Program; OSHA - Occupational Safety and Health Administration; PEL- Permissible Exposure Limit; RCRA - Resource Conservation and Recovery Act; SARA - Superfund Amendments and Reauthorization Act; STEL - Short-term Exposure Limit; TDG - Transportation of Dangerous Goods; TLV - Threshold Limit Value; TSCA - Toxic Substances Control Act; TWA - Time Weighted Average; UEL - Upper Explosive Limit; UN/NA - United Nations /North American; US - United States; WHMIS - Workplace Hazardous Materials Information System (Canada).

SDS ID: 820329

## Other Information Disclaimer:

User assumes all risks incident to the use of this product. To the best of our knowledge, the information contained herein is accurate. However, Safety-Kleen assumes no liability whatsoever for the accuracy or completeness of the information contained herein. No representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose or of any other nature are made hereunder with respect to the information or the product to which the information refers. The data contained on this sheet apply to the product as supplied to the user.

Page 8 of 8 Rev. 12/18