

Section 1 - PRODUCT AND COMPANY IDENTIFICATION

Material Name Performance Plus NGEO 15W-40 NGP3 **Product Code** Prefix 22 Synonyms Natural Gas Engine Oil; Engine Oil **Product Use** Lubricating oil. If this product is used in combination with other products, refer to the Safety Data Sheet for those products. **Restrictions on Use** None known. FOR PRODUCT MANUFACTURED IN THE U.S.A.: MANUFACTURER **SUPPLIER (in Canada)** Safety-Kleen Systems, Inc. Safety-Kleen Canada, Inc. 42 Longwater Drive 25 Regan Road Norwell, MA 02061-9149 Brampton, Ontario, L7A 1B2 Canada U.S.A.

FOR PRODUCT MANUFACTURED IN CANADA:

MANUFACTURER Safety-Kleen Systems, Inc. 25 Regan Road Brampton, Ontario, L7A 1B2 Canada

SUPPLIER (in the U.S.A.)

Safety-Kleen Systems, Inc. 42 Longwater Drive Norwell, MA 02061-9149 U.S.A.

www.safety-kleen.com Phone: 1-800-669-5740 Emergency Phone #: 1-800-468-1760

Issue Date May 28, 2020 Supersedes Issue Date New Issue SDS Original Issue Date May 28, 2020

Section 2 - HAZARDS IDENTIFICATION

Classification in accordance with Schedule 1 of Canada's Hazardous Products Regulations (HPR) (SOR/2015-17) and paragraph (d) of 29 CFR 1910.1200 in the United States

None needed according to classification criteria.

GHS Label Elements

Symbol(s)

None needed according to classification criteria.

Signal Word

None needed according to classification criteria

Hazard Statement(s)

None needed according to classification criteria.

Precautionary Statement(s)

Prevention

None needed according to classification criteria.

Material Name: NGEO 15W-40 NGP3

Response

None needed according to classification criteria.

Storage

None needed according to classification criteria.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

CAS	Component Name	Percent
64742-58-1	Lubricating oils, petroleum, hydrotreated spent	77-79
64742-65-0	Distillates, petroleum, solvent-dewaxed heavy paraffinic	3-5
64742-54-7	Distillates, petroleum, hydrotreated heavy paraffinic	0.15 - 4
64742-55-8	Distillates, petroleum, hydrotreated light paraffinic	1.5-3
64742-70-7	Paraffin oils, petroleum, catalytic dewaxed heavy	0.15 - 1
113706-15-3	Phosphorodithioic acid, mixed O,O-bis(sec-butyl and isooctyl) esters, zinc salts	0.6-0.7

Section 4 - FIRST AID MEASURES

Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get medical attention, if needed.

Skin

IF ON SKIN: Wash with plenty of soap and water. Get medical attention, if needed.

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention, if needed.

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting. **Most Important Symptoms/Effects**

Acute

No information on significant adverse effects.

Delayed

No information on significant adverse effects.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically and supportively.

Section 5 - FIRE FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media

carbon dioxide, regular foam, dry chemical, water spray, water fog, Water or foam may cause frothing.

Unsuitable Extinguishing Media

Do not use high-pressure water streams.

Material Name: NGEO 15W-40 NGP3

Special Hazards Arising from the Chemical

Negligible fire hazard. Avoid static electricity and sparks.

Hazardous Combustion Products

Decomposition and combustion materials may be toxic. Burning may produce oxides of carbon and unidentified organic compounds.

Fire Fighting Measures

Move container from fire area if it can be done without risk. Cool containers with water spray until well after the fire is out.

Special Protective Equipment and Precautions for Firefighters

A positive-pressure, self-contained breathing apparatus (SCBA) and full-body protective equipment are required for fire emergencies.

Section 6 - ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Wear personal protective clothing and equipment, see Section 8. Avoid release to the environment.

Methods and Materials for Containment and Cleaning Up

Remove all ignition sources. Do not touch or walk through spilled product. Stop leak if you can do it without risk. Wear protective equipment and provide engineering controls as specified in SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Ventilate area and avoid breathing vapor or mist. Contain spill away from surface water and sewers. Contain spill as a liquid for possible recovery, or sorb with compatible sorbent material and shovel with a clean, spark proof tool into a sealable container for disposal. Additionally, for large spills: Dike far ahead of liquid spill for collection and later disposal.

Section 7 - HANDLING AND STORAGE

Precautions for Safe Handling

Keep away from heat, sparks and naked flames. Where flammable mixtures may be present, equipment safe for such locations should be used. Use clean tools and explosion-proof equipment. Use in a well ventilated area. Avoid contact with eyes Skin clothing shoes.

Conditions for Safe Storage, Including any Incompatibilities

None needed according to classification criteria.

Keep container tightly closed when not in use and during transport. Store containers in a cool, dry place. Do not pressurize, cut, weld, braze, solder, drill, or grind containers. Keep containers away from flame, sparks, static electricity, or other sources of ignition.

Incompatible Materials

Strong oxidizing materials.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Component Exposure Limits

Canada and ACGIH have not developed exposure limits for any of this product's components.

ACGIH - Threshold Limit Values - Biological Exposure Indices (BEI)

There are no biological limit values for any of this product's components.

Engineering Controls

Provide general ventilation. Where adequate general ventilation is unavailable, use process enclosures, local exhaust ventilation, or other engineering controls.

Material Name: NGEO 15W-40 NGP3

Individual Protection Measures, such as Personal Protective Equipment **Eye/face protection**

Wear safety glasses. Additional protection like goggles, face shields, or respirators may be needed dependent upon anticipated use and concentrations of mists or vapors. Eve wash fountain and emergency showers are recommended. Contact lens use is not recommended.

Respiratory Protection

A respiratory protection program which meets USA's OSHA General Industry Standard 29 CFR 1910.134 or Canada's CSA Standard Z94.4-M1982 requirements must be followed whenever workplace conditions warrant a respirator's use. Consult a qualified Industrial Hygienist or Safety Professional for respirator selection guidance.

Skin Protection/Glove Recommendations

Where skin contact is likely, wear gloves impervious to product; use of natural rubber (latex) or equivalent gloves is not recommended. To avoid prolonged or repeated contact where spills and splashes are likely, wear appropriate chemical-resistant face shield, boots, apron, whole body suits or other protective clothing.

Protective Materials

Personal protective equipment should be selected based upon the conditions under which this material is used. A hazard assessment of the work area for PPE requirements should be conducted by a qualified professional pursuant to regulatory requirements. The following PPE should be considered the minimum required: Safety glasses. Gloves. Lab coat or apron.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Amber liquid	Physical State	Liquid
Odor	Not available	Color	Amber
Odor Threshold	Not available	рН	Not available
Melting Point	Not available	Boiling Point	Not available
Boiling Point Range	Not available	Freezing point	Not available
Evaporation Rate	Not available	Flammability (solid, gas)	Not available
Autoignition Temperature	Not available	Flash Point	240 °C
Lower Explosive Limit	Not available	Decomposition temperature	Not available
Upper Explosive Limit	Not available	Vapor Pressure	Not available
Vapor Density (air=1)	Not available	Specific Gravity (water=1)	Not available
Water Solubility	Not available	Partition coefficient: n-octanol/water	Not available
Viscosity	113.7 cSt 40 °C	Kinematic viscosity	Not available
Solubility (Other)	Not available	Density	Not available
Physical Form	liquid	Molecular Weight	Not available
Volatile Organic Compoun	ds (As regulated)	Negligible as per U.S. EPA 40 CFR 51.	100(s)

Section 10 - STABILITY AND REACTIVITY

Reactivity

No reactivity hazard is expected.

Material Name: NGEO 15W-40 NGP3

Chemical Stability

Stable under normal temperatures and pressures.

Possibility of Hazardous Reactions

Will not polymerize.

Conditions to Avoid

Avoid flames, sparks and other sources of ignition

Incompatible Materials

Avoid oxidizing agents.

Hazardous decomposition products

None under normal temperatures and pressures. See also SECTION 5: HAZARDOUS COMBUSTION PRODUCTS.

Section 11 - TOXICOLOGICAL INFORMATION

Information on Likely Routes of Exposure

Inhalation

No information on significant adverse effects.

Skin Contact

May cause skin irritation.

Eve Contact

May cause eye irritation.

Ingestion

May cause gastrointestinal irritation, nausea, vomiting, diarrhea.

Acute and Chronic Toxicity

Component Analysis - LD50/LC50

The components of this material have been reviewed in various sources and the following selected endpoints are published:

Lubricating oils, petroleum, hydrotreated spent (64742-58-1)

Oral LD50 Rat >2000 mg/kg; Dermal LD50 Rabbit >4480 mg/kg

Distillates, petroleum, solvent-dewaxed heavy paraffinic (64742-65-0)

Oral LD50 Rat >15000 mg/kg (no deaths occurred) Dermal LD50 Rabbit >5000 mg/kg (no deaths occurred) Inhalation LC50 Rat >2400 mg/m3 4 h (no deaths occurred)

Distillates, petroleum, hydrotreated heavy paraffinic (64742-54-7)

Oral LD50 Rat >15 g/kg (no deaths occurred); Dermal LD50 Rabbit >5000 mg/kg (no deaths occurred)

Distillates, petroleum, hydrotreated light paraffinic (64742-55-8)

Inhalation LC50 Rat 3900 mg/m3 4 h

Paraffin oils, petroleum, catalytic dewaxed heavy (64742-70-7)

Oral LD50 Rat >15000 mg/kg; Dermal LD50 Rabbit >5000 mg/kg

Product Toxicity Data

Acute Toxicity Estimate

Dermal	> 2000 mg/kg				
Oral	> 2000 mg/kg				

Immediate Effects

No information on significant adverse effects.

Delayed Effects

No information on significant adverse effects.

Irritation/Corrosivity Data

May cause eye irritation. May cause skin irritation.

Respiratory Sensitization

No information available for the product.

Material Name: NGEO 15W-40 NGP3

Dermal Sensitization
No information available for the product.
Component Carcinogenicity
None of this product's components are listed by ACGIH, IARC, NTP, DFG or OSHA.
Germ Cell Mutagenicity
No information available for the product.
Tumorigenic Data
No data available
Reproductive Toxicity
No information available for the product.
Specific Target Organ Toxicity - Single Exposure
No target organs identified.
Specific Target Organ Toxicity - Repeated Exposure No target organs identified.
Aspiration hazard No information on significant adverse effects.
Medical Conditions Aggravated by Exposure
Individuals with pre-existing respiratory tract (nose, throat, and lungs), eye, and/or skin disorders may have
increased susceptibility to the effects of exposure.
Additional Data
No additional information is available.

Section 12 - ECOLOGICAL INFORMATION

Component Analysis - Aquatic Toxicity

Distillates, petroleum, solvent-dewaxed heavy paraffinic	64742-65-0			
Fish:	LC50 96 h Oncorhynchus mykiss >5000 mg/L			
Invertebrate:	EC50 48 h Daphnia magna >1000 mg/L IUCLID			
Distillates, petroleum, hydrotreated heavy paraffinic	64742-54-7			
Fish:	LC50 96 h Oncorhynchus mykiss >5000 mg/L			
Invertebrate:	EC50 48 h Daphnia magna >1000 mg/L IUCLID			
Distillates, petroleum, hydrotreated light paraffinic	64742-55-8			
Fish:	LC50 96 h Oncorhynchus mykiss >5000 mg/L			
Invertebrate:	EC50 48 h Daphnia magna >1000 mg/L IUCLID			

Persistence and Degradability

No information available for the product.

Bioaccumulative Potential

No information available for the product.

Mobility

No information available for the product.

Section 13 - DISPOSAL CONSIDERATIONS

Disposal Methods

Dispose in accordance with federal, state, provincial, and local regulations. Regulations may also apply to empty containers. The responsibility for proper waste disposal lies with the owner of the waste. Contact Safety-Kleen regarding proper recycling or disposal.

Component Waste Numbers

The U.S. EPA has not published waste numbers for this product's components.

Section 14 - TRANSPORT INFORMATION

US DOT Information: Not regulated for transport.

IATA Information: Not regulated for transport.

IMDG Information: Not regulated for transport.

TDG Information: Not regulated for transport.

International Bulk Chemical Code

This material does not contain any chemicals required by the IBC Code to be identified as dangerous chemicals in bulk.

Section 15 - REGULATORY INFORMATION

Canada Regulations

CEPA - Priority Substances List

None of this product's components are on the list.

Ozone Depleting Substances

None of this product's components are on the list.

Council of Ministers of the Environment - Soil Quality Guidelines

None of this product's components are on the list.

Council of Ministers of the Environment - Water Quality Guidelines

None of this product's components are on the list.

U.S. Federal Regulations

None of this product's components are listed under SARA Sections 302/304 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), CERCLA (40 CFR 302.4), TSCA 12(b), or require an OSHA process safety plan.

SARA Section 311/312 (40 CFR 370 Subparts B and C) reporting categories

No hazard categories applicable.

U.S. State Regulations

The following components appear on one or more of the following state hazardous substances lists:

Component	CAS	CA	MA	MN	NJ	PA
Distillates, petroleum, hydrotreated light paraffinic	64742-55-8	No	Yes	No	No	No
Paraffin oils, petroleum, catalytic dewaxed heavy	64742-70-7	No	Yes	No	No	No

California Safe Drinking Water and Toxic Enforcement Act (Proposition 65)

Not listed under California Proposition 65.

Material Name: NGEO 15W-40 NGP3

SDS ID: 820423

Component Analysis - Inventory

Lubricating oils, petroleum, hydrotreated spent (64742-58-1)

Eubin	Lubricating oils, petroleum, hydrotreated spent (64/42-58-1)											
US	CA	AU	CN		EU	J	JP - ENCS	JP - ISHL		KR KECI - Annex 1	KR KECI - Annex 2	
Yes	DSL	Yes	Yes EIN No No			Yes	No					
KR - REACH CCA MX NZ					NZ	РН	TH- TECI TW		VN (Draft)			
No Yes Yes						Yes	Yes	No	Yes	Yes		
Distillates, petroleum, solvent-dewaxed heavy paraffinic (64742-65-0)												
				CN E		IJ	JP - ENCS	JP - ISHL		KR KECI - Annex 1	KR KECI - Annex 2	
Yes	DSL	Yes	Y	es	EI	N	No	No		Yes	No	
KR -	KR - REACH CCA			MX		NZ	РН	TH- TECI TW		VN (Draft)		
No	No Yes Yes						Yes	No	Yes	Yes		
Distill	ates, pe	troleu	m,	hyċ	dro	treate	d heavy par	affinic (647	42-54	-7)	·	
US CA AU C			C	CN EU		J	JP - ENCS	JP - ISHL		KR KECI - Annex 1	KR KECI - Annex 2	
Yes	DSL	Yes	Yes EIN		N	Yes	Yes		Yes	No		
KR -	KR - REACH CCA			MX		NZ	РН	TH- TECI TW		VN (Draft)		
No				Yes		Yes	Yes	No	Yes	Yes		
Distill	ates, pe	troleu	m,	hyċ	dro	treate	d light para	ffinic (6474	2-55-8	3)	' 	
US CA AU C			N EU		J	JP - ENCS	JP - ISHL		KR KECI - Annex 1	KR KECI - Annex 2		
Yes	DSL Yes Y		Yes E		EI	N	Yes	Yes		Yes	No	
KR -	KR - REACH CCA MX			X	NZ	РН	TH- TECI	TW	VN (Draft)			
No No					0	Yes	Yes	No Yes		Yes		

Material Name: NGEO 15W-40 NGP3

SDS ID: 820423

US	CA	AU	I CN II EU II		KR KECI - Annex 1	KR KECI - Annex 2							
Yes	DSL	Yes	Ye	Yes E		Yes		1	No	No		Yes	No
KR - REACH CCA		MX		X 1	NZ	РН	TH- TECI TW		VN (Draft)				
No	No			Nc) '	Yes	Yes	No Yes Yes		Yes			
Phosp	Phosphorodithioic acid, mixed O,O-bis(sec-butyl and isooctyl) esters, zinc salts (113706-15-3)												
US	CA AU CI		CN	N	EU		JP - ENCS	JP - ISHL		KR KECI - Annex 1	KR KECI - Annex 2		
Yes	DSL	Yes	Yes		Yes		No		Yes	Yes		No	No
KR - REACH CCA			A	M	X NZ PH		РН	TH- TECI	TW	VN (Draft)			
No			No Yes			Yes	No	No	Yes	Yes			

Paraffin oils, petroleum, catalytic dewaxed heavy (64742-70-7)

Section 16 - OTHER INFORMATION

NFPA Ratings

Health: 1 Fire: 1 Instability: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

Summary of Changes

New Issue SDS

Key / Legend

ACGIH - American Conference of Governmental Industrial Hygienists; ADR - European Road Transport; AU - Australia; BOD - Biochemical Oxygen Demand; C - Celsius; CA - Canada; CA/MA/MN/NJ/PA -California/Massachusetts/Minnesota/New Jersey/Pennsylvania*; CAS - Chemical Abstracts Service; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CFR - Code of Federal Regulations (US); CLP - Classification, Labelling, and Packaging; CN - China; CPR - Controlled Products Regulations; DFG - Deutsche Forschungsgemeinschaft; DOT - Department of Transportation; DSD - Dangerous Substance Directive; DSL - Domestic Substances List; EC - European Commission; EEC -European Economic Community; EIN - European Inventory of (Existing Commercial Chemical Substances); EINECS - European Inventory of Existing Commercial Chemical Substances; ENCS - Japan Existing and New Chemical Substance Inventory; EPA - Environmental Protection Agency; EU - European Union; F -Fahrenheit; F - Background (for Venezuela Biological Exposure Indices); IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; ICAO - International Civil Aviation Organization; IDL - Ingredient Disclosure List; IDLH - Immediately Dangerous to Life and Health; IMDG -International Maritime Dangerous Goods; ISHL - Japan Industrial Safety and Health Law; IUCLID -International Uniform Chemical Information Database; JP - Japan; Kow - Octanol/water partition coefficient; KR KECI Annex 1 - Korea Existing Chemicals Inventory (KECI) / Korea Existing Chemicals List (KECL); KR KECI Annex 2 - Korea Existing Chemicals Inventory (KECI) / Korea Existing Chemicals List (KECL), KR - Korea; LD50/LC50 - Lethal Dose/ Lethal Concentration; KR REACH CCA - Korea Registration and Evaluation of Chemical Substances Chemical Control Act; LEL - Lower Explosive Limit; LLV - Level Limit Value; LOLI - List Of LIstsTM - ChemADVISOR's Regulatory Database; MAK -

Material Name: NGEO 15W-40 NGP3

Maximum Concentration Value in the Workplace; MEL - Maximum Exposure Limits; MX – Mexico; Ne-Non-specific; NFPA - National Fire Protection Agency; NIOSH - National Institute for Occupational Safety and Health; NJTSR - New Jersey Trade Secret Registry; Nq - Non-quantitative; NSL – Non-Domestic Substance List (Canada); NTP - National Toxicology Program; NZ - New Zealand; OSHA - Occupational Safety and Health Administration; PEL- Permissible Exposure Limit; PH - Philippines; RCRA - Resource Conservation and Recovery Act; REACH- Registration, Evaluation, Authorisation, and restriction of Chemicals; RID - European Rail Transport; SARA - Superfund Amendments and Reauthorization Act; Sc -Semi-quantitative; STEL - Short-term Exposure Limit; TCCA – Korea Toxic Chemicals Control Act; TDG -Transportation of Dangerous Goods; TH-TECI - Thailand - FDA Existing Chemicals Inventory (TECI); TLV - Threshold Limit Value; TSCA - Toxic Substances Control Act; TW – Taiwan; TWA - Time Weighted Average; UEL - Upper Explosive Limit; UN/NA - United Nations /North American; US - United States; VLE - Exposure Limit Value (Mexico); VN (Draft) - Vietnam (Draft); WHMIS - Workplace Hazardous Materials Information System (Canada).

Other Information

Disclaimer:

User assumes all risks incident to the use of this product. To the best of our knowledge, the information contained herein is accurate. However, Safety-Kleen assumes no liability whatsoever for the accuracy or completeness of the information contained herein. No representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose or of any other nature are made hereunder with respect to the information or the product to which the information refers. The data contained on this sheet apply to the product as supplied to the user.